

SEMICONDUCTOR PRODUCTS

SHORT FORM CATALOG



2022

JSC "INTEGRAL" - Holding Management Company reserves the right to make changes in device design, specifications and other information identified in this publication without notice and assumes no responsibility for the use of any device described herein.

JSC "INTEGRAL" - Holding Management Company advises its customers to obtain the latest version of relevant information to verify before placing orders, that the information being relied upon is current.

Reference to products of other manufacturers are solely for convenience and do not imply total equivalency of design, performance, or otherwise.

CONTENTS

Introduction	5
Quality	6
Integrated Circuits	7
Microcontrollers, Drivers, Peripherals IC	8
Display Driver IC	8
LED Driver Circuits	8
Interface Integrated Circuits (Reference Data)	9
Real Time Clock	9
Real Time Clock (Reference Data)	10
TV and Audio IC	11
IC for Audio Systems	11
IC for Audio Systems (Reference Date)	12
Telecommunications IC	13
Switches and DTMF Receivers	13
Pulse and Tone/Pulse Dialers	13
Single Chip Telephone IC	14
Speaker Integrated Circuits	14
Tone Telephone Ringers	15
IC for Smart Cards	16
IC for Systems of Identification	16
Power Electronics, Standard Analog IC	18
IC for Control and Power Electronics	18
Automotive	19
Timers	20
Comparators	20
Comparators (Reference Data)	20
Timers (Reference Data)	21
Operational Amplifiers	22
Operational Amplifiers (Reference Data)	22
µp Supervisory Circuits	23
µp Supervisory Circuits (Reference Data)	23
Voltage Regulators	23
Precision Low Voltage Reference	25
Switching Regulators (Reference Data)	26
PWM Controllers	26
Voltage Detectors	26
Voltage Regulators (Reference Data)	27
Standard Digital Logic IC	29
IW4000A series	29
IW4000B series	29
IN74ACXXXX series	31
IN74ACTXXXX series	32
INT4VHCXXX series	33
INT4VHCTXXX series	33
IN74HCXXXX series	34
IN74HCTXXX series	35
IN74LVXXX series	36
IN74XXX series	37
IN74LSXXX series	37
N74ALSXXXX series	37
Functional selection	40
Family Characteristics	45
Clock/Watch IC/Electronic Thermometer IC	48
CMOS IC for LCD Wrist-Watches and Clocks	48
Digital watch	48
Analog clock	48
Electronic Thermometer IC	48
Melody IC	49
Voltage Control Oscillator (VCO) IC	49
Discrete Semiconductors	50
Transistors, Diodes, Diode Arrays	51
Power N-Channel MOSFETs	51
Fast (Ultrafast) Rectifying Diode (FRD, UFRD)	52
Bipolar Transistors	52
Unijunction Transistors	52

Power Thyristors and Triacs.....	52
Foundry-business	53
Contacts.....	54

INTRODUCTION

JSC "INTEGRAL" – Holding Management Company develops, manufactures and exports microelectronic components and electronic products. JSC "INTEGRAL" – Holding Management Company provides a full cycle of design and manufacture: from silicon substrates up to integrated circuits and semiconductor devices, from microelectronic components up to electronic.

Total labour is more than 6 thousand persons.

Mr. Vitaly A. Solodukha has been the General Director of JSC "INTEGRAL" – Holding Management Company.

The main line of activity of JSC "INTEGRAL" – Holding Management Company is design and manufacture of microelectronic products - over 70 % of the total production volume - for the branches manufacturing goods of household and consumer electronics.

JSC "INTEGRAL" – Holding Management Company exports more than 70 % of the volume of manufactured goods to the markets of the Russian Federation, South-East Asia, India and Western Europe.

The goods are exported to 30 countries of the world.

Manufacture of 0,35 μm design rule integrated circuits on Ø200 mm (8 inch) wafers has been set up.

The main lines of the development of JSC "INTEGRAL" – Holding Management Company – Holding Management Company are as follows: design and implementation of microelectronic components of power electronics, microsensorics and optoelectronics.

Development of production of finished electronics is to be carried out in the following lines: displays; automotive electronics and electronics and equipment for health application; cashless payment systems, payment terminals, commercial and bank equipment, smart cards, identification and record keeping systems.

JSC "INTEGRAL" – Holding Management Company is open for cooperation both in design and deliveries of products, and in terms of joint realization of long-term investment projects.

• BASIC TYPES OF INTEGRATED CIRCUITS MANUFACTURED:

- Memories
- Microcontrollers, drivers, - Standard digital logic IC
- peripheral IC*
- TV and audio IC
- Telecommunications IC
- Power electronics, standard analog IC
- Special-purpose electronic component base
- Clock/watch, calculator IC
- Music synthesizer and electronic thermometer

• BASIC TYPES OF SEMICONDUCTOR DEVICES MANUFACTURED:

- Bipolar transistors
- Power bipolar Darlington transistors
- Insulated gate bipolar transistors
- Bipolar transistors with integrated anti-saturating element
- Bipolar transistors with damping diode and resistor in the emitter-base circuit
- Unijunction bipolar transistors
- Low-power n- and p-channel MOSFETs

- Power n- and p-channel MOSFETs
- Microwave mixing diodes, rectifier diodes, Schottky diodes
- Power high-speed diodes and diode matrices
- Pulse diode matrices
- Power rectifier and limiter diodes



INTEGRATED CIRCUITS

INTEGRATED CIRCUITS

Microcontrollers, Drivers, Peripherals IC

• Display Driver IC

Part	Pin to Pin Compatibility	Supply Voltage, Ucc,V	LCD Voltage, V	Duty	RAM	Column Lines	Co m- mon Line s	Fre-quency, kHz	Pins (Pads)	Notes
LCD Controllers and Drivers										
IZ6570AA	NJU6570AA SED1520DAA	2.4...5.5	2.4...13	1/16 1/32	80x32	61	16	2	(100)	Chip
IZ6570OA	NJU6570OA SED1520DOA	2.4...5.5	2.4...13	1/16 1/32	80x32	61	16	18	(100)	Chip
IZ6450	NJU6450A	2.4...5.5	3.5...10	1/16 1/32	80x32	61	16	18	(100)	Chip
IZ6451	NJU6451A	2.4...5.5	3.5...10	1/16 1/32	80x32	72	8	18	(100)	Chip
IZ7065	KS0065	2.7...5.5	3...13	1/8 1/16		40		max400	(59)	Chip
IZ7066	KS0066	4.5...5.5	3...13	1/8 1/11 1/16	80x8	40	16	350	(80)	Chip
IZ602	FL602 HT1621	2.4...5.5	2.4...Ucc	1/2 1/3 1/4	32x4	32	4	256	(48)	Chip

• LED Driver Circuits

Part	Pin to Pin Compatibility	Function	Package	
IL9910N IL9910D IL9910DH IZ9910	HV9910	Universal High Brightness LED Driver, 1A	DIP-8 SO-8 SO-16 Chip	
IZ9921 IZ9922 IZ9922A IZ9923	HV9921 HV9922 -	20mA/50mA/30mA Switch-Mode LED Driver IC	Chip	
IZ7150 IZ7150A	AMC7150			
IL3361AD IL3361BD IZ3361	HV9961	Power LED Driver, 1,5 A	Chip	
IL3367D IZ3367		Power LED Driver, 0,8 A		
IL3367D IZ3367	HV9967	High-stable LED-driver IC; 8 V÷450 V supply voltage	SO-8 SO-16 -	
IZ33120 IZ3302		120mA LED Driver IC with built-in MOSFET, 8 V÷450 V input voltage		
IZR402U IZR402R	BCR402	Universal High Brightness LED Driver, 1A	Chip	
		Constant current LED-driver; 42 V supply voltage; 18.6 V output voltage; LED-driver current: 22 mA up to 65 mA with external resistor		
		Constant current LED-driver; 60 V supply voltage; 38.6 V output voltage; LED-driver current: 22 mA up to 65 mA with external resistor		

• **Interface Integrated Circuits** (Reference Date)

Parameter	IL75232N IL75232DW	ILX202N ILX202D	ILX207N ILX207DW	ILX208N ILX208D	ILX232N ILX232D	ILX485N ILX485D	ILX3221N	ILX3226N	ILX3232N ILX3232D	ILX3483N	ILX3485N	ILX3486N
ESD Voltage (kV)	0.5	2	2	2	2	4	4	4	4	4	4	4
Power Supply Voltage (V)	±9...±15 for TX 5 for RX	4.5...5.5	4.75...5.25	4.5...5.5	4.5...5.5	4.75...5.25	3...5.5	3...5.5	3...5.5	3...3.6	3...3.6	3...3.6
No. of TX/RX	3/5	2/2	5/3	4/4	2/2	1/1	1/1	1/1	2/2	1/1	1/1	1/1
No. of TX/RX on Bus						32						
Supply Current (mA)	30	10	20	20	10	0.9	0.001	0.001	1	0.001	0.001	0.001
Standard	RS-232 RS-485/RS-422	•	•	•	•	•	•	•	•	•	•	•
AutoShutdown Plus, AutoShutdown						•	•					
Date Rate (bps)		64K	120K	120K	120K	2.5M	250K	250K	120K	250K	12M	2.5M
External Caps (µF)		4x0.1	4x0.1	4x0.1	4x1.0		4x0.1	4x0.1	4x0.1	-	-	-
Operating Temperature Range (°C)	0 ÷ +75						-40 ÷ +85					

• **Real Time Clock**

Part	Pin to Pin Compatibility	Function	Package
Digital timers			
IN1307N IN1307D	DS1307N/ZN	64 x 8 Serial Real Time Clock	DIP-8 SO-8
IN1356D	M41T56	512 bit (64 bit x 8) Serial Access Timekeeper SRAM	SO-8
IN1363D	PCF8563	Real Time Clock / Calendar	SO-8



INTEGRATED CIRCUITS

Microcontrollers, Drivers, Peripherals IC

• Real Time Clock (Reference Date)

Parameter	Symbol	IN1307N/D	IN1356D	IN1363D	
Supply Voltage, Ucc	V	4.5....5.5	4.5....5.5	1.8....5.5	
Battery Supply Voltage, VBAT	V	2.0....3.5	2.5....3.5		
Standby Current, Iccs (max)	µA	200	100 (typ)	0.55	
Active Supply Current, IccA, (max)	µA	1500	300	800	
Battery Current, IBAT1 (max)	nA	500	550		
Clock Frequency, fscl (max)	kHz	100	100	400	
Programmable Signal	Hz	1; 4096; 8192; 32768	512	1; 32; 1024; 32768	
Operating Temperature, TA	°C		- 40 ÷ + 85		
Functions	clock	seconds	•	•	
		minutes	•	•	
		hours	•	•	
		alarm		•	
	calendar	weekday	•	•	
		date of the month	•	•	
		month	•	•	
		years	•	•	
		century		•	
programmable alarm, timer and interrupt function				•	
software clock calibration			•		
automatic power-fail detect and switch circuitry		•	•		
interface		I ² C	I ² C	I ² C	

• IC for Audio Systems

Part	Pin to Pin Compatibility	Function	Features	Package
IL34119N IL34119D	MC34119	0.25 W Low Power Mono Audio Amplifier	<ul style="list-style-type: none"> <input type="checkbox"/> Vcc=2...16 V <input type="checkbox"/> Low Quiescent Supply Current for Battery Powered Applications <input type="checkbox"/> Chip Disable Input to Power Down the IC <input type="checkbox"/> Drives a Wide Range of Speaker Loads (8-100 Ω) <input type="checkbox"/> Output Power Exceed 250 mW with 32 Ω Speaker <input type="checkbox"/> Gain Adjustable from 0 dB to 46 dB for Voice Band <input type="checkbox"/> Requires Few External Components 	DIP-8 SO-8
IL386N IL386D	LM386	1 W Low Power Mono Audio Amplifier	<ul style="list-style-type: none"> <input type="checkbox"/> Vcc=4...12 V <input type="checkbox"/> Battery Operation <input type="checkbox"/> Low Quiescent Current Drain: 4 mA <input type="checkbox"/> Voltage Gains from 20 to 200 dB <input type="checkbox"/> Ground Referenced Input <input type="checkbox"/> Self-Centering Output Quiescent Voltage <input type="checkbox"/> Low Distortion 	DIP-8 SO-8
ILA7056B	TDA7056B	5 W Mono BTL Audio Amplifier with DC Volume Control	<ul style="list-style-type: none"> <input type="checkbox"/> Vcc=4.5...18 V <input type="checkbox"/> DC volume control <input type="checkbox"/> Few external components <input type="checkbox"/> Mute mode <input type="checkbox"/> Thermal protection <input type="checkbox"/> Short-circuit proof <input type="checkbox"/> No switch-on and off clicks <input type="checkbox"/> Low HF radiation <input type="checkbox"/> Low power consumption 	SIL-9MPF
ILA7496Q	TDA7496Q	2 x 5 W Stereo Power Amplifier with linear volume adjustment	<ul style="list-style-type: none"> <input type="checkbox"/> Vcc=11...35 V <input type="checkbox"/> DC volume control <input type="checkbox"/> Few external components 	SIL-15P

INTEGRATED CIRCUITS

TV and Audio IC

• IC for Audio Systems (Reference Data)

IC's Class	Part	Pin to Pin Compatibility	Supply Voltage, V	Maximum Power, W	Gain, dB	Load resistance, Ω	Package
Low Power	IL34119N, D Mono	MC34119	2.0...16.0	0.25	80	8; 16; 32	DIP-8, SO-8
	IL386N, D Mono	LM386	4.0...12.0	1.0	26...42	8.0 (4.0; 16)	DIP-8, SO-8
Middle Power	ILA7056B Mono with DC Control	TDA7056B	4.5...18.0	5.0	39.5...41.5	16.0	SIL-9MPF
Large Power	ILA7496Q Stereo with Linear Volume Adjustment	TDA7496Q	10.0...32.0	2x5	28.5...31.5	8.0	SIL-15P

• DTMF Receivers

Part	Pin to Pin Compatibility	Function	Features	Package
IL9170N IL9170DW	HM9170	DTMF Receiver	<input type="checkbox"/> Vcc=2.5...5.5 V <input type="checkbox"/> Icc max=9.0 mA <input type="checkbox"/> Power consumption 15 mW <input type="checkbox"/> Quartz generator 3.58 MHz <input type="checkbox"/> Decoding of 16 DTMF tones-pairs <input type="checkbox"/> 4-bit parallel output <input type="checkbox"/> PWDN	DIP-18 SO-18

• Pulse and Tone/Pulse Dialers

Part	Pin to Pin Compatibility	Function	Features	Package
IL91531N	UM91531	Parallel Input Tone/Pulse Dialer	<input type="checkbox"/> Vcc=2.5...5.5 V <input type="checkbox"/> Quartz generator 3.58 MHz <input type="checkbox"/> Output signal: pulse 10 Hz or DTMF <input type="checkbox"/> 4-bit parallel data input from microcomputer <input type="checkbox"/> Selectable Make/Break ratio <input type="checkbox"/> Inter digital pause 800 ms	DIP-16
IL91214AN IL91214AD	UMS91214A	Tone/Pulse Dialer with Handfree Control and Flash Function	<input type="checkbox"/> Vcc=2.0...5.5 V <input type="checkbox"/> Quartz generator 3.58 MHz <input type="checkbox"/> 32-digit redial memory <input type="checkbox"/> Tone/Pulse switchable <input type="checkbox"/> Output signal: pulse 10 Hz(20Hz) or DTMF <input type="checkbox"/> Flash Function <input type="checkbox"/> 4x4 keyboard <input type="checkbox"/> 09 - mode output pin (IL91214BN/BDW) <input type="checkbox"/> 10 – key in tone output (IL91214BN/BDW)	DIP-16 SO-16

INTEGRATED CIRCUITS

Telecommunications IC

• Single Chip Telephone IC

Part	Pin to Pin Compatibility	Function	Features	Package
IL2533N IL2533DW	AS2533	Multi-Standart CMOS Single Chip Telephone IC with Dual Soft Clipping	<ul style="list-style-type: none"> □ Line/speech circuit, LD/MF repertory dialler and tone ringer on one 28 pin CMOS chip □ Operating range from 13 to 100 mA (down to 5mA with reduced performance) □ Soft clipping to avoid harsh distortion □ Volume control of receive signal □ Line loss compensation selectable by pin option □ Low noise (max. - 72 dBmp) □ Real or complex impedance □ NET 4 compatible. □ LD/MF switchable dialling □ Pacifier tone during programming □ 31 digit last number redial □ Sliding cursor protocol with comparison □ Pause key for access pause or wait function □ 3 flash keys, 100 ms, 280 ms and 375/600 ms □ On chip MF filter (CEPT CS 203 compatible) □ Ring frequency discrimination □ 3-tone melody generator □ Oscillator Frequency (Resonator: Murata CSA 3.58MG312AM)-3.58 MHz □ 4x4...4x8 Keyboard 	DIP-28 SO-28

• Speaker Integrated Circuits

Part	Pin to Pin Compatibility	Function	Features	Package
IL34118N IL34118DW	MC34118	Voice Switched Speakerphone Circuit	<ul style="list-style-type: none"> □ Ucc=3.0...6.5 V □ Icc=5.0 mA □ Improved Attenuator Gain Range: 52 dB Between Transmit and Receive □ Low Voltage Operation for Line-Powered Applications (3.0-6.5 V) □ 4-Point Signal Sensing for Improved Sensitivity □ Background Noise Monitors for Both Transmit and Receive Paths □ Microphone Amplifier Gain Set by External Resistors – Mute Function Included □ Chip Disable for Active/Standby Operation □ On Board Filter Pinned-Out for User Defined Function □ Dial Tone Detector to Inhibit Receive Idle Mode During Dial Tone Presence □ Standard 28-Pin Plastic Dip Package and SOIC Package Available □ Compatible with IL34119 Speaker Amplifier 	DIP-28 SO-28
IL34119N IL34119D	MC34119	Telephone Audio Amplifier	<ul style="list-style-type: none"> □ Vcc=2.0...16.0 V □ Icc=2.7 mA □ Drives a wide range of speaker loads (8...100 Ω) □ Output power exceeds 250 mW with 32 Ω Speaker □ Low total harmonic distortion □ Gain adjustable 0...46 dB for voice band □ Requires few external components 	DIP-8 SO-8

• Speaker Integrated Circuits (continued)

Part	Pin to Pin Compatibility	Function	Features	Package
IL3726/18N IL3726/18DW	PBL3726/18	Speaker Integrated Circuit	<ul style="list-style-type: none"> <input type="checkbox"/> $V_{LN}=3.3\ldots 4.1$ V ($I_L=15$ mA) <input type="checkbox"/> $V_{LN}=11.0\ldots 15.0$ V ($I_L=100$ mA) <input type="checkbox"/> 7 Capacitors & Resistors <input type="checkbox"/> Low Voltage Operating <input type="checkbox"/> DTMF signal input with confidence tone <input type="checkbox"/> Mute input for DTMF dialing <input type="checkbox"/> Line loss compensation (line current dependent) for microphone and earpiece amplifiers <input type="checkbox"/> Gain control curve adaptable to exchange supply <input type="checkbox"/> DC line voltage adjustment facility 	DIP-18 SO-20
ILA1062AN ILA1062AD ILA1062N ILA1062D	TEA1062A TEA1062	Low Voltage Transmission Circuit with Dialer Interface	<ul style="list-style-type: none"> <input type="checkbox"/> Low DC line voltage; operates down to 1.6 V <input type="checkbox"/> Line operation current range 10...140 mA <input type="checkbox"/> $I_{CC} \leq 1.35$ mA <input type="checkbox"/> Voltage gain range: microphone amplifier 11...52 dB telephone amplifier 20...31 dB <input type="checkbox"/> Voltage regulator with adjustable static resistance <input type="checkbox"/> Provides supply for external circuits <input type="checkbox"/> Symmetrical high-impedance inputs <input type="checkbox"/> (64 kΩ) for dynamic, magnetic or piezoelectric microphones <input type="checkbox"/> Asymmetrical high-impedance inputs (32 kΩ) for electret microphones <input type="checkbox"/> DTMF signal input with confidence tone <input type="checkbox"/> Mute input for pulse or DTMF dialing <input type="checkbox"/> Receiving amplifier for dynamic, magnetic or piezoelectric earpieces <input type="checkbox"/> Large gain setting range on microphone and earpiece amplifiers 	DIP-16 SO-16 DIP-16 SO-16

• Tone Telephone Ringers

Part	Pin to Pin Compatibility	Function	Features	Package
IL2418N IL2418D	KA2418	Two-Tone Telephone Ringer with Diode Bridge	<ul style="list-style-type: none"> <input type="checkbox"/> $V_{CC}=26$ V <input type="checkbox"/> I_{CC} max=1.8 mA <input type="checkbox"/> Activation voltage 12.2...13 V <input type="checkbox"/> Sustaining voltage 8.0...8.8 V <input type="checkbox"/> Internal Zener diodes to protect against over voltages <input type="checkbox"/> High noise immunity due to built-in voltage-current hysteresis <input type="checkbox"/> Ringer impedance adjustable with external components <input type="checkbox"/> Output $F_1=2100\ldots 2550$ Hz $F_2=1500\ldots 1850$ Hz 	DIP-8 SO-8

INTEGRATED CIRCUITS

Telecommunications IC

• IC for Smart Cards (continued)

Part	Pin to Pin Compatibility	Function	Features	Pads
IZ2815A-03	SLE4436E	IC for Prepaid Cards	<ul style="list-style-type: none"><input type="checkbox"/> Vcc=4.5...5.5 V<input type="checkbox"/> Icc=5 mA<input type="checkbox"/> 221-bit EEPROM and 16 bit mask-programmable ROM<input type="checkbox"/> 104 bit user memory fully compatible with IZ4406:<ul style="list-style-type: none">- 64 bit identification area- 40 bit counter area including 1 bit for personalization<input type="checkbox"/> 133 bit additional memory for advanced features<ul style="list-style-type: none">- 4 bit counter backup (anti-tearing flags)- 1 bit initiation flag for authentication key 2- 16 bit data area 1 for free user access- 48 bit authentication key 1- either 64 bit data area 1 for user defined data or 48 bit authentication key 2<input type="checkbox"/> EEPROM programming time 5 ms<input type="checkbox"/> Endurance minimum of 100000 write/erase cycles per bit<input type="checkbox"/> Data retention for minimum of 10 years<input type="checkbox"/> Contact configuration and serial interface in accordance to ISO standard 7816-3	5

• IC for identification systems

Part	Pin to pin compatibility	Function	Features	Pads
IZ2806	H4102, H4100	Amplitude-modulated transponder IC	<ul style="list-style-type: none"><input type="checkbox"/> For non-contact plastic card<input type="checkbox"/> Operating frequency range: 100 ... 150 kHz<input type="checkbox"/> ROM information capacity: 64 bit<input type="checkbox"/> External inductor AC voltage value: 3min and 15 max<input type="checkbox"/> Data retention with the power off: 5 years min	5
IZ2803	ATA5567	Read / write transponder IC	<ul style="list-style-type: none"><input type="checkbox"/> For non-contact plastic card<input type="checkbox"/> Operating frequency range: 100 ... 150 kHz<input type="checkbox"/> ROM information capacity: 64 bit<input type="checkbox"/> External inductor AC voltage value: 3min and 15 max<input type="checkbox"/> Data retention with the power off: 5 years min	4
IZ2805	RI-TRP-W9QL	Read / write transponder IC	<ul style="list-style-type: none"><input type="checkbox"/> Operating frequency: 134,2 kHz<input type="checkbox"/> ROM capacity: 80 bit<input type="checkbox"/> Frequency modulation<input type="checkbox"/> Complies with ISO 11784/785	4

• **IC for identification systems** (continued)

Part	Pin to pin compatibility	Function	Features	Pads
IZ1990	DS1990A	1-Wire interface electronic key IC	<ul style="list-style-type: none"> □ Power supply: 2.8 – 6.0 V □ Unique 64 bite code 	2
IZ1991	DS1991	1-Wire interface and increased security level electronic key IC	<ul style="list-style-type: none"> □ Power supply: 2.8 – 6.0 V □ Unique 64 bite code □ 3 memory blocks, 384 bit each □ Scratch-pad memory: 512 bit 	2
IZ2009-01 IZ2009-02	DS1990	1-Wire interface and increased security level electronic key IC	<ul style="list-style-type: none"> □ Power supply: 2.8 – 6.0 V □ Unique 64 bite code 	2
IZ1961	DS1961	Secret controller IC for private key access systems	<ul style="list-style-type: none"> □ 64 bit EEPROM □ 512 bit SHA block □ 64 bit scratch-pad □ Security code memory: 64 bit □ Data EEPROM: 1024 bit □ Register page: 64 bit □ CRC16 generator 	2

INTEGRATED CIRCUITS

Power Electronics, Standard Analog IC

• IC for Control and Power Electronics

Part	Pin to Pin Compatibility	Function	Package
IL33035N IL33035DW	MC33035	Brushless DC Motor Controller	DIP-24 SO-24
IL33153PN	MC33153P	Single IGBT Gate Driver	DIP-8
IL33262N IL33262D	MC33262	Power Factor Controller ($T_A = -40...+105^\circ\text{C}$)	DIP-8 SO-8
IL34262N IL34262D	MC34262	Power Factor Controller	DIP-8 SO-8
IL6562D	L6562		SO-8
IL6562N	L6562	Power Factor Controller	DIP-8
IL7101N/AN/BN IL7101D/AD/BD	GL7101	Earth Leakage Current Detector ($U_T = 4..9 \text{ mV}$ for AN) ($U_T = 9..18 \text{ mV}$ for N/D)	DIP-8 DIP-8 SO-8
IL4145AN	RV4145A	Low Power Ground Fault Interrupter	DIP-8
ILN2003AN	ULN2003A	High-Voltage High-Current Darlington Transistor Arrays	DIP-16
ILN2004AN ILN2004AD	ULN2004A	High-Voltage High-Current Darlington Transistor Arrays	DIP-16 SO-16
ILN62083N ILN62083D	TD62083AFN	8CH Darlington Sink Driver	DIP-18 SO-18
ILN62084N ILN62084D	TD62084AFN		DIP-18 SO-18
ILN62783N ILN62783D	TD62783AFN		DIP-18 SO-18
ILN62784N ILN62784D	TD62784AFN		DIP-18 SO-18

Part	Topr (°C)	I_{OUT} (max) (mA)	V_{CE} (max) (V)	I_{IN} (max) (mA)	V_{IN} (max) (V)	V_F / V_R (max) (V/V)	Designation	Package
7CH High-Voltage Drivers								
ILN2003AN	- 20 ÷ +85	500	50	1.35	30	2/50	TTL, 5V CMOS	DIP-16
ILN2004AN ILN2004AD	- 20 ÷ +85	500	50	1.35	30	2/50	6 ~ 15V PMOS, CMOS	DIP-16 SO-16
8CH High-Voltage Drivers								
ILN62083N ILN62083D	- 40 ÷ +85	500	50	1.35	30	2/50	TTL, 5V CMOS	DIP-18 SO-18
ILN62084N ILN62084D	- 40 ÷ +85	500	50	0.50	30	2/50	6 ~ 15V PMOS, CMOS	DIP-18 SO-18
ILN62783N ILN62783D	- 40 ÷ +85	-500	50	0.26	30	2/50	TTL, 5V CMOS	DIP-18 SO-18
ILN62784N ILN62784D	- 40 ÷ +85	-500	50	0.13	30	2/50	6 ~ 15V PMOS, CMOS	DIP-18 SO-18

• Automotive

Part	Pin to Pin Compatibility	Function	Package
IL33193N IL33193D	MC33193	Automotive Direction Indicator $R_S=20\text{ m}\Omega$, $F_n=2.2$, Duty Cycle (Normal Operation) 45±55%, Duty Cycle (One 21 W Lamp Defect) 35±45%, Defect Lamp Detector Threshold 42.5±56 mV, $R_{SS}=220\text{ }\Omega$	DIP-8 SO-8
IL33193N-03 IL33193D-03	UEA1041B	Automotive Direction Indicator $R_S=30\text{ m}\Omega$, $F_n=2.5$, Duty Cycle (Normal Operation) 45±55%, Duty Cycle (One 21 W Lamp Defect) 35±45%, Defect Lamp Detector Threshold 75±95 mV, $R_{SS}=220\text{ }\Omega$, Short Circuit Detector Threshold	DIP-8 SO-8
IL33197AN IL33197AD	MC33197A	Automotive Wash Wiper Timer Output Clamp Voltage ($I_{out}=20\text{ mA}$) 19.5±22 V, Internally incorporated Zener diode 20 V	DIP-8 SO-8
IL6083N IL6083N-01	U6083B	Power Control With Interference Suppression (for N-01: Duty cycle 10... 100%, $V_{S1}=24.5\text{...}28.0\text{ V}$, $V_{S2}=18.5\text{...}22.0\text{ V}$, $V_{Batt1}=16.7\text{...}21.0\text{ V}$ (switched on), $V_{Batt1}=18.3\text{...}22.5\text{ V}$ (switched off), $V_{TS}=10.1\text{...}10.7\text{ V}$, $I_S=5\text{...}17\text{ mA}$)	DIP-8
IN9014N		For light control relay IC	DIP-8
IL8190N IL8190DW	CS8190ENF16 CS8190EDWF20	Precision Air-Core Tach/Speedo Driver with Return to Zero	DIP-16 SO-20
IL33290AD	MC33290	ISO K Line Serial Link Interface	SO-8
ILA82C251D	PCA82C251T	CAN transceiver for 24 V systems	SO-8
IN2515/AN/ADW/BN/BDW	MCP2515	CAN Controller	SO-18
IL33091AN IL33091AD	MC33091A	High-Side MOS Driver	DIP-8 SO-8
ILE4250GS	TLE4250G	Low-Drop Voltage Tracker (2±36 V); 50 mA: Reverse Polarity Protection	P-TO-263-5-1 TO-220AB/5
ILE4260 ILE4260-2	TLE4260	Low-Drop Voltage Regulator 5 V; 500 mA; Reverse Polarity Protection	P-TO-220-5-12
ILE4264G IZE4264-2	TLE4264G TLE4264-2G	Low-Drop Voltage Regulator 5 V; 100 mA; Reverse Polarity Protection	P-SOT223-4-1 Chip
ILE4266G IZE4266-2	TLE4266G TLE4266-2G	Low-Drop Voltage Regulator 5 V; 100 mA; Reverse Polarity Protection	P-SOT223-4-2 Chip
ILE4267G ILE4267S	TLE4267G TLE4267S	Low-Drop Voltage Regulator 5 V; 400 mA; Reverse Polarity Protection	P-TO-220-7-180 P-TO-220-7-230
ILE4268GDW	TLE4268G	Low-Drop Voltage Regulator 5 V; 150 mA; Reverse Polarity Protection	P-DSO-20-6
ILE4270G ILE4270S ILE4270Q IL4270	TLE4270G TLE4270S	Low-Drop Voltage Regulator 5 V; 550 mA; Reverse Polarity Protection IL4270 - without "RESET"	P-TO-263-5-1 P-TO-220-5-12 P-TO-220-5-11 TO-220AB/3
ILE4271G ILE4271S	TLE4271G TLE4271S	Low-Drop Voltage Regulator 5 V; 550 mA; Reverse Polarity Protection	P-TO-220-7-180 P-TO-220-7-230
ILE4274V50/V85/V10	TLE4274	Low-Drop Voltage Regulator 5 V/8.5 V/10 V; 400 mA: Reverse Polarity Protection	TO-220AB/3
ILE4275G/S	TLE4275G	Low-Drop Voltage regulator 5 V; 400 mA: Reverse Polarity Protection	P-TO-263-5-1 TO-220AB/5
ILE4276VG/VS/V50G/V50S/V85G/V85S/V10S	TLE4276	Low-Drop Voltage Regulator 5 V/8.5 V/10 V; 400 mA: Reverse Polarity Protection	P-TO-263-5-1 TO-220AB/5
IZE4278	TLE4278	Low-Drop Voltage Regulator 5 V; 150 mA: Reverse Polarity Protection	Chip
IZ4206	TLE4206G	1 A DC Motor Driver for Serve Driver Applications	Chip
IZE4263	TLE4263	LDO Regulator 5 V; 150 mA	Chip
IZE4279	TLE4279	LDO Regulator 5 V; 150 mA	Chip

INTEGRATED CIRCUITS

Power Electronics, Standard Analog IC

• Timers

Part	Pin to Pin Compatibility	Function	Package
Digital timers			
IN555N IN555D	NE555	Timer	DIP-8 SO-8
ILC555N ILC555D	GLC555	Timer	DIP-8 SO-8
IN556N IN556D	NE556	Dual Timer	DIP-14 SO-14
ILC556N	GLC556	Dual Timer	DIP-14
IN558N	NE558	Quad Timer	DIP-16
ILC558N	GLC558	Quad Timer	DIP-16

• Comparators

Part	Pin to Pin Compatibility	Function	Package
IL311AN IL311AD IL311ANM	LM311, LM211	Highly Flexible Voltage Comparators ($T_A = -45 \dots +85^\circ\text{C}$)	DIP-8 SO-8 DIP-14
IL339N IL339D	LM339	Quad Comparator	DIP-14 SO-14
IL293N IL293D	LM293	Dual Comparator ($T_A = -40 \dots +85^\circ\text{C}$)	DIP-8 SO-8
IL393N IL393D	LM393	Dual Comparator	DIP-8 SO-8

• Comparators (Reference Data)

Part	Topr (°C)	I _B (nA) Max	V _{io} (mV) Max	I _{io} (nA) Max	A _v (V/mV) Min	Response Time (ns) Typ	Supply Voltage (V)	Package
Single Comparators								
IL311ANM	-45 ÷ +85	250	3.0	50	150	300	+15, -15	DIP-14
IL311AN								DIP-8
IL311AD								SO-8
Dual Comparators								
IL293N	-40 ÷ +85	250	5.0	50	50	300	$\pm 2.5 \div \pm 15$ or $5.0 \div 30$	DIP-8
IL293D								
IL393N	0 ÷ +70							DIP-8
IL393D								SO-8
Quad Comparators								
IL339N	0 ÷ +70	250	5.0	50	200	300	$\pm 2.5 \div \pm 15$ or $5.0 \div 30$	DIP-14
IL339D								SO-14

INTEGRATED CIRCUITS

Power Electronics, Standard Analog IC

• Timers (Reference Date)

CMOS TIMERS (ILC555N/D, ILC556N, ILC558N)						BIPOLAR TIMERS (IN555N/D, IN556N/D, IN558N)					
Parameter	Test Condition		Value		Unit	Test Condition		Value		Unit	
	V _{cc}	Min	Type	Max	μA	V _{cc}	Min	Type	Max	μA	
Supply Voltage, V _{cc}	-20°C ≤ T _A ≤ +70°C	2		18	V	10°C ≤ T _A ≤ +70°C	4.5		16	V	
Supply Current, I _{cc}	ILC555	2	—	60	200	IN555	5	—	3000	6000	
	ILC556	18	—	120	300	IN556	15	—	10000	15000	
	ILC558	2	—	120	400	IN558	5	—	6000	12000	
	ILC558	18	—	240	600		15	—	16000	30000	
Timing Error	R=1–100 kΩ, C = 0.1 μF		2.0 50		5.0 200		R=1–100kΩ, C = 0.1μF		2.25 150		
Initial Accuracy, t _A			% / °C		ppm /°C				% / °C		
Drift With Temperature, ΔtA/ΔT	5	10	15	300	600						
Drift With Supply Voltage, ΔtA/ΔVs			1.0 5		3.0 % / V				0.3 0.3		
Threshold Voltage, V _{TH}	5	0.65xV _{CC}	0.67xV _{CC}	0.7xV _{CC}	V		5		3.33	V	
Trigger Voltage, V _{TRIG}	5	0.31xV _{CC}	0.33xV _{CC}	0.36xV _{CC}	V		5	1.1	1.67	V	
Trigger Current, I _{TRIG}	18	50	5	10	pA	V _{TRIG} = 0V	15	4.5	5.0	μA	
Threshold Current, I _{TH}	18	50	5	10	pA				0.5	2.0	
Reset Current, I _{RST}	V _{RESET} = Ground	18	100	20	pA	V _{RESET} = 0V			0.1	0.25	
		5	20	2.0						μA	
Reset Voltage, V _{RST}	18	0.4	0.7	1.0	V				0.4	0.4 mA	
	2	0.4	0.7	1.0					0.7	1.0	
Control Voltage Lead, V _{CV}			0.65xV _{CC}		0.69xV _{CC}				1.0 11		
Output Voltage Low, V _{OL}	I _O = 20 mA I _O = 3.2 mA	15	0.4 0.2	1.0 0.4	V	I _O = 10mA I _O = 50mA I _O = 8nA I _O = 5mA	15 5 5 5	10 2.6 0.1 0.25	1.1 4.0 0.4 0.4	V	
Output Voltage High, V _{OH}	I _O = 0.8 mA I _O = 0.8 mA	15	14.3 4.0	14.6 4.3	V	I _O = 100mA I _O = 200mA I _O = 100mA	15 15 5	12.75 2.75 2.75	13.3 12.5 3.3	kHz	
Rise (Fall) Time of Output, t _{T_{LH}, t_{T_{HL}}}	R _L = 10 MΩ, C _L = 10 pF	5	35	40	75	ns			100	ns	
Guaranteed Max Osc Freq, f _{max}	Astable Operation		500		kHz		500		10 to +70		
Operating Temperature, T _{opr}			°C				°C		-10 to +70		
Note:	T _A = 25°C, V _{CC} = + 2 – + 15V unless other specified										

INTEGRATED CIRCUITS

Power Electronics, Standard Analog IC

• Operational Amplifiers

Part	Pin to Pin Compatibility	Function	Package
IL258N IL258D	LM258	Dual Operational Amplifier ($T_A = -40 \div +85^\circ\text{C}$)	DIP-8 SO-8
IL358N IL358D	LM358	Dual Operational Amplifier	DIP-8 SO-8
IL224N IL224D	LM224	Quad Operational Amplifier ($T_A = -40 \div +85^\circ\text{C}$)	DIP-14 SO-14
IL324N IL324D	LM324	Quad Operational Amplifier	DIP-14 SO-14
IL1776CN, CAN IL1776CD, CAD	MC1776C	Micropower Programmable Operational Amplifier (CAN, CAD $T_A = -40 \div +85^\circ\text{C}$)	DIP-8 SO-8
IL4558N IL4558D	GL4558	Dual Operational Amplifier	DIP-8 SO-8
IZ4560	NJM4560	Dual Operational Amplifier ($T_A = -25 \div +75^\circ\text{C}$)	Chip
IZ4580	NJM4580	Dual Operational Amplifier ($T_A = -40 \div +85^\circ\text{C}$)	Chip
IL9002N	OP-07	Low bias operational amplifier	DIP-8
IL9002AN	OP-07A	Low bias operational amplifier	DIP-8
IL8541D	AD8541	Micropower CMOS operational amplifier	Chip SO-8
IL8515D	AD8515	Low power operational amplifier	Chip SO-8
IL8615D	AD8615	Rail to Rail wide bandwidth operational amplifier	Chip SO-8

• Operational Amplifiers (Reference Data)

Part	Topr (°C)	I _B (nA) Max	V _{IO} (mV) Max	T _{CVIO} (μV/°C) Type	I _{IO} (nA) Max	A _{VOL} (V/mV) Min	Supply Voltage (V)		Package
							Min	Max	
Micropower Programmable Operational Amplifier									
IL1776CN	0 \div +70	10	6.0		6.0	25	± 3.0	± 15	DIP-8
IL1776CD	-40 \div +85								SO-8
IL1776CAN									DIP-8
IL1776CAD									SO-8
Dual Operational Amplifier									
IL258N	-40 \div +85	250	7.0	7.0	50	25	± 2.5 +5.0	± 15 +30	DIP-8
IL258D									SO-8
IL358N	0 \div +70								DIP-8
IL358D									SO-8
IL4558N	0 \div +70	500	5.0		200	20		± 16	DIP-8
IL4558D									SO-8
IZ4560	-25 \div +75	500	6.0		200	86 dB	± 4	± 15	Chip
IZ4580	-40 \div +85	500	3.0		200	90 dB	± 2	± 15	Chip
Quad Operational Amplifier									
IL224N	-40 \div +85	250	7.0	7.0	50	25	± 2.5 +5.0	± 15 +30	DIP-14
IL224D									SO-14
IL324N	0 \div +70								DIP-14
IL324D									SO-14
Low bias operational amplifier									
IL9002N	-60 \div +125	2.5	0.055	0.6	2.5	250	$+3.0$	± 18	DIP-8
IL9002AN		4	0.105	1.3	3.5	150			

• µP Supervisory Circuits

Part	Pin to Pin Compatibility	Function	Package
IN1232N IN1232D	DS1232	Micro Monitor	DIP-8 SO-8
IN1705N IN1705D IN1705RN IN1705RD	DS1705	Micro Monitor (RN,RD – Push-Pull Reset Output)	DIP-8 SO-8 DIP-8 SO-8
IN1706N IN1706D IN1706SRN IN1706SRD	DS1706S	Micro Monitor (SRN, SRD - Push-Pull Reset Output)	DIP-8 SO-8 DIP-8 SO-8
IN1708N IN1708D	DS1708	Micro Monitor	DIP-8 SO-8
IL809/810LW IL809/810MW IL809/810TW IL809/810SW IL809/810RW	STM809/810LW STM809/810MW STM809/810TW STM809/810SW STM809/810RW	Reset Circuit	SOT-23-3

• µP Supervisory Circuits (Reference Data)

PARAMETER	IN1232N IN1232D	IN1705N IN1705D	IN1705R N IN1705R D	IN1706N IN1706D	IN1706SRN IN1706SRD	IN1708N IN1708D	IL809/810LW	IL809/810MW	IL809/810TW	IL809/810SW	IL809/810RW
Supply Voltage, V	4.5...5.5	1.2...5.5	1.2...5.5	1.2...5.5	1.2...5.5	1.2...5.5	1.2...5.5	1.2...5.5	1.2...5.5	1.2...5.5	1.2...5.5
Nominal Reset Threshold, V	4.37	4.65	4.65	2.93	2.93	4.40	4.63	4.38	3.08	2.93	2.63
Minimum Reset Pulse Width, ms	250	100	100	130	130	130	130	130	130	130	140
Push-Pull RESET Output	L, H	L	H	L	H	L, H	L/H	L/H	L/H	L/H	L/H
Watchdog	•	•	•	•	•	•	•	•	•	•	•
Nominal Watchdog Timeout Period (s), if available	0.15	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	-
Separate Watchdog Output		•	•	•	•	•	•	•	•	•	•
Power-Fail Comparator/Reset Input		•	•	•	•	•	•	•	•	•	•
Manual-Reset Input	•	•	•	•	•	•	•	•	•	•	•
Supply Current in Operating Mode, µA, max (typ)	2000 (500)	350 (100)	350 (100)	50	50	50	50	50	50	50	15 (7)
Operating Temperature, °C	- 10 ÷ +70			- 40 ÷ +85			- 40 ÷ +85		- 40 ÷ +85		- 40 ÷ +85
Package	DIP-8 SO-8	DIP-8 SO-8	DIP-8 SO-8	DIP-8 SO-8	DIP-8 SO-8	DIP-8 SO-8	DIP-8 SO-8	DIP-8 SO-8	DIP-8 SO-8	DIP-8 SO-8	SOT-23-3

• Voltage Regulators

Part	Pin to Pin Compatibility	Output Voltage, V	Output Current, A	Output Voltage Tolerance, %	Tested Operating Junction Temp. Range, °C	Package
------	--------------------------	-------------------	-------------------	-----------------------------	---	---------

Positive Voltage Regulators

KP1180EHXXA KP1180EHXXB KP1180EHXXB	78XXAC 78XXC 78XXB	5; 6; 8; 9; 10, 12; 15; 18; 20; 24	1.0	2 4 4	T _j = -10...+125 T _j = -10...+125 T _j = -45...+125	TO-220
K1261EHXXП	78FXX	5; 6; 8; 9;10;12;15;18;24	1.0	4	T _j = -10...+125	TO-126
K1332EHXX	78MXX	5; 6; 8; 9; 12; 15; 18; 24	0,5	2 4	T _j = -10...+125	TO-126
KP1181EHXXA KP1181EHXXB	78LXXAC 78LXXC	3.3; 5; 6; 8; 9; 12; 15; 18; 24	0.1	5 10	T _j = -10...+125	TO-92



INTEGRATED CIRCUITS

Power Electronics, Standard Analog IC

• Voltage Regulators (continued)

Negative Regulators						
KP1179EHXXA	IL79XXAC	5; 6; 8; 9; 12; 15;	1.0	2	T _j = -10...+125	
KP1179EHXXB	IL79XXC	18; 20; 24		4	T _j = -10...+125	TO-220
KP1179EHXXB	IL79XXB			4	T _j = -45...+125	
KP1199EHXXA	79LXXAC	5; 6; 8; 9; 12; 15;	0.1	5	T _j = -10...+125	TO-92
KP1199EHXXB	79LXXC	18; 24		10		
Low Dropout Voltage Regulators						
ILE4250G/S (Tracker)	TLE4250G	2 ÷ 36	0.05	0.5	T _j = -40...+150	P-TO-263-5-1 TO-220AB/5
ILE4260 ILE4260-2	TLE4260S	5	0.5	5 2	T _j = -40...+125	P-TO-220-5-12
ILE4264G	TLE4264G	5	0.10	2	T _j = -40...+125	P-SOT223-4-1
IZE4264-2	TLE4264-2G	5	0.10	3	T _j = -40...+125	Chip
ILE4266G	TLE4266G	5	0.10	2	T _j = -40...+125	P-SOT223-4-2
IZE4266-2	TLE4266-2G	5	0.10	3	T _j = -40...+125	Chip
ILE4267G ILE4267S	TLE4267G TLE4267S	5	0.4	2	T _j = -40...+125	P-TO-220-7-180 P-TO-220-7-230
ILE4268GDW	TLE4268G	5	0.15	2	T _j = -40...+125	SO-20
ILE4270G ILE4270S ILE4270Q	TLE4270G TLE4270S	5	0.55	2	T _j = -40...+125	P-TO-263-5-1 P-TO-220-5-12 P-TO-220-5-11
ILE4270 (without "RESET")		5	0.55	2	T _j = -40...+125	TO-220AB/3
ILE4271G ILE4271S	TLE4271G TLE4271S	5	0.55	2	T _j = -40...+125	P-TO-220-7-180 P-TO-220-7-230
ILE4274V50/V8 5/V10	TLE4274	5; 8.5; 10	0.4	4	T _j = -40...+150	TO-220AB/3
ILE4275G/S	TLE4275G	5	0.4	2	T _j = -40...+150	P-TO-263-5-1 TO-220AB/5
ILE4276VG/VS/ V50G/V50S/V8 5G/V85S/V10G/ V10S	TLE4276	5; 8.5; 10	0.4	4	T _j = -40...+150	
IZE4278	TLE4278	5	0.15	2	T _j = -40...+150	Chip
IZ1734-33	SSAAC1734-33	3.3	0.3	2	T _j = -40...+125	Chip
IZ1734-50	SSAAC1734-50	5	0.3	2		
IZ1735-33	SSAAC1735-33	3.3	0.5	2		
IZ1735-50	SSAAC1735-50	5	0.5	2		
IL5212G	CS5201 LD1117S	1.2	0.8	5	T _j = 0...+125	P-SOT-223-4-1
IL5218G		1.8	0.8	2		
IL5225G		2.5	0.8	2		
IL5228G		2.85	0.8	2		
IL5230G		3.0	0.8	2		
IL5233G		3.3	0.8	2		
IL5250G		5.0	0.8	2		
IL1117A-XX	AMS1117A-XX	1.2; 1.25; Adj; 1.5; 1.8; 2.5; 2.85; 3.3; 5	1.0	1.5	T _j = -40...+125	TO-220 TO-126
K1280EHXX	LM3480-XX	3.3; 5.0	0.1	4	T _j = -10...+125	TO-92
K1282EHXX	LT1084-XX	1.25; 1.5; 1.8; 2.5; 2.85; 3.3; 3.6; 5.0	5.0	1.5	T _j = -10...+125	TO-220
K1320EXX	LT1085	1.25; 1.5; 1.8; 2.5; 2.85; 3.3; 3.6; 5.0	3.0	1.5	T _j = -10...+125	TO-220
IL5219T	MIC5219	Adj; 1.8; 2.5; 3.3; 5.0	1.0	2	T _j = -40...+125	TO-220 TO-126 Chip

• Voltage Regulators (continued)

Adjustable Voltage Regulators

Part	Pin to Pin Compatibility	Function	Package
IL317	LM317T	Adjustable Output Positive Voltage Regulator 1.5 A; (1.2...37 V) $T_j = -40 \dots +125^\circ C$	TO-220AB/3
IZ317L	LM317L	Adjustable Output Positive Voltage Regulator 0.1 A; (1.2...37 V) $T_j = -40 \dots +125^\circ C$	TO-92
IL2931CD	LM2931C	Adjustable Dropout Voltage Regulator 0.1 A; (3...24 V) $T_j = -40 \dots +125^\circ C$	SO-8
IL5200G	CS5201 LD1117S	Adjustable Dropout Voltage Regulator 0.8 A; (1.25 ... 13.5 V) $T_j = 0 \dots +125^\circ C$	P-SOT-223-4-1

Switching Regulators

Part	Pin to Pin Compatibility	Function	Package
IL2576 – 3.3	LM2576 – 3.3		
IL2576 – 5	LM2576 – 5		
IL2576 – 12	LM2576 – 12	3.0 A, 15 V, Step-Down Switching Regulator	TO-220 AB/5
IL2576 – 15	LM2576 – 15		
IL2576 – ADJ	LM2576 – ADJ		
IL2596 – 3.3	LM2596 – 3.3		
IL2596 – 5	LM2596 – 5		
IL2596 – 12	LM2596 – 12	Power Converter 150 kHz 3 A Step-Down Voltage Regulator	TO-220 AB/5
IL2596 – ADJ	LM2596 – ADJ		
IL1501 – 33	AP1501 – 3.3V		
IL1501 – 50	AP1501 – 5V		
IL1501 – 12	AP1501 – 12V	150 kHz, 3 A PWM Buck DC/DC Converter	TO-220 AB/5
IL1501 – ADJ	AP1501 – ADJ		
IZ9261 – 15	RT9261 – 15		
IZ9261 – 25	RT9261 – 25		
IZ9261 – 33	RT9261 – 33	VFM Step-up DC/DC Converter	Chip
IZ9261 – 50	RT9261 – 50		
IL34063AN	MC34063A	Step-Up /Down/inverting Switching Regulator ($I_{sw} \leq 1.5A$)	Dip-8
IL34063AD			SO-8
IL33063AN	MC33063A	Step-Up /Down/inverting Switching Regulator $T_A = (-40 \dots +85^\circ C)$	Dip-8
IL33063AD			SO-8
IL34063S1	MC34063A	Step-Up/Down/inverting Switching Regulator ($I_{sw} \leq 0.8 A$)	Chip
IZ1583	MP1583	Step-Down Switching Regulator	Chip

• Precision Low Voltage Reference

Part	Pin to Pin Compatibility	Function	Features	Package
K1242EP1	TL431	Programmable precision references. This monolithic IC voltage references operate as a low temperature coefficient zener which is programmable from U_{ref} to 16/37 with two external resistors.	<ul style="list-style-type: none"> <input type="checkbox"/> $V_{ref} = 2.5 \dots 37 V$ <input type="checkbox"/> $I_{k max} = 100 mA$ <input type="checkbox"/> Shunt Reference Dynamic Impedance $Z \leq 0.5 \Omega$ <input type="checkbox"/> Tolerance 0.5%; 1%; 2% 	TO-92 SOT-23 SO-8
K142EP2ПИМ	TL432	The characteristics of these references make them excellent replacements for zener diodes in many applications such as digital voltmeters, power supplies, and operation amplifier circuitry.	<ul style="list-style-type: none"> <input type="checkbox"/> $V_{ref} = 1.24 \dots 16V$ <input type="checkbox"/> $I_{kmax} = 100 mA$ <input type="checkbox"/> Shunt Reference Dynamic Impedance $Z \leq 0.5 \Omega$ <input type="checkbox"/> Tolerance 0.5%; 1% 	TO-92

INTEGRATED CIRCUITS

Power Electronics, Standard Analog IC

• Precision Low Voltage Reference (continued)

IL17431	HA17431	Temperature-compensated variable shunt regulator. Includes a photocoupler by pass resistor (2kΩ)	<input type="checkbox"/> Vref= 1.24...16V <input type="checkbox"/> I _{kmax} = 100 mA <input type="checkbox"/> Shunt Reference Dynamic Impedance Z ≤ 0.2 Ω (typ) <input type="checkbox"/> Tolerance 0.5%	Chip
---------	---------	--	---	------

• Switching Regulators (Reference Data)

Part	T (°C)	I _{OUT} (A)	V _{IN} (V)		V _{OUT} (V)	F _{sw} (typ) (kHz)	I _{STBY} (typ) (μA)	Package
			Min	Max				
Step-Down (Buck)								
IL1509	- 40 ÷ +125	3	4.5	22	1.8, 2.5, 3.3, 5, Adj (1.23 to 22)	150	70	TO- 220AB/5 Chip
IL2576	- 40 ÷ +125	3	6.0	40	3.3, 5, 12, 15, Adj (1.23 to 37)	52	80	TO- 220AB/5
IL2576HVR**	- 40 ÷ +125	3	6.0	60	3.3, 5, 12, 15, Adj (1.23 to 37)	52	80	TO- 220AB/5
IL2596	- 40 ÷ +125	3	4.5	40	3.3, 5, 12, Adj (1.23 to 37)	150	80	TO- 220AB/5
IL1501AT1	- 40 ÷ +125	5	4.5	40	3.3, 5, 12, Adj (1.23 to 37)	150	150	chip
IZ1583	- 40 ÷ +85	3	4.75	23	Adj (1.22 to 21)	385		Chip
Step-Up								
IZ9261	- 25 ÷ +85	0.250	1	4.5	1.5, 2.5, 3.3, 5	120	0.5	Chip
Step-Up /Down/Inverting								
IL33063AN	- 40 ÷ +85	1.5	3.0	40	Adj	33	2.5 mA	Dip-8
IL33063AD								SO-8
IL34063AN	0 ÷ +70	1.5	3.0	40	Adj	33	2.5 mA	Dip-8
IL34063AD								SO-8
IL34063S1	0 ÷ +70	0.8	3.0	40	Adj	33	2.5 mA	Chip

**Under Development

• PWM Controllers

Part	Pin to Pin Compatibility	Function	Package
IL494N	TL494IN	Pulse-Width-Modulation Control Circuit	DIP-16
IL6083N IL6083N-01	U6083B	Power Control With Interference Suppression (for IL6083N N-01: Duty cycle 10... 100%, V _{S1} =24.5...28.0 V, V _{S2} =18.5...22.0 V, V _{Batt1} =16.7...21.0 V (switched on), V _{batt1} =18.3...22.5 V (switched off), V _{Ts} =10.1...10.7 V, I _s =5...17 mA)	DIP-8
IZ7500		Pulse-Width-Modulation Control Circuit	Chip

• Voltage Detectors

Part	Pin to Pin Compatibility	Function	Package
K1274СΠХХП	KIA70XX	Voltage Detector Ucc max= 15 V; I _{OLmax} <16 mA; Us= 2.1/2.3/2.5/ 2.7 /2.9/ 3.1 /3.3/ 3.5 /3.6/3.7/ 3.9/ 4.2/ 4.5 V	TO-92

- *Voltage Regulators (Reference Data)*

• *Voltage Regulators (Reference Data)*

Parameter	Chip												Package
	P-SOT223-4-1			SO-8			TO-220AB/3			IZ317L			
Output current, mA	≤800	≤800	≤800	≤800	≤800	≤800	≤800	≤800	≤800	≤300	≤300	≤500	100
Input voltage (max), V	15	8	10	10	12	15	15	15	12	12	12	12	40
Output voltage, V	1.2	1.8	2.5	2.85	3	3.3	5	1.25-13.5	3.3	5	3.3	5	3-24
Drop voltage, V	≤1.2	≤1.2	≤1.2	≤1.2	≤1.2	≤1.2	≤1.2	≤1.2	0.47	0.4	0.65	0.51	0.6 ≤2.5
Output voltage tolerance, %	Iq max	5	2	2	2	2	2	2	2	2	2	2	5 0.07%/ <i>N</i>
Current consumption, mA	Iq = max	10	10	10	10	10	10	10	10	0.08	0.08	0.09	0.09 6 0.1 (<i>Io=0.5A</i>)
Shot-circuit proof	•	•	•	•	•	•	•	•	•	•	•	•	•
Oversupply protection	•	•	•	•	•	•	•	•	•	•	•	•	•
Reverse polarity protection	•	•	•	•	•	•	•	•	•	•	•	•	•
Overtemperature protection	•	•	•	•	•	•	•	•	•	•	•	•	•
On/off logic	•	•	•	•	•	•	•	•	•	•	•	•	•
Junction Temperature, °C	0 ÷ +125												-40 ÷ +125



• Power Supply ICs

Part	Pin to Pin Compatibility	Function	Package
K1294EEXXX	TSM1051	Constant Voltage and Constant Current Controller For Adaptors and Battery Chargers	DIP-8 Chip
IL1051(14V) IL1052(20V) IL1053(40V)		Constant Voltage and Constant Current Controller For Adaptors and Battery Chargers	Chip
K1301THXX	ICL7660	CMOS Voltage Converter	DIP-8, SO - 8 Chip

• IW4000AN, D(DW) Series

Part	Pin to Pin Compatibility	Function	Package
IW4001AN,AD	CD4001AN,AD	Quad 2-Input NOR Gate	DIP-14, SO-14
IW4002AN,AD	CD4002AN,AD	Dual 4-Input NOR Gate	DIP-14, SO-14
IW4011AN,AD	CD4011AN,AD	Quad 2-Input NAND Gate	DIP-14, SO-14
IW4012AN,AD	CD4012AN,AD	Dual 4-Input NAND Gate	DIP-14, SO-14
IW4013AN,AD	CD4013AN,AD	Dual D-Type Flip-Flop	DIP-14, SO-14
IW4015AN,AD	CD4015AN,AD	Dual 4-Bit Shift Register	DIP-16, SO-16
IW4017AN,AD	CD4017AN,AD	Decade Counter/Driver	DIP-16, SO-16
IW4019AN,AD	CD4019AN,AD	Quad AND-OR Gate	DIP-16, SO-16
IW4020AN,AD	CD4020AN,AD	14-Bit Binary Divide Counter	DIP-16, SO-16
IW4023AN,AD	CD4023AN,AD	Triple 3-Input NAND Gate	DIP-14, SO-14
IW4025AN,AD	CD4025AN,AD	Triple 3-Input NOR Gate	DIP-14, SO-14
IW4028AN,AD	CD4028AN,AD	BCD-to-Decimal Decoder	DIP-16, SO-16
IW4029AN,AD	CD4029AN,AD	Binary or BCD-Decade Counter	DIP-16, SO-16
IW4030AN,AD	CD4030AN,AD	Quad Exclusive-OR Gate	DIP-14, SO-14
IW4034AN,ADW	CD4034AN,AD	8-Bit Shift Register	DIP-24, SO-24
IW4043AN,AD	CD4043AN,AD	Quad NOR R-S Latch (3-State)	DIP-16, SO-16
IW4049AN,AD	CD4049AN,AD	Hex Buffer/Converter	DIP-14, SO-14
IW4050AN,AD	CD4050AN,AD	Hex Buffer/Converter	DIP-16, SO-16
IW4051AN,AD	CD4051AN,AD	Single 8-Channel Multiplexer/Demultiplexer	DIP-16, SO-16
IW4052AN,AD	CD4052AN,AD	Differential 4-Channel Multiplexer/Demultiplexer	DIP-16, SO-16
IW4066AN,AD	CD4066AN,AD	Quad Bilateral Switch	DIP-14, SO-14
IW4069AN,AD	CD4069AN,AD	Hex Inverter	DIP-14, SO-14
IW4093AN,AD	CD4093AN,AD	Quad 2-Input NAND Schmitt Trigger	DIP-14, SO-14
IW4502AN,AD	CD4502AN,AD	Hex Inverter/Buffer	DIP-16, SO-16
IW4516AN,AD	CD4516AN,AD	Presettable Binary Up/Down Counter	DIP-16, SO-16
IW4520AN,AD	CD4520AN,AD	Dual Binary Up Counter	DIP-16, SO-16

• IW4000BN, D(DW) Series

Part	Pin to Pin Compatibility	Function	Package
IW4001BN,BD	CD4001BN,BD	Quad 2-Input NOR Gate	DIP-14, SO-14
IW4002BN,BD	CD4002BN,BD	Dual 4-Input NOR Gate	DIP-14, SO-14
IW4006BN,BD	CD4006BN,BD	18-Bit Static Shift Register	DIP-14, SO-14
IW4008BN,BD	CD4008BN,BD	4-Bit Full Adder	DIP-16, SO-16
IW4011BN,BD	CD4011BN,BD	Quad 2-Input NAND Gate	DIP-14, SO-14
IW4012BN,BD	CD4012BN,BD	Dual 4-Input NAND Gate	DIP-14, SO-14
IW4013BN,BD	CD4013BN,BD	Dual D-Type Flip-Flop	DIP-14, SO-14
IW4015BN,BD	CD4015BN,BD	Dual 4-Bit Static Shift Register	DIP-16, SO-16
IW4016BN,BD	CD4016BN,BD	Quad Bilateral Switch	DIP-14, SO-14
IW4017BN,BD	CD4017BN,BD	Decade Counter/Driver	DIP-16, SO-16
IW4018BN,BD	CD4018BN,BD	Presettable Divide-by-N Counter	DIP-16, SO-16
IW4019BN,BD	CD4019BN,BD	Quad AND-OR Gate	DIP-16, SO-16
IW4020BN,BD	CD4020BN,BD	14-Bit Binary Divide Counter	DIP-16, SO-16

INTEGRATED CIRCUITS

Power Electronics, Standard Analog IC, Standard Digital Logic IC

• IW4000BN, D(DW) Series (continued)

Part	Pin to Pin Compatibility	Function	Package
IW4021BN,BD	CD4021BN,BD	8-Bit Shift Register	DIP-16, SO-16
IW4022BN,BD	CD4022BN,BD	Divide-by-8 Counter/Divider	DIP-16, SO-16
IW4023BN,BD	CD4023BN,BD	Triple 3-Input NAND Gate	DIP-14, SO-14
IW4025BN,BD	CD4025BN,BD	Triple 3-Input NOR Gate	DIP-14, SO-14
IW4027BN,BD	CD4027BN,BD	Dual J-K Flip-Flop	DIP-16, SO-16
IW4028BN,BD	CD4028BN,BD	BCD-to-Decimal Decoder	DIP-16, SO-16
IW4029BN,BD	CD4029BN,BD	Binary or BCD-Decade Counter	DIP-16, SO-16
IW4030BN,BD	CD4030BN,BD	Quad Exclusive-OR Gate	DIP-14, SO-14
IW4034BN,BDW	CD4034BN,BD	8-Bit Shift Register	DIP-24, SO-24
IW4035BN,BD	CD4035BN,BD	4-Bit Parallel-In/Parallel-Out Shift Register	DIP-16, SO-16
IW4040BN,BD	CD4040BN,BD	12-Bit Binary Counter	DIP-16, SO-16
IW4042BN,BD	CD4042BN,BD	Quad Clocked D-Latch	DIP-16, SO-16
IW4043BN,BD	CD4043BN,BD	Quad NOR R-S Latch (3-State)	DIP-16, SO-16
IW4049BN,BD	CD4049BN,BD	Hex Buffer/Converter	DIP-16, SO-16
IW4050BN,BD	CD4050BN,BD	Hex Buffer/Converter	DIP-16, SO-16
IW4051BN,BD	CD4051BN,BD	8-Channel Analog Multiplexer/Demultiplexer	DIP-16, SO-16
IW4052BN,BD	CD4052BN,BD	Dual 4-Channel Analog Multiplexer/Demultiplexer	DIP-16, SO-16
IW4053BN,BD	CD4053BN,BD	Triple 2-Channel Analog Multiplexer/Demultiplexer	DIP-16, SO-16
IW4059AN,ADW	CD4059AN,AD	Programmable Counter	DIP-24, SO-24
IW4060BN,BD	CD4060BN,BD	14-Bit Binary Divide/ Counter	DIP-16, SO-16
IW4066BN,BD	CD4066BN,BD	Quad Bilateral Switch	DIP-14, SO-14
IW4068BN,BD	CD4068BN,BD	8-Input NAND Gate	DIP-14, SO-14
IW4069UBN,UBD	CD4069UBN,UBD	Hex Inverter	DIP-14, SO-14
IW4070BN,BD	CD4070BN,BD	Quad Exclusive-OR Gate	DIP-14, SO-14
IW4071BN,BD	CD4071BN,BD	Quad 2-Input OR Gate	DIP-14, SO-14
IW4072BN,BD	CD4072BN,BD	Dual 4-Input OR Gate	DIP-14, SO-14
IW4073BN,BD	CD4073BN,BD	Triple 3-Input AND Gate	DIP-14, SO-14
IW4075BN,BD	CD4075BN,BD	Triple 3-Input OR Gate	DIP-14, SO-14
IW4077BN,BD	CD4077BN,BD	Quad Exclusive-NOR Gate	DIP-14, SO-14
IW4081BN,BD	CD4081BN,BD	Quad 2-Input AND Gate	DIP-14, SO-14
IW4093BN,BD	CD4093BN,BD	Quad 2-Input NAND Schmitt Trigger	DIP-14, SO-14
IW4098BN,BD	CD4098BN,BD	Dual Monostable Multivibrator	DIP-16, SO-16
IW40107BN,BD	CD40107BN,BD	Dual 2-Input NAND Buffer/Driver	DIP-14, SO-14
IW4502BN,BD	CD4502BN,BD	Hex Inverter/Buffer	DIP-16, SO-16
IW4503BN,BD	CD4503BN,BD	Hex Buffer	DIP-16, SO-16
IW4511BN,BD	CD4511BN,BD	BCD-to-7-Segment Latch Decoder/Driver	DIP-16, SO-16
IW4516BN,BD	CD4516BN,BD	Presettable Binary Up/Down Counter	DIP-16, SO-16
IW4518BN,BD	CD4518BN,BD	Dual BCD Up Counter	DIP-16, SO-16
IW4519BN,BD	CD4519BN,BD	Quad AND/OR Select Gate	DIP-16, SO-16
IW4520BN,BD	CD4520BN,BD	Dual Binary Up Counter	DIP-16, SO-16
IW4528BN,BD	CD4528BN,BD	Dual Monostable Multivibrator	DIP-16, SO-16
IW4531BN,BD	NEF4531BN,BD	12-Bit Checker Tree	DIP-16, SO-16
IW4541BN,BD	CD4541BN,BD	Programmable Timer	DIP-14, SO-14
IW4543BN,BD	CD4543BN,BD	BCD-to-7-Segment Latch/Decoder/Driver for Liquid-Crystal Display	DIP-16, SO-16
IW4585BN,BD	CD4585BN,BD	4-Bit Comparator	DIP-16, SO-16

• IN74ACXXXXN, D (DW) Series

Part	Pin to Pin Compatibility	Function	Package
IN74AC00N,D	MC74AC00N,D	Quad 2-Input NAND Gate	DIP-14, SO-14
IN74AC02N,D	MC74AC02N,D	Quad 2-Input NOR Gate	DIP-14, SO-14
IN74AC04N,D	MC74AC04N,D	Hex Inverter	DIP-14, SO-14
IN74AC05N,D	CD74AC05N,D	Hex Inverter, OC	DIP-14, SO-14
IN74AC08N,D	MC74AC08N,D	Quad 2-Input AND Gate	DIP-14, SO-14
IN74AC10N,D	MC74AC10N,D	Triple 3-Input Positive-NAND Gate	DIP-14, SO-14
IN74AC11N,D	MC74AC11N,D	Triple 3-Input AND Gate	DIP-14, SO-14
IN74AC14N,D	MC74AC14N,D	Hex Schmitt-Trigger Inverter	DIP-14, SO-14
IN74AC20N,D	CD74AC20N,D	Dual 4-Input NAND Gate	DIP-14, SO-14
IN74AC21N,D	own	Dual 4-Input AND Gate	DIP-14, SO-14
IN74AC27N,D	own	Triple 3-Input NOR Gate	DIP-14, SO-14
IN74AC32N,D	MC74AC32N,D	Quad 2-Input OR Gate	DIP-14, SO-14
IN74AC34N,D	own	Hex Non-Inverter	DIP-14, SO-14
IN74AC74N,D	MC74AC74N,D	Dual D-Type Flip-Flop	DIP-14, SO-14
IN74AC86N,D	MC74AC86N,D	Quad 2-Input Exclusive-OR Gate	DIP-14, SO-14
IN74AC109N,D	MC74AC109N,D	Dual J-K Positive-Edge-Triggered Flip-Flop	DIP-16, SO-16
IN74AC112N,D	CD74AC112N,D	Dual J-K Negative-Edge-Triggered Flip-Flop	DIP-16, SO-16
IN74AC125N,D	T74AC125N,D	Quad 3-State Buffer	DIP-14, SO-14
IN74AC132N,D	MC74AC132N,D	Quad 2-Input NAND Schmitt-Trigger Inverter	DIP-14, SO-14
IN74AC138N,D	MC74AC138N,D	3-8 Decoder/Demultiplexer	DIP-16, SO-16
IN74AC139N,D	MC74AC139N,D	Dual 2-4 Decoder/Demultiplexer	DIP-16, SO-16
IN74AC151N,D	MC74AC151N,D	8-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74AC153N,D	MC74AC153N,D	Dual 4-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74AC157N,D	MC74AC157N,D	Quad 2-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74AC158N,D	MC74AC158N,D	Quad 2-1 Data Selector/Multiplexer, INV	DIP-16, SO-16
IN74AC161N,D	MC74AC161N,D	4-Bit Synchronous Binary Counter, Asynchronous Reset	DIP-16, SO-16
IN74AC163N,D	MC74AC163N,D	4-Bit Synchronous Binary Counter, Synchronous Reset	DIP-16, SO-16
IN74AC164N,D	CD74AC164N,D	8-Bit Serial-In Parallel-Out Shift Register	DIP-14, SO-14
IN74AC174N,D	MC74AC174N,D	Hex D-Type Flip-Flop	DIP-16, SO-16
IN74AC175N,D	MC74AC175N,D	Quad D-Type Flip-Flop	DIP-16, SO-16
IN74AC192N,D	MC74AC192N,D	Synchronous Decade Up/Down Counter	DIP-16, SO-16
IN74AC193N,D	CD74AC193N,D	4-Bit Synchronous Binary Up/Down Counter	DIP-16, SO-16
IN74AC240N,DW	MC74AC240N,D	Octal Buffer/Line Driver, INV (3-State)	DIP-20, SO-20
IN74AC241N,DW	MC74AC241N,D	Octal Buffer/Line Driver, NINV (3-State)	DIP-20, SO-20
IN74AC244N,DW	MC74AC244N,D	Octal Buffer/Line Driver NINV (3-State)	DIP-20, SO-20
IN74AC245N,DW	MC74AC245N,D	Octal Bus Transceiver, NINV (3-State)	DIP-20, SO-20
IN74AC251N,D	MC74AC251N,D	8-I Data Selector/Multiplexer (3-State)	DIP-16, SO-16
IN74AC253N,D	MC74AC253N,D	Dual 4-1 Data Selector/Multiplexer, NINV (3-State)	DIP-16, SO-16
IN74AC257N,D	MC74AC257N,D	Quad 2-1 Data Selector/Multiplexer, NINV (3-State)	DIP-16, SO-16
IN74AC258N,D	MC74AC258N,D	Quad 2-1 Data Selector/Multiplexer, INV (3-State)	DIP-16, SO-16
IN74AC273N,DW	MC74AC273N,D	Octal D-Type Flip-Flop	DIP-20, SO-20
IN74AC299N,DW	MC74AC299N,D	8-Bit Universal Shift/Storage Register (3-State)	DIP-20, SO-20
IN74AC323N,DW	CD74AC323N,D	8-Bit Universal Shift/Storage Register (3-State)	DIP-20, SO-20
IN74AC373N,DW	MC74AC373N,D	Octal D-Type Latch (3-State)	DIP-20, SO-20
IN74AC374N,DW	MC74AC374N,D	Octal D-Type Flip-Flop (3-State)	DIP-20, SO-20
IN74AC533N,DW	MC74AC533N,D	Octal D-Type Latch, INV (3-State)	DIP-20, SO-20
IN74AC534N,DW	MC74AC534N,D	Octal D-Type Flip-Flop, NINV (3-State)	DIP-20, SO-20
IN74AC563N,DW	MC74AC563N,D	Octal D-Type Transparent Latch	DIP-20, SO-20
IN74AC564N,DW	MC74AC564N,D	Octal Edge-Triggered Flip-Flop	DIP-20, SO-20
IN74AC573N,DW	MC74AC573N,D	Octal Transparent Latch (3-State)	DIP-20, SO-20
IN74AC574N,DW	MC74AC574N,D	Octal D-Type Flip-Flop, NINV (3-State)	DIP-20, SO-20
IN74AC620N,DW	MC74AC620N,D	Octal Bidirectional Bus Transceiver, INV	DIP-20, SO-20
IN74AC623N,DW	MC74AC623N,D	Octal Bidirectional Bus Transceiver, NINV	DIP-20, SO-20
IN74AC640N,DW	MC74AC640N,D	Octal Bus Transceiver (3-State)	DIP-20, SO-20

INTEGRATED CIRCUITS

Power Electronics, Standard Analog IC, Standard Digital Logic IC

• IN74ACXXXXN, D(DW) Series (continued)

Part	Pin to Pin Compatibility	Function	Package
IN74AC643N,DW	MC74AC643N,D	Octal Bus Transceiver (3-State)	DIP-20, SO-20
IN74AC651N,DW	CD74AC651N,D	Octal Bus Transceiver/Register, INV (3-State)	DIP-24, SO-24
IN74AC652N,DW	own	Octal Bus Transceiver/Register, NINV (3-State)	DIP-24, SO-24
IN74AC810N,D	MC74AC810N,D	Quad Exclusive-NOR Gate	DIP-14, SO-14
IN74AC4006N,D	own	18-Bit Static Shift Register	DIP-14, SO-14
IN74AC4015N,D	own	Dual 4-Bit Static Shift Register	DIP-16, SO-16
IN74AC4035N,D	own	4-Bit Parallel-In/Parallel-Out Shift Register	DIP-16, SO-16
IN74AC4520N,D	own	Dual 4-Bit Synchronous Binary Counter	DIP-16, SO-16

• IN74ACTXXXXN, D(DW) Series

Part	Pin to Pin Compatibility	Function	Package
IN74ACT00N,D	MC74ACT00N,D	Quad 2-Input NAND Gate	DIP-14, SO-14
IN74ACT02N,D	MC74ACT02N,D	Quad 2-Input NOR Gate	DIP-14, SO-14
IN74ACT04N,D	CD74ACT04N,D	Hex Inverter	DIP-14, SO-14
IN74ACT05N,D	CD74ACT05N,D	Hex Inverter, OC	DIP-14, SO-14
IN74ACT08N,D	MC74ACT08N,D	Quad 2-Input AND Gate	DIP-14, SO-14
IN74ACT10N,D	MC74ACT10N,D	Triple 3-Input Positive-NAND Gate	DIP-14, SO-14
IN74ACT11N,D	MC74ACT11N,D	Triple 3-Input AND Gate	DIP-14, SO-14
IN74ACT14N,D	MC74ACT14N,D	Hex Schmitt-Trigger Inverter	DIP-14, SO-14
IN74ACT20N,D	CD74ACT20N,D	Dual 4-Input NAND Gate	DIP-14, SO-14
IN74ACT21N,D	own	Dual 4-Input Positive-AND Gate	DIP-14, SO-14
IN74ACT27N,D	own	Triple 3-Input NOR Gate	DIP-14, SO-14
IN74ACT32N,D	MC74ACT32N,D	Quad 2-Input OR Gate	DIP-14, SO-14
IN74ACT34N,D	own	Hex Non-Inverter	DIP-14, SO-14
IN74ACT74N,D	MC74ACT74N,D	Dual D-Type Flip-Flop	DIP-14, SO-14
IN74ACT86N,D	MC74ACT86N,D	Quad 2-Input Exclusive-OR Gate	DIP-14, SO-14
IN74ACT109N,D	MC74ACT109N,D	Dual J-K Positive-Edge-Triggered Flip-Flop	DIP-16, SO-16
IN74ACT112N,D	MC74ACT112N,D	Dual J-K Negative-Edge-Triggered Flip-Flop	DIP-16, SO-16
IN74ACT125N,D	own	Quad 3-State Buffer	DIP-14, SO-14
IN74ACT132N,D	MC74ACT132N,D	Quad 2-Input NAND Schmitt-Trigger Inverter	DIP-14, SO-14
IN74ACT138N,D	MC74ACT138N,D	3-8 Decoder/Demultiplexer	DIP-16, SO-16
IN74ACT139N,D	MC74ACT139N,D	Dual 2-4 Decoder/Demultiplexer	DIP-16, SO-16
IN74ACT151N,D	MC74ACT151N,D	8-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74ACT153N,D	MC74ACT153N,D	Dual 4-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74ACT157N,D	MC74ACT157N,D	Quad 2-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74ACT158N,D	MC74ACT158N,D	Quad 2-1 Data Selector/Multiplexer, INV	DIP-16, SO-16
IN74ACT161N,D	MC74ACT161N,D	4-Bit Synchronous Binary Counter, Asynchronous Reset	DIP-16, SO-16
IN74ACT163N,D	MC74ACT163N,D	4-Bit Synchronous Binary Counter, Synchronous Reset	DIP-16, SO-16
IN74ACT164N,D	CD74ACT164N,D	8-Bit Serial-In Parallel-Out Shift Register	DIP-14, SO-14
IN74ACT174N,D	MC74ACT174N,D	Hex D-Type Flip-Flop	DIP-16, SO-16
IN74ACT175N,D	CD74ACT175N,D	Quad D-Type Flip-Flop	DIP-16, SO-16
IN74ACT192N,D	own	Synchronous Decade Up/Down Counter	DIP-16, SO-16
IN74ACT193N,D	CD74ACT193N,D	4-Bit Synchronous Binary Up/Down Counter	DIP-16, SO-16
IN74ACT240N,DW	MC74ACT240N,D	Octal Buffer/Line Driver, INV (3-State)	DIP-20, SO-20
IN74ACT241N,DW	MC74ACT241N,D	Octal Buffer/Line Driver, NINV (3-State)	DIP-20, SO-20
IN74ACT244N,DW	MC74ACT244N,D	Octal Buffer/Line Driver NINV (3-State)	DIP-20, SO-20
IN74ACT245N,DW	MC74ACT245N,D	Octal Bus Transceiver, NINV (3-State)	DIP-20, SO-20
IN74ACT251N,D	MC74ACT251N,D	8-I Data Selector/Multiplexer (3-State)	DIP-16, SO-16
IN74ACT253N,D	MC74ACT253N,D	Dual 4-1 Data Selector/Multiplexer, NINV (3-State)	DIP-16, SO-16
IN74ACT257N,D	MC74ACT257N,D	Quad 2-1 Data Selector/Multiplexer, NINV (3-State)	DIP-16, SO-16
IN74ACT258N,D	MC74ACT258N,D	Quad 2-1 Data Selector/Multiplexer, INV (3-State)	DIP-16, SO-16
IN74ACT273N,DW	MC74ACT273N,D	Octal D-Type Flip-Flop	DIP-20, SO-20
IN74ACT299N,DW	MC74ACT299N,D	8-Bit Universal Shift/Storage Register (3-State)	DIP-20, SO-20

• **IN74ACTXXXXN, D(DW) Series** (continued)

Part	Pin to Pin Compatibility	Function	Package
IN74ACT323N,DW	MC74ACT323N,D	8-Bit Universal Shift/Storage Register (3-State)	DIP-20, SO-20
IN74ACT373N,DW	MC74ACT373N,DW	Octal D-Type Latch (3-State)	DIP-20, SO-20
IN74ACT374N,DW	MC74ACT374N,DW	Octal D-Type Flip-Flop (3-State)	DIP-20, SO-20
IN74ACT533N,DW	MC74ACT533N,DW	Octal D-Type Latch, INV (3-State)	DIP-20, SO-20
IN74ACT534N,DW	MC74ACT534N,DW	Octal D-Type Flip-Flop, NINV (3-State)	DIP-20, SO-20
IN74ACT563N,DW	MC74ACT563N,DW	Octal D-Type Transparent Latch	DIP-20, SO-20
IN74ACT564N,DW	MC74ACT564N,DW	Octal Edge-Triggered Flip-Flop	DIP-20, SO-20
IN74ACT573N,DW	MC74ACT573N,DW	Octal Transparent Latch (3-State)	DIP-20, SO-20
IN74ACT574N,DW	MC74ACT574N,DW	Octal D-Type Flip-Flop, NINV (3-State)	DIP-20, SO-20
IN74ACT620N,DW	MC74ACT620N,DW	Octal Bidirectional Bus Transceiver, INV	DIP-20, SO-20
IN74ACT623N,DW	MC74ACT623N,DW	Octal Bidirectional Bus Transceiver, NINV	DIP-20, SO-20
IN74ACT640N,DW	MC74ACT640N,DW	Octal Bus Transceiver (3-State)	DIP-20, SO-20
IN74ACT643N,DW	MC74ACT643N,DW	Octal Bus Transceiver (3-State)	DIP-20, SO-20
IN74ACT651N,DW	CD74ACT651D	Octal Bus Transceiver/Register, INV (3-State)	DIP-24, SO-24
IN74ACT652N,DW	own	Octal Bus Transceiver/Register, NINV (3-State)	DIP-24, SO-24
IN74ACT810N,D	IN74ACT810D	Quad Exclusive-NOR Gate	DIP-14, SO-14
IN74ACT4006N,D	own	18-Bit Static Shift Register	DIP-14, SO-14
IN74ACT4015N,D	own	Dual 4-Bit Static Shift Register	DIP-16, SO-16
IN74ACT4035N,D	own	4-Bit Parallel-In/Parallel-Out Shift Register	DIP-16, SO-16
IN74ACT4520N,D	own	Dual 4-Bit Synchronous Binary Counter	DIP-16, SO-16

• **IN74VHCXXXD(DW)**

Part	Pin to Pin Compatibility	Function	Package
IN74VHC00D	TC74VHC00D	Quad 2-Input NAND Gate	SO-14
IN74VHC02D	TC74VHC02D	Quad 2-Input NOR Gate	SO-14
IN74VHC08D	TC74VHC08D	Quad 2-Input AND Gate	SO-14
IN74VHC32D	TC74VHC32D	Quad 2-Input OR Gate	SO-14
IN74VHC74D	TC74VHC74D	Dual D-type Flip-Flop	SO-14
IN74VHC125D	TC74VHC125D	Quad 3-State Buffer	SO-14
IN74VHC126D	TC74VHC126D	Quad 3-State Buffer	SO-14
IN74VHC240DW	TC74VHC240D	Octal Buffer/Line Driver, INV (3-State)	SO-20
IN74VHC241DW	TC74VHC241D	Octal Buffer/Line Driver, NINV (3-State)	SO-20
IN74VHC244DW	TC74VHC244D	Octal Buffer/Line Driver NINV (3-State)	SO-20
IN74VHC373DW	TC74VHC373D	Octal D-Type Latch (3-State)	SO-20
IN74VHC374DW	TC74VHC374D	Octal D-Type Flip-Flop (3-State)	SO-20

• **IN74VHCTXXXD(DW)**

Part	Pin to Pin Compatibility	Function	Package
IN74VHCT00D	TC74VHCT00D	Quad 2-Input NAND Gate	SO-14
IN74VHCT02D	TC74VHCT02D	Quad 2-Input NOR Gate	SO-14
IN74VHCT08D	TC74VHCT08D	Quad 2-Input AND Gate	SO-14
IN74VHCT32D	TC74VHCT32D	Quad 2-Input OR Gate	SO-14
IN74VHCT74D	TC74VHCT74D	Dual D-type Flip-Flop	SO-14
IN74VHCT125D	TC74VHCT125D	Quad 3-State Buffer	SO-14
IN74VHCT126D	TC74VHCT126D	Quad 3-State Buffer	SO-14
IN74VHCT240DW	TC74VHCT240D	Octal Buffer/Line Driver, INV (3-State)	SO-20
IN74VHCT241DW	TC74VHCT241D	Octal Buffer/Line Driver, NINV (3-State)	SO-20
IN74VHCT244DW	TC74VHCT244D	Octal Buffer/Line Driver NINV (3-State)	SO-20
IN74VHCT373DW	TC74VHCT373D	Octal D-Type Latch (3-State)	SO-20
IN74VHCT374DW	TC74VHCT374D	Octal D-Type Flip-Flop (3-State)	SO-20



INTEGRATED CIRCUITS

Power Electronics, Standard Analog IC, Standard Digital Logic IC

• IN74HCXXXXAN, D(DW) Series

Part	Pin to Pin Compatibility	Function	Package
IN74HC00AN,AD	MC74HC00AN,AD	Quad 2-Input NAND Gate	DIP-14, SO-14
IN74HC02AN,AD	MC74HC02AN,AD	Quad 2-Input NOR Gate	DIP-14, SO-14
IN74HC03AN,AD	MC74HC03AN,AD	Quad 2-Input NAND Gate, OC	DIP-14, SO-14
IN74HC04AN,AD	MC74HC04AN,AD	Hex Inverter	DIP-14, SO-14
IN74HC05AN,AD	SN74HC05AN,AD	Hex Inverter, OC	DIP-14, SO-14
IN74HC08AN,AD	MC74HC08AN,AD	Quad 2-Input AND Gate	DIP-14, SO-14
IN74HC10AN,AD	MC74HC10AN,AD	Triple 3-Input NAND Gate	DIP-14, SO-14
IN74HC11AN,AD	MC74HC11AN,AD	Triple 3-Input AND Gate	DIP-14, SO-14
IN74HC14AN,AD	MC74HC14AN,AD	Hex Schmitt-Trigger Inverter	DIP-14, SO-14
IN74HC20AN,AD	MC74HC20AN,AD	Dual 4-Input NAND Gate	DIP-14, SO-14
IN74HC21AN,AD	MC74HC21AN,AD	Dual 4-Input Positive-AND Gate	DIP-14, SO-14
IN74HC22AN,AD	MC74HC22AN,AD	Dual 4-Input Positive-NAND Gate, OC	DIP-14, SO-14
IN74HC27AN,AD	MC74HC27AN,AD	Triple 3-Input Positive-NOR Gate	DIP-14, SO-14
IN74HC30AN,AD	MC74HC30AN,AD	8-Input Positive-NAND Gate	DIP-14, SO-14
IN74HC32AN,AD	MC74HC32AN,AD	Quad 2-Input OR Gate	DIP-14, SO-14
IN74HC74AN,AD	MC74HC74AN,AD	Dual D-Type Flip-Flop	DIP-14, SO-14
IN74HC75AN,AD	MC74HC75AN,AD	Quad Bistable Latch	DIP-16, SO-16
IN74HC85AN,AD	MC74HC85AN,AD	4-Bit Magnitude Comparator	DIP-16, SO-16
IN74HC86AN,AD	MC74HC86AN,AD	Quad 2-Input Exclusive-OR Gate	DIP-14, SO-14
IN74HC109AN,AD	MC74HC109AN,AD	Dual J-K Positive-Edge-Triggered Flip-Flop	DIP-16, SO-16
IN74HC112AN,AD	MC74HC112AN,AD	Dual J-K Negative-Edge-Triggered Flip-Flop	DIP-16, SO-16
IN74HC123AN,AD	MC74HC123AN,AD	Dual Monostable Multivibrator with Reset	DIP-16, SO-16
IN74HC125AN,AD	MC74HC125AN,AD	Quad 3-State Buffer	DIP-14, SO-14
IN74HC132AN,AD	MC74HC132AN,AD	Quad 2-Input NAND Schmitt-Trigger Inverter	DIP-14, SO-14
IN74HC138AN,AD	MC74HC138AN,AD	3-8 Decoder/Demultiplexer	DIP-16, SO-16
IN74HC139AN,AD	MC74HC139AN,AD	Dual 2-4 Decoder/Demultiplexer	DIP-16, SO-16
IN74HC151AN,AD	MC74HC151AN,AD	8-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74HC153AN,AD	MC74HC153AN,AD	Dual 4-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74HC154AN,ADW	MC74HC154AN,ADW	4-16 Decoder/Demultiplexer (3-State)	DIP-24, SO-24
IN74HC155AN,AD	MM74HC155AN,AD	Dual 2-4 Decoder/Demultiplexer	DIP-16, SO-16
IN74HC157AN,AD	MC74HC157AN,AD	Quad 2-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74HC158AN,AD	MC74HC158AN,AD	Quad 2-1 Data Selector/Multiplexer, INV	DIP-16, SO-16
IN74HC161AN,AD	MC74HC161AN,AD	4-Bit Synchronous Binary Counter, Asynchronous Reset	DIP-16, SO-16
IN74HC163AN,AD	MC74HC163AN,AD	4-Bit Synchronous Binary Counter, Synchronous Reset	DIP-16, SO-16
IN74HC164AN,AD	MC74HC164AN,AD	8-Bit Serial-In Parallel-Out Shift Register	DIP-14, SO-14
IN74HC165AN,AD	MC74HC165AN,AD	8-Bit Parallel-in Serial-Out Shift Register	DIP-16, SO-16
IN74HC166AN,AD	CD74HC166AN,AD	8-Bit Parallel-in Serial-Out Shift Register	DIP-16, SO-16
IN74HC174AN,AD	MC74HC174AN,AD	Hex D-Type Flip-Flop	DIP-16, SO-16
IN74HC175AN,AD	MC74HC175AN,AD	Quad D-Type Flip-Flop	DIP-16, SO-16
IN74HC192AN,AD	CD74HC192AN,AD	Synchronous Decade Up/Down Counter	DIP-16, SO-16
IN74HC193AN,AD	CD74HC193AN,AD	4-Bit Synchronous Binary Up/Down Counter	DIP-16, SO-16
IN74HC221AN,AD	CD74HC221AN,AD	Dual Monostable Multivibrator with Reset	DIP-16, SO-16
IN74HC240AN,ADW	MC74HC240AN,ADW	Octal Buffer/Line Driver, INV (3-State)	DIP-20, SO-20
IN74HC241AN,ADW	MC74HC241AN,ADW	Octal Buffer/Line Driver, NINV (3-State)	DIP-20, SO-20
IN74HC244AN,ADW	MC74HC244AN,AD	Octal Buffer/Line Driver NINV (3-State)	DIP-20, SO-20
IN74HC245AN,ADW	MC74HC245AN,AD	Octal Bus Transceiver, NINV (3-State)	DIP-20, SO-20
IN74HC251AN,AD	MC74HC251AN,AD	8-I Data Selector/Multiplexer (3-State)	DIP-16, SO-16
IN74HC253AN,AD	MC74HC253AN,AD	Dual 4-1 Data Selector/Multiplexer, NINV (3-State)	DIP-16, SO-16
IN74HC257AN,AD	MC74HC257AN,AD	Quad 2-1 Data Selector/Multiplexer, NINV (3-State)	DIP-16, SO-16
IN74HC258AN,AD	CD74HC258AN,AD	Quad 2-1 Data Selector/Multiplexer, INV (3-State)	DIP-16, SO-16
IN74HC273AN,ADW	MC74HC273AN,AD	Octal D-Type Flip-Flop	DIP-20, SO-20
IN74HC279AN,AD	MC74HC279AN,AD	Quad Set/Reset Latch	DIP-16, SO-16
IN74HC283AN,AD	CD74HC283AN,AD	4-Bit Full Adder	DIP-16, SO-16
IN74HC299AN,ADW	MC74HC299AN,AD	8-Bit Universal Shift/Storage Register (3-State)	DIP-20, SO-20
IN74HC323AN,ADW	MC74HC323AN,AD	8-Bit Universal Shift/Storage Register (3-State)	DIP-20, SO-20
IN74HC365AN,AD	MC74HC365AN,AD	Hex Buffer/Line Driver (3-State)	DIP-16, SO-16

• **IN74HCXXXXAN, D(DW) Series**

(continued)

Part	Pin to Pin Compatibility	Function	Package
IN74HC367AN,AD	MC74HC367AN,AD	Hex Buffer/Line Driver (3-State)	DIP-16, SO-16
IN74HC373AN,ADW	MC74HC373AN,AD	Octal D-Type Latch (3-State)	DIP-20, SO-20
IN74HC374AN,ADW	MC74HC374AN,AD	Octal D-Type Flip-Flop (3-State)	DIP-20, SO-20
IN74HC393AN,AD	MC74HC393AN,AD	Dual 4-Bit Binary Counter	DIP-14, SO-14
IN74HC533AN,ADW	MC74HC533AN,AD	Octal D-Type Latch, INV (3-State)	DIP-20, SO-20
IN74HC534AN,ADW	MC74HC534AN,AD	Octal D-Type Flip-Flop, NINV (3-State)	DIP-20, SO-20
IN74HC573AN,ADW	MC74HC573AN,AD	Octal Transparent Latch (3-State)	DIP-20, SO-20
IN74HC574AN,ADW	MC74HC574AN,AD	Octal D-Type Flip-Flop, NINV (3-State)	DIP-20, SO-20
IN74HC595AN,AD	MC74HC595AN,AD	8-Bit Shift Register with Output Latch	DIP-16, SO-16
IN74HC597AN,AD	MC74HC597AN,AD	8-Bit Shift Register with Input Latch	DIP-16, SO-16
IN74HC620AN,ADW	SN74HC620AN,AD	Octal Bidirectional Bus Transceiver, INV	DIP-20, SO-20
IN74HC623AN,ADW	SN74HC623AN,AD	Octal Bidirectional Bus Transceiver, NINV	DIP-20, SO-20
IN74HC640AN,ADW	MC74HC640AN,AD	Octal Bus Transceiver (3-State)	DIP-20, SO-20
IN74HC651AN,ADW	CD74HC651AN,AD	Octal Bus Transceiver/Register (3-State)	DIP-24, SO-24
IN74HC652AN,ADW	CD74HC652AN,AD	Octal Bus Transceiver/Register, NINV (3-State)	DIP-24, SO-24
IN74HC874AN,ADW	own	Dual 4-Bit D-Type Flip Flop	DIP-24, SO-24
IN74HC4015AN,AD	MC74HC4015AN,AD	Dual 4-Bit Static Shift Register	DIP-16, SO-16
IN74HC4046AN,AD	MC74HC4046AN,AD	Phase-Locked Loop	DIP-16, SO-16
IN74HC4051AN,AD	MC74HC4051AN,AD	8-Channel Analog Multiplexer/Demultiplexer	DIP-16, SO-16
IN74HC4052AN,AD	MC74HC4052AN,AD	Dual 4-Channel Analog Multiplexer/Demultiplexer	DIP-16, SO-16
IN74HC4053AN,AD	MC74HC4053AN,AD	Triple 2-Channel Analog Multiplexer/Demultiplexer	DIP-16, SO-16
IN74HC4094AN,AD	CD74HC4094AN,AD	8-Bit Shift and Bus Register	DIP-16, SO-16

• **IN74HCTXXXAN, D(DW) Series**

Part	Pin to Pin Compatibility	Function	Package
IN74HCT00AN,AD	MC74HCT00AN,AD	Quad 2-Input NAND Gate	DIP-14, SO-14
IN74HCT02AN,AD	MC74HCT02AN,AD	Quad 2-Input NOR Gate	DIP-14, SO-14
IN74HCT04AN,AD	MC74HCT04AN,AD	Hex Inverter	DIP-14, SO-14
IN74HCT08AN,AD	MC74HCT08AN,AD	Quad 2-Input AND Gate	DIP-14, SO-14
IN74HCT10AN,AD	MC74HCT10AN,AD	Triple 3-Input NAND Gate	DIP-14, SO-14
IN74HCT14AN,AD	MC74HCT14AN,AD	Hex Schmitt-Trigger Inverter	DIP-14, SO-14
IN74HCT20AN,AD	MC74HCT20AN,AD	Dual 4-Input NAND Gate	DIP-14, SO-14
IN74HCT27AN,AD	MC74HCT27AN,AD	Triple 3-Input Positive-NOR Gate	DIP-14, SO-14
IN74HCT30AN,AD	MC74HCT30AN,AD	8-Input Positive-NAND Gate	DIP-14, SO-14
IN74HCT32AN,AD	MC74HCT32AN,AD	Quad 2-Input OR Gate	DIP-14, SO-14
IN74HCT74AN,AD	MC74HCT74AN,AD	Dual D-Type Flip-Flop	DIP-14, SO-14
IN74HCT85AN,AD	MC74HCT85AN,AD	4-But Magnitude Comparator	DIP-16, SO-16
IN74HCT86AN,AD	MC74HCT86AN,AD	Quad 2-Input Exclusive-OR Gate	DIP-14, SO-14
IN74HCT125AN,AD	MC74HCT125AN,AD	Quad 3-State Buffer	DIP-14, SO-14
IN74HCT126AN,AD	MC74HCT126AN,AD	Quad 3-State Buffer	DIP-14, SO-14
IN74HCT132AN,AD	MC74HCT132AN,AD	Quad 2-Input NAND Schmitt-Trigger Inverter	DIP-14, SO-14
IN74HCT138AN,AD	MC74HCT138AN,AD	3-8 Decoder/Demultiplexer	DIP-16, SO-16
IN74HCT139AN,AD	MC74HCT139AN,AD	Dual 2-4 Decoder/Demultiplexer	DIP-16, SO-16
IN74HCT151AN,AD	MC74HCT151AN,AD	8-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74HCT153AN,AD	MC74HCT153AN,AD	Dual 4-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74HCT155AN,AD	MM74HCT155AN,AD	Dual 2-4 Decoder/Demultiplexer	DIP-16, SO-16
IN74HCT157AN,AD	MC74HCT157AN,AD	Quad 2-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74HCT163AN,AD	MC74HCT163AN,AD	4-Bit Synchronous Binary Counter, Synchronous Reset	DIP-16, SO-16
IN74HCT164AN,AD	MC74HCT164AN,AD	8-Bit Serial-in Parallel-Out Shift Register	DIP-14, SO-14
IN74HCT165AN,AD	MC74HCT165AN,AD	8-Bit Parallel-in Serial-Out Shift Register	DIP-16, SO-16
IN74HCT174AN,AD	MC74HCT174AN,AD	Hex D-Type Flip-Flop	DIP-16, SO-16
IN74HCT240AN,ADW	MC74HCT240AN,AD	Octal Buffer/Line Driver, INV (3-State)	DIP-20, SO-20

INTEGRATED CIRCUITS

Power Electronics, Standard Analog IC, Standard Digital Logic IC

• IN74HCTXXXAN, D(DW) Series

(continued)

Part	Pin to Pin Compatibility	Function	Package
IN74HCT241AN,ADW	MC74HCT241AN,AD	Octal Buffer/Line Driver, NINV (3-State)	DIP-20, SO-20
IN74HCT244AN,ADW	MC74HCT244AN,AD	Octal Buffer/Line Driver NINV (3-State)	DIP-20, SO-20
IN74HCT245AN,ADW	MC74HCT245AN,AD	Octal Bus Transceiver, NINV (3-State)	DIP-20, SO-20
IN74HCT251AN,AD	MC74HCT251AN,AD	8-1 Data Selector/Multiplexer, INV (3-State)	DIP-16, SO-16
IN74HCT273AN,ADW	MC74HCT273AN,AD	Octal D-Type Flip-Flop	DIP-20, SO-20
IN74HCT283AN,AD	CD74HCT283AN,AD	4-Bit Adder	DIP-16, SO-16
IN74HCT299AN,ADW	MC74HCT299AN,AD	8-Bit Universal Shift/Storage Register (3-State)	DIP-20, SO-20
IN74HCT323AN,ADW	MC74HCT323AN,AD	8-Bit Universal Shift/Storage Register (3-State)	DIP-20, SO-20
IN74HCT373AN,ADW	MC74HCT373AN,AD	Octal D-Type Latch (3-State)	DIP-20, SO-20
IN74HCT374AN,ADW	MC74HCT374AN,AD	Octal D-Type Flip-Flop (3-State)	DIP-20, SO-20
IN74HCT573AN,ADW	MC74HCT573AN,AD	Octal Transparent Latch (3-State)	DIP-20, SO-20
IN74HCT574AN,ADW	MC74HCT574AN,AD	Octal D-Type Flip-Flop, NINV (3-State)	DIP-20, SO-20
IN74HCT620AN,ADW	SN74HCT620AN,AD	Octal Bidirectional Bus Transceiver, INV	DIP-20, SO-20
IN74HCT623AN,ADW	own	Octal Bidirectional Bus Transceiver, NINV	DIP-20, SO-20
IN74HCT640AN,ADW	own	Octal Bus Transceiver (3-State)	DIP-20, SO-20
IN74HCT874AN,ADW	MC74HCT874AN,AD	Dual 4-Bit D-Type Flip-Flop	DIP-24, SO-24

• IN74LVXXXN, D(DW) Series

Part	Pin to Pin Compatibility	Function	Package
IN74LV00N,D	74LV00N,D	Quad 2-Input NAND Gate	DIP-14, SO-14
IN74LV02N,D	74LV02N,D	Quad 2-Input NOR Gate	DIP-14, SO-14
IN74LV04N,D	74LV04N,D	Hex Inverter	DIP-14, SO-14
IN74LVU04N,D	74LVU04N,D	Hex Inverter	DIP-14, SO-14
IN74LV08N,D	74LV08N,D	Quad 2-Input AND Gate	DIP-14, SO-14
IN74LV14N,D	74LV14N,D	Hex Schmitt-Trigger Inverter	DIP-14, SO-14
IN74LV32N,D	74LV32N,D	Quad 2-Input OR Gate	DIP-14, SO-14
IN74LV74N,D	74LV74N,D	Dual D-Type Flip-Flop	DIP-14, SO-14
IN74LV86N,D	74LV86N,D	Quad 2-Input Exclusive-OR Gate	DIP-14, SO-14
IN74LV138N,D	74LV138N,D	3-8 Decoder/Demultiplexer	DIP-16, SO-16
IN74LV139N,D	74LV139N,D	Dual 2-4 Decoder/Demultiplexer	DIP-16, SO-16
IN74LV164N,D	74LV164N,D	8-Bit Serial-In Parallel-Out Shift Register	DIP-14, SO-14
IN74LV174N,D	74LV174N,D	Hex D-Type Flip-Flop	DIP-16, SO-16
IN74LV240N,DW	74LV240N,D	Octal Buffer/line Driver, INV (3-State)	DIP-20, SO-20
IN74LV241N,DW	74LV241N,D	Octal Buffer/Line Driver, NINV (3-State)	DIP-20, SO-20
IN74LV244N,DW	74LV244N,D	Octal Buffer/Line Driver, NINV (3-State)	DIP-20, SO-20
IN74LV245N,DW	74LV245N,D	Octal Bus Transceiver, NINV (3-State)	DIP-20, SO-20
IN74LV273N,DW	74LV273N,D	Octal D-Type Flip-Flop	DIP-20, SO-20
IN74LV373N,DW	74LV373N,D	Octal D-Type Latch (3-State)	DIP-20, SO-20
IN74LV374N,DW	74LV374N,D	Octal D-Type Flip-Flop (3-State)	DIP-20, SO-20
IN74LV573N,DW	74LV573N,D	Octal Transparent Latch (3-State)	DIP-20, SO-20
IN74LV574N,DW	74LV574N,D	Octal D-Type Flip-Flop, NINV (3-State)	DIP-20, SO-20
IN74LV620N,DW	74LV620N,D	Octal Bidirectional Bus Transceiver, INV	DIP-20, SO-20
IN74LV623N,DW	74LV623N,D	Octal Bidirectional Bus Transceiver, NINV	DIP-20, SO-20
IN74LV640N,DW	74LV640N,D	Octal Bus Transceiver (3-State)	DIP-20, SO-20

• IN74XXXN, D Series

Part	Pin to Pin Compatibility	Function	Package
IN7401N	SN7401N	Quad 2-Input NAND Gate, OC	DIP-14
IN7406N,D	SN7406N,D	Hex Inverter/Buffer with High-Voltage Output, OC	DIP-14, SO-14
IN7420N	SN7420N	Dual 4-Input NAND Gate	DIP-14
IN7450N	SN7450N	Dual 2-Wide 2-Input AND-OR-Invert Gate	DIP-14
IN7472N	SN7472N	J-K Flip-Flop	DIP-14
IN74141N	SN74141N	BCD-to-Decimal Decoder/Driver	DIP-16
IN74145N	SN74145N	BCD-to-Decimal Decoder, OC	DIP-16
IN74154N	SN74154N	4-16 Decoder/Demultiplexer	DIP-24
IN74175N	SN74175N	Quad D-Type Flip-Flop	DIP-16

• IN74LSXXXN, D(DW) Series

Part	Pin to Pin Compatibility	Function	Package
IN74LS04N,D	CD74LS04N,D	Hex Inverter	DIP-14, SO-14
IN74LS05N,D	CD74LS05N,D	Hex Inverter, OC	DIP-14, SO-14
IN74LS06N,D	CD74LS06N,D	Hex Inverter/Buffer with High-Voltage Output, OC	DIP-14, SO-14
IN74LS07N,D	CD74LS07N,D	Hex Buffer with High-Voltage Output, OC, 30 V	DIP-14, SO-14
IN74LS14N,D	CD74LS14N,D	Hex Schmitt-Trigger Inverter	DIP-14, SO-14
IN74LS86N,D	CD74LS86N,D	Quad 2-Input Exclusive-OR Gate	DIP-14, SO-14
IN74LS138N,D	CD74LS138N,D	3-8 Decoder/Demultiplexer	DIP-16, SO-16
IN74LS157N,D	CD74LS157N,D	Quad 2-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74LS161AN,AD	CD74LS161AN,AD	4-Bit Binary Counter	DIP-16, SO-16
IN74LS164N,D	CD74LS164N,D	8-Bit Parallel-Out Shift Register	DIP-14, SO-14
IN74LS244N,DW	CD74LS244N,DW	Octal Buffer/Line Driver, NINV (3-State)	DIP-20, SO-20
IN74LS245N,DW	CD74LS245N,DW	Octal Bus Transceiver, NINV (3-State)	DIP-20, SO-20

• IN74ALSXXXXN, D(DW) Series

Part	Pin to Pin Compatibility	Function	Package
IN74ALS00AN,AD	SN74ALS00AN,AD	Quad 2-Input Positive-NAND Gate	DIP-14, SO-14
IN74ALS01N,D	SN74ALS01N,D	Quad 2-Input Positive-NAND Gate, OC	DIP-14, SO-14
IN74ALS02N,D	SN74ALS02N,D	Quad 2-Input Positive-NOR Gate	DIP-14, SO-14
IN74ALS03AN,AD	SN74ALS03AN,AD	Quad 2-Input Positive-NAND Gate, OC	DIP-14, SO-14
IN74ALS04AN,AD	SN74ALS04AN,AD	Hex Inverter	DIP-14, SO-14
IN74ALS05AN,AD	SN74ALS05AN,AD	Hex Inverter, OC	DIP-14, SO-14
IN74ALS08N,D	SN74ALS08N,D	Quad 2-Input Positive-AND Gate	DIP-14, SO-14
IN74ALS09N,D	SN74ALS09N,D	Quad 2-Input Positive-AND Gate, OC	DIP-14, SO-14
IN74ALS10AN,AD	SN74ALS10AN,AD	Triple 3-Input Positive-NAND Gate	DIP-14, SO-14
IN74ALS11AN,AD	SN74ALS11AN,AD	Triple 3-Input Positive-AND Gate	DIP-14, SO-14
IN74ALS12AN,AD	SN74ALS12AN,AD	Triple 3-Input Positive-NAND Gate, OC	DIP-14, SO-14
IN74ALS14N,D	SN74ALS14N,D	Hex Schmitt-Trigger Inverter	DIP-14, SO-14
IN74ALS15AN,AD	SN74ALS15AN,AD	Triple 3-Input Positive-AND Gate, OC	DIP-14, SO-14
IN74ALS20AN,AD	SN74ALS20AN,AD	Dual 4-Input Positive-NAND Gate	DIP-14, SO-14
IN74ALS21N,AD	SN74ALS21N,AD	Dual 4-Input Positive-AND Gate	DIP-14, SO-14
IN74ALS22BN,BD	SN74ALS22BN,BD	Dual 4-Input Positive-NAND Gate, OC	DIP-14, SO-14
IN74ALS27N,D	SN74ALS27N,D	Triple 3-Input Positive-NOR Gate	DIP-14, SO-14
IN74ALS30AN,AD	SN74ALS30AN,AD	8-Input Positive-NAND Gate	DIP-14, SO-14
IN74ALS32N,D	SN74ALS32N,D	Quad 2-Input Positive-OR Gate	DIP-14, SO-14
IN74ALS33AN,AD	SN74ALS33AN,AD	Quad 2-Input Positive-NOR Buffer, OC	DIP-14, SO-14

INTEGRATED CIRCUITS

Power Electronics, Standard Analog IC, Standard Digital Logic IC

• IN74ALSXXXXN, D(DW) Series (continued)

Part	Pin to Pin Compatibility	Function	Package
IN74ALS51N,D	SN74ALS51N,D	AND-OR-Invert Gate	DIP-14, SO-14
IN74ALS54N,D	SN74ALS54N,D	4-Wide AND-OR-Invert Gate	DIP-14, SO-14
IN74ALS55N,D	SN74ALS55N,D	2-Wide 4-Input AND-OR-Invert Gate	DIP-14, SO-14
IN74ALS74AN,AD	SN74ALS74AN,AD	Dual D-Type Flip-Flop	DIP-14, SO-14
IN74ALS75N,D	SN74ALS75N,D	Quad Bistable Latch	DIP-16, SO-16
IN74ALS85N,D	SN74ALS85N,D	4-Bit Magnitude Comparator	DIP-16, SO-16
IN74ALS86N,D	SN74ALS86N,D	Quad 2-Input Exclusive-OR Gate	DIP-14, SO-14
IN74ALS90N,D	SN74ALS90N,D	4-Bit Decade Counter	DIP-14, SO-14
IN74ALS93N,D	SN74ALS93N,D	4-Bit Binary Counter	DIP-14, SO-14
IN74ALS107N,D	SN74ALS107N,D	Dual J-K Flip-Flop with Clear	DIP-14, SO-14
IN74ALS109N,D	SN74ALS109N,D	Dual J-K Positive-Edge-Triggered Flip-Flop	DIP-16, SO-16
IN74ALS112AN,AD	SN74ALS112AN,AD	Dual J-K Negative-Edge-Triggered Flip-Flop	DIP-16, SO-16
IN74ALS113AN,AD	SN74ALS113AN,AD	Dual J-K Negative-Edge-Triggered Flip-Flop	DIP-14, SO-14
IN74ALS114AN,AD	SN74ALS114AN,AD	Dual J-K Negative-Edge-Triggered Flip-Flop	DIP-14, SO-14
IN74ALS123N,D	SN74ALS123N,D	Dual Monostable Multivibrator with Reset	DIP-16, SO-16
IN74ALS125N,D	SN74ALS125N,D	Quad 3-State Buffer	DIP-14, SO-14
IN74ALS136N,D	SN74ALS136N,D	Quad 2-Input Exclusive-OR Gate, OC	DIP-14, SO-14
IN74ALS138N,D	SN74ALS138N,D	3-8 Decoder/Demultiplexer	DIP-16, SO-16
IN74ALS139N,D	SN74ALS139N,D	Dual 2-4 Decoder/Demultiplexer	DIP-16, SO-16
IN74ALS151N,D	SN74ALS151N,D	8-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74ALS153N,D	SN74ALS153N,D	Dual 4-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74ALS154N,DW	SN74ALS154N,D	4-16 Decoder/Demultiplexer (3-State)	DIP-24, SO-24
IN74ALS155N,D	SN74ALS155N,D	Dual 2-4 Decoder/Demultiplexer	DIP-16, SO-16
IN74ALS157N,D	SN74ALS157N,D	Quad 2-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74ALS158N,D	SN74ALS158N,D	Quad 2-1 Data Selector/Multiplexer, INV	DIP-16, SO-16
IN74ALS160AN,AD	SN74ALS160AN,AD	Synchronous Decade Counter, Asynchronous Reset	DIP-16, SO-16
IN74ALS161AN,AD	SN74ALS161AN,AD	4-Bit Synchronous Binary Counter, Asynchronous Reset	DIP-16, SO-16
IN74ALS162AN,AD	SN74ALS162AN,AD	Synchronous Decade Counter, Synchronous Reset	DIP-16, SO-16
IN74ALS163AN,AD	SN74ALS163AN,AD	4-Bit Synchronous Binary Counter, Synchronous Reset	DIP-16, SO-16
IN74ALS164N,D	SN74ALS164N,D	8-Bit Serial-In Parallel-Out Shift Register	DIP-14, SO-14
IN74ALS165N,D	SN74ALS165N,D	8-Bit Parallel-in Serial-Out Shift Register	DIP-16, SO-16
IN74ALS166N,D	SN74ALS166N,D	8-Bit Parallel-in Serial-Out Shift Register	DIP-16, SO-16
IN74ALS170N,D	SN74ALS170N,D	4-by-4 Register File, OC	DIP-16, SO-16
IN74ALS173AN,AD	SN74ALS173AN,AD	4-Bit D-Type Register (3-State)	DIP-16, SO-16
IN74ALS174N,D	SN74ALS174N,D	Hex D-Type Flip-Flop	DIP-16, SO-16
IN74ALS175N,D	SN74ALS175N,D	Quad D-Type Flip-Flop	DIP-16, SO-16
IN74ALS181N,DW	SN74ALS181N,D	4-Bit Arithmetic Logic Unit	DIP-24, SO-24
IN74ALS182N,D	SN74ALS182N,D	Look-Ahead Carry Generator	DIP-16, SO-16
IN74ALS190N,D	SN74ALS190N,D	Synchronous Decade Up/Down Counter	DIP-16, SO-16
IN74ALS191N,D	SN74ALS191N,D	4-Bit Synchronous Binary Up/Down Counter	DIP-16, SO-16
IN74ALS192N,D	SN74ALS192N,D	Synchronous Decade Up/Down Counter	DIP-16, SO-16
IN74ALS193N,D	SN74ALS193N,D	4-Bit Synchronous Binary Up/Down Counter	DIP-16, SO-16
IN74ALS240AN,ADW	SN74ALS240AN,AD	Octal Buffer/Line Driver, INV (3-State)	DIP-20, SO-20
IN74ALS241AN,ADW	SN74ALS241AN,AD	Octal Buffer/Line Driver, NINV (3-State)	DIP-20, SO-20
IN74ALS242AN,AD	SN74ALS242AN,AD	Quad Bus Transceiver, INV (3-State)	DIP-14, SO-14
IN74ALS243AN,AD	SN74ALS243AN,AD	Quad Bus Transceiver, NINV (3-State)	DIP-14, SO-14
IN74ALS244AN,ADW	SN74ALS244AN,AD	Octal Buffer/Line Driver, NINV (3-State)	DIP-20, SO-20
IN74ALS245AN,ADW	SN74ALS245AN,AD	Octal Bus Transceiver, NINV (3-State)	DIP-20, SO-20
IN74ALS251N,D	SN74ALS251N,D	8-1 Data Selector/Multiplexer, INV (3-State)	DIP-16, SO-16
IN74ALS253N,D	SN74ALS253N,D	Dual 4-1 Data Selector/Multiplexer, NINV (3-State)	DIP-16, SO-16
IN74ALS257AN,AD	SN74ALS257AN,AD	Quad 2-1 Data Selector/Multiplexer, NINV (3-State)	DIP-16, SO-16
IN74ALS258AN,AD	SN74ALS258AN,AD	Quad 2-1 Data Selector/Multiplexer, INV (3-State)	DIP-16, SO-16
IN74ALS259N,D	SN74ALS259N,D	8-Bit Addressable Latch	DIP-16, SO-16
IN74ALS273N,DW	SN74ALS273N,D	Octal D-Type Flip-Flop	DIP-20, SO-20
IN74ALS279N,D	SN74ALS279N,D	Quad Set/Reset Latch	DIP-16, SO-16
IN74ALS280N,D	SN74ALS280N,D	9-Bit Odd/Even Parity Generator/Checker	DIP-14, SO-14

• **IN74ALSXXXXN, D(DW) Series** (continued)

Part	Pin to Pin Compatibility	Function	Package
IN74ALS295BN,BD	SN74ALS295BN,BD	4-Bit Universal Shift Register	DIP-14, SO-14
IN74ALS298N,D	SN74ALS298N,D	Quad 2-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74ALS299N,DW	SN74ALS299N,D	8-Bit Universal Shift/Storage Register (3-State)	DIP-20, SO-20
IN74ALS323N,DW	SN74ALS323N,D	8-Bit Universal Shift/Storage Register (3-State)	DIP-20, SO-20
IN74ALS352N,D	SN74ALS352N,D	Dual 4-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74ALS353N,D	SN74ALS353N,D	Dual 4-1 Data Selector/Multiplexer (3-State)	DIP-16, SO-16
IN74ALS368N,D	SN74ALS368N,D	Hex Bus Driver (3-State)	DIP-16, SO-16
IN74ALS373N,DW	SN74ALS373N,D	Octal D-Type Latch (3-State)	DIP-20, SO-20
IN74ALS374AN,ADW	SN74ALS374AN,AD	Octal D-Type Flip-Flop (3-State)	DIP-20, SO-20
IN74ALS377AN,ADW	SN74ALS377AN,AD	Octal D-Type Flip-Flop with Enable	DIP-20, SO-20
IN74ALS393N,D	SN74ALS393N,D	Dual 4-Bit Binary Counter	DIP-14, SO-14
IN74ALS465AN,ADW	SN74ALS465AN,AD	Octal Buffer, NINV (3-State)	DIP-20, SO-20
IN74ALS466AN,ADW	SN74ALS466AN,AD	Octal Buffer, INV (3-State)	DIP-20, SO-20
IN74ALS573N,DW	SN74ALS573N,D	Octal Transparent Latch (3-State)	DIP-20, SO-20
IN74ALS574N,DW	SN74ALS574N,D	Octal D-Type Flip-Flop (3-State)	DIP-20, SO-20
IN74ALS640BN,BDW	SN74ALS640BN,BD	Octal Bus Transceiver (3-State)	DIP-20, SO-20
IN74ALS643AN,ADW	SN74ALS643AN,AD	Octal Bus Transceiver (3-State)	DIP-20, SO-20
IN74ALS670N,D	SN74ALS670N,D	4-by-4 Register File (3-State)	DIP-16, SO-16
IN74ALS873N,DW	SN74ALS873N,D	Dual 4-Bit D-Type Latch (3-State)	DIP-24, SO-24
IN74ALS874N,DW	SN74ALS874N,D	Dual 4-Bit D-Type Flip-Flop	DIP-24, SO-24
IN74ALS1000AN,AD	SN74ALS1000AN,AD	Quad 2-Input Positive-NAND Buffer	DIP-14, SO-14
IN74ALS1002AN,AD	SN74ALS1002AN,AD	Quad 2-Input Positive-NOR Buffer	DIP-14, SO-14
IN74ALS1003AN,AD	SN74ALS1003AN,AD	Quad 2-Input Positive-NAND Buffer, OC	DIP-14, SO-14
IN74ALS1004N,D	SN74ALS1004N,D	Hex Inverting Driver	DIP-14, SO-14
IN74ALS1005N,D	SN74ALS1005N,D	Hex Inverting Buffer, OC	DIP-14, SO-14
IN74ALS1008AN,AD	SN74ALS1008AN,AD	Quad 2-Input Positive-NAND Buffer	DIP-14, SO-14
IN74ALS1010AN,AD	SN74ALS1010AN,AD	Triple 3-Input Positive-NAND Buffer	DIP-14, SO-14
IN74ALS1011AN,AD	SN74ALS1011AN,AD	Triple 3-Input Positive-AND Buffer	DIP-14, SO-14
IN74ALS1020AN,AD	SN74ALS1020AN,AD	Dual 4-Input Positive-NAND Buffer	DIP-14, SO-14
IN74ALS1032AN,AD	SN74ALS1032AN,AD	Quad 2-Input Positive-OR Buffer/Driver	DIP-14, SO-14
IN74ALS1034N,D	SN74ALS1034N,D	Hex Driver	DIP-14, SO-14
IN74ALS1035N,D	SN74ALS1035N,D	Hex Noninverting Buffer, OC	DIP-14, SO-14

INTEGRATED CIRCUITS

Standard Digital Logic IC

• FUNCTIONAL SELECTION

GATES

Function	Part	Technology										Pins
		74AC	74ACT	74VHC	74VHCT	74HC	74HCT	74LV	74	74LS	74ALS	
Positive-NAND Gates												
8-Input	30					x	x				x	14
Dual 4-Input	20	x	x			x	x		x		x	14
	40											14
	1020										x	14
Triple 3-Input	10	x	x			x	x				x	14
	1010										x	14
Quad 2-Input	00	x	x	x	x	x	x	x		x		14
	132	x	x			x	x					14
	1000										x	14
Positive-NAND Gates, OC												
Dual 4-Input	22					x	x				x	14
Triple 3-Input	12										x	14
Quad 2-Input	01								x		x	14
	03					x					x	14
	1003										x	14
Positive-AND Gates, OC												
Triple 3-Input	15										x	14
Quad 2-Input	09										x	14
Positive-AND Gates												
Dual 4-Input	21	x	x			x	x				x	14
Triple 3-Input	11	x	x			x					x	14
	1011										x	14
Quad 2-Input	08	x	x	x	x	x	x	x		x		14
	1008										x	14
Positive-OR Gates												
Quad 2-Input	32	x	x	x	x	x	x	x		x		14
	1032										x	14
Positive-NOR Gates												
Triple 3-Input	27	x	x			x	x				x	14
Quad 2-Input	02	x	x	x	x	x	x	x		x		14
	33										x	14
	1002										x	14
Exclusive-OR Gates												
Quad 2-Input	86	x	x	x	x	x	x	x		x	x	14
	810	x	x									14
Quad 2-Input, OC	136										x	14
AND-OR Gates												
2-Wide 4-Input	55										x	14
4-Wide 2-3-3-2 Input	54										x	14
Dual 2-Wide 2-Input	51										x	14
Expandable Gates												
Dual 2-Wide AND-OR-Invert	50								x			14
4-Wide AND-OR-Invert	53											14
Dual 4-Input Expander	60											14

• FUNCTIONAL SELECTION

(continued)

HEX INVERTERS/NONINVERTERS

Function	Part	Technology										Pins
		74AC	74ACT	74VHC	74VHCT	74HC	74HCT	74LV	74	74LS	74ALS	
Hex Inverters	04	X	X			X	X	X		X	X	14
	U04							X				14
	05	X	X			X				X	X	14
	06								X	X		14
	14	X	X			X	X	X		X	X	14
	16											14
	1004										X	14
	1005										X	14
Hex Noninverters	34	X	X									14

DRIVERS AND BUS TRANSCEIVERS

Function	Part	Technology										Pins
		74AC	74ACT	74VHC	74VHCT	74HC	74HCT	74LV	74	74LS	74ALS	
Hex Drivers												
Hex Drivers	07									X		14
	1034										X	14
	1035										X	14
Noninverting Hex Buffers/Drivers	365					X						16
	367					X						16
	368										X	16
Drivers with 3-State Outputs												
Quad Buffer Drivers	125	X	X	X	X	X	X				X	14
	126			X	X		X					14
Octal Buffer/Drivers, NINV	241	X	X	X	X	X	X	X			X	20
	244	X	X	X	X	X	X	X		X	X	20
	465										X	20
Octal Buffer Drivers, INV	240	X	X	X	X	X	X	X			X	20
	466										X	20
Bus Transceivers with 3-State Outputs												
Quad Transceiver, NINV	243										X	14
Quad Transceiver, INV	242										X	14
Octal Transceiver	245	X	X			X	X	X		X	X	20
	620	X	X			X	X	X				20
	640	X	X			X	X	X			X	20
	643	X	X								X	20
Octal Bus Transceivers with Registers	651	X	X			X						24
	652	X	X			X						24
True Output Transceiver	623	X	X			X	X	X				20
50/75-Ohm Line Drivers												
Quad 2-Input Positive-NOR	128											14

INTEGRATED CIRCUITS

Standard Digital Logic IC

• FUNCTIONAL SELECTION

(continued)

FLIP-FLOPS

Function	Part	Technology										Pins
		74AC	74ACT	74VHC	74VHCT	74HC	74HCT	74LV	74	74LS	74ALS	
Dual and Single Flip-Flops												
Single J-K	72								x			14
Dual J-K Edge-Triggered	107										x	14
	109	x	x			x					x	16
	112	x	x			x					x	16
	113										x	14
	114										x	14
Dual D-Type	74	x	x	x	x	x	x	x			x	14
Quad and Hex Flip-Flops												
Quad D-Type	175	x	x			x			x		x	16
Hex D-Type	174	x	x			x	x	x			x	16
Quad J-K	279					x	x				x	16
D-Type Flip-Flops												
Octal (3-State)	374	x	x	x	x	x	x	x			x	20
	574	x	x			x	x	x			x	20
Octal with Clear	273	x	x			x	x	x			x	20
Dual 4-Bit with Clear	874					x	x				x	24
Octal with Enable	377										x	20
Octal Inverting (3-State)	534	x	x			x						20
	564	x	x									

LATCHES AND MULTIVIBRATORS

Function	Part	Technology										Pins
		74AC	74ACT	74VHC	74VHCT	74HC	74HCT	74LV	74	74LS	74ALS	
Lasches												
4-Bit Bistable	75					x					x	16
Quad Set/Reset	279					x	x				x	16
Transparent (3-State)	373	x	x	x	x	x	x	x			x	20
	573	x	x			x	x	x			x	20
Dual 4-Bit Transparent (3-State)	873										x	24
Inverting Transparent	533	x	x			x						20
	563	x	x									20
8-Bit Addressable	259										x	16
Multivibrators												
Dual Monostable with Clear	123					x					x	16
	221					x						20

• FUNCTIONAL SELECTION (continued)

REGISTERS

Function	Part	Technology										Pins
		74AC	74ACT	74VHC	74VHCT	74HC	74HCT	74LV	74	74LS	74ALS	
Shift Registers												
8-Bit Universal	198											24
	299	x	x			x	x			x		20
	323	x	x			x	x			x		20
4-Bit Parallel-in/ Parallel-out	295									x		14
	4035	x	x									16
8-Bit Serial-in Parallel-Out	164	x	x			x	x	x		x	x	14
8-Bit Parallel-in Serial-Out	165					x	x			x		16
	166					x				x		16
Dual 4-Bit Static	4015	x	x			x						16
8-Bit Shift and Store	4094					x						16
	4006	x	x									14
Shift Registers with Latches												
Serial-in Parallel-Out with Output Latches	595					x						16
Parallel-in Serial-Out with Input Latches	597					x						16
Register Files												
4-by-4, OC (3-State)	170									x		16
	670									x		16
Other Registers												
4-Bit D-Type Register (3-State)	173									x		16

COUNTERS

Function	Part	Technology										Pins
		74AC	74ACT	74VHC	74VHCT	74HC	74HCT	74LV	74	74LS	74ALS	
Synchronous Counters												
4-Bit Decade, Asynchronous Reset	160									x		16
	162									x		16
Decade Up/Down	190									x		16
	192	x	x			x				x		16
4-Bit Binary, Asynchronous Reset	161	x	x			x				x	x	16
	163	x	x			x	x			x		16
4-Bit Binary Up/Down	191									x		16
	193	x	x			x				x		16
Asynchronous Counters												
4-Bit Decade	90									x		14
4-Bit Binary	93									x		14
Dual 4-Bit Binary	393					x				x		14
	4520	x	x									16

INTEGRATED CIRCUITS

Standard Digital Logic IC

• FUNCTIONAL SELECTION (continued)

DECODERS, DATA SELECTORS/MULTIPLEXERS

Function	Part	Technology										Pins
		74AC	74ACT	74VHC	74VHCT	74HC	74HCT	74LV	74	74LS	74ALS	
Data Selectors/Multiplexers												
Quad 2-1	157	x	x			x	x			x	x	16
	158	x	x			x					x	16
	298										x	16
	257	x	x			x					x	16
	258	x	x			x					x	16
Dual 4-1	153	x	x			x	x				x	16
	253	x	x			x					x	16
	352										x	16
	353										x	16
8-1	151	x	x			x	x				x	16
	152											14
	251	x	x			x	x				x	16
16-1	150											24
Analog Multiplexers/Demultiplexers												
8-Channel	4051					x						16
Dual 4-Channel	4052					x						16
Triple 2-Channel	4053					x						16
Decoders												
Dual 2-4	139	x	x			x	x	x			x	16
	155					x	x				x	16
3-8	138	x	x			x	x	x		x	x	16
4-16	154					x			x		x	24
BCD-to-Decimal	141								x			16
	145								x			16
Digital Loops												
Phase-Lock Loop	4046					x						16

COMPARATORS AND ERROR DETECTION CIRCUITS

Function	Part	Technology										Pins
		74AC	74ACT	74VHC	74VHCT	74HC	74HCT	74LV	74	74LS	74ALS	
Comparators												
4-Bit Magnitude Comparator	85					x	x				x	16
Parity Generators/Checkers												
8-Bit Odd/Even Parity	180											14
9-Bit Odd/Even Parity	280										x	14

ARITHMETIC CIRCUITS

Function	Part	Technology										Pins
		74AC	74ACT	74VHC	74VHCT	74HC	74HCT	74LV	74	74LS	74ALS	
4-Bit Arithmetic Logic Unit	181										x	24
Look-Ahead Carry Generator	182										x	16
4-Bit Full Adder	283					x	x					16

• FAMILY CHARACTERISTICS

DC Characteristics (Max)

Parameters	TTL				CMOS				Units				
	74	74LS	74ALS	4000A	4000B	74AC	74ACT	74VHC	74VHCT	74HC	74HCT	74LV	
Supply Voltage Range, $V_{CC}(V_{DD})$	5±5%	5±5%	5±10%	3...15	3...18	2...6	5±10%	2...5.5	5±5%	2...6	5±10%	1.0...5.5	V
Operating Temperature, T_A	-10...+70	0...+70	-10...+70	-45...+85	-55...+125	-45...+85	-45...+85	-40...+85	-40...+85	-55...+125	-55...+125	-40...+125	°C
High-Level Input Voltage, V_{IH} (min)	2	2	0.8x V_{DD}	0.7x V_{DD}	0.7x V_{CC}	2	0.7x V_{CC}	2	0.7x V_{CC}	2	0.7x V_{CC}	2	V
Low-Level Input Voltage, V_{IL} (max)	0.8	0.8	0.8	0.2x V_{DD}	0.3x V_{DD}	0.3x V_{CC}	0.8	0.3x V_{CC}	0.8	0.3x V_{CC}	0.8	0.3x V_{CC}	V
High-Level Output Voltage, V_{OH} (min)	2.4	V_{CC} -2	V_{CC} -2	V_{DD} -1	V_{DD} -0.05	V_{CC} -0.1	V_{CC} -0.1	3.8	3.8	V_{CC} -0.1	V_{CC} -0.1	V_{CC} -0.2	V
Low-Level Output Voltage, V_{OL} (max)	0.4	0.5	0.5	0.05	0.05	0.1	0.1	0.44	0.44	0.1	0.1	0.2	V
High-Level Input Current, I_{IH}	40	20	20	+1	+0.3	+1	+1	+1	+1	+1	+1	+1	µA
Low-Level Input Current, I_{IL}	-1600	-400	-100	-1	-0.3	-1	-1	-1	-1	-1	-1	-1	µA
High-Level Output Current, I_{OH}	-0.4	-0.4	-0.4	-0.25 at $V_0=4.5$ V	-4.2 at $V_0=2.5$ V	-24 at $V_0=V_{CC}-0.8$	-24 at $V_0=V_{CC}-0.8$	-8	-8	$V_0=V_{CC}-0.8$	-4 at $V_0=V_{CC}-0.8$	-4 at $V_0=V_{CC}-0.8$	nA
Low-Level Output Current, I_{OL}	16	8	8	0.5 at $V_0=0.5$ V	0.88 at $V_0=0.4$ V	24 at $V_0=0.4$ V	24 at $V_0=0.4$ V	8	8	$V_0=0.4$ V	4 at $V_0=0.4$ V	4 at $V_0=0.4$ V	16 mA
DC Noise Margin, DCM	0.4/0.4	0.3/0.7	0.3/0.7	1.0 at $V_{DD}=5$ V	1.0 at $V_{DD}=5$ V	1.5 at $V_{DD}=5$ V	1.5 at $V_{DD}=5$ V	1.25/1.25	0.7/2.4	1.25/1.25	0.7/2.4	0.7/2.4	V



• FAMILY CHARACTERISTICS

DC Characteristics (Type)

Parameters	TTL				CMOS				Units				
	74	74LS	74ALS	4000A	4000B	74AC	74ACT	74VHC	74HCT	74HC	74HCT	74LV	
Supply Current for Gate, I_G	3.4	0.4	0.2	0.0004	0.0001	0.0005	0.0005	0.0005	0.0005	0.0005	0.0005	0.0005	mA
Power Supply for Gate, P_G	10	2	1	0.0025	0.0001	0.0025	0.0025	0.0025	0.0025	0.001	0.001	0.001	mW
Propagation Delay Time, T_P	10	7	5	40 at $V_{DD}=5\text{ V}$ 20 at $V_{DD}=10\text{ V}$ $V_{DD}=10\text{ V}$	40 at $V_{DD}=5\text{ V}$ 20 at $V_{DD}=10\text{ V}$ 15 at $V_{DD}=15\text{ V}$	5	5	5.3	5.5	8	8	10	ns
Clock Frequency, F_{max}	35	40	45	5 at $V_{DD}=5\text{ V}$ 10 at $V_{DD}=10\text{ V}$ 14 at $V_{DD}=15\text{ V}$ $C_L=50\text{ pF}$	5 at $V_{DD}=5\text{ V}$ 10 at $V_{DD}=10\text{ V}$ 14 at $V_{DD}=15\text{ V}$ $C_L=50\text{ pF}$	140 $C_L=50\text{ pF}$	140 $C_L=50\text{ pF}$	115 $C_L=50\text{ pF}$ 170 $C_L=15\text{ pF}$	140 $C_L=50\text{ pF}$ 160 $C_L=15\text{ pF}$	30 $C_L=50\text{ pF}$	30 $C_L=50\text{ pF}$	40 $C_L=50\text{ pF}$	MHz
C O M P A T I B I L I T Y	Inputs V_{IL}/V_{IH}	TTL	TTL	CMOS	CMOS	TTL, CMOS	TTL at $V_0=3.3\text{ V}$, CMOS	TTL, CMOS	TTL, CMOS	TTL, CMOS	TTL, CMOS	-	-
B L E	Outputs V_{OL}/V_{OH}	TTL	TTL	TTL, CMOS	TTL, CMOS	TTL, CMOS	TTL, CMOS	TTL, CMOS	TTL, CMOS	TTL, CMOS	TTL, CMOS	TTL, CMOS	-

• FAMILY CHARACTERISTICS

AC Characteristics

Parameters	Performance	TTL								CMOS								Units
		7400	74LS00	74ALS00	4001A	4001B	74AC00	74ACT00	74VHCT00	74VHCT00	74HC00	74HCT00	74HCT00	74LV00	74LV00			
Propagation Delay, t_{PHL}/t_{PHL}	Type C _L =15 pF	10 C _L =15 pF	7 C _L =15 pF	5 C _L =50 pF	80 at V _{DD} =5 V 40 at V _{DD} =10 V C _L =15 pF	60 at V _{DD} =5 V 25 at V _{DD} =10 V 20 at V _{DD} =15 V C _L =50 pF	5 C _L =50 pF	5 C _L =50 pF	5.4 C _L =50 pF 3.9 C _L =15 pF	5.9 C _L =50 pF 5.4 C _L =15 pF	8 C _L =50 pF	8 C _L =50 pF	10 C _L =50 pF	ns	ns	ns		
Propagation Delay, t_{PHL}/t_{PHL}	Gate, NOR or NAND	Max C _L =15 pF	22 C _L =15 pF	15 C _L =15 pF	11 C _L =50 pF	120 at V _{DD} =5 V 60 at V _{DD} =10 V C _L =15 pF	110 at V _{DD} =5 V 60 at V _{DD} =10 V 48 at V _{DD} =15 V C _L =50 pF	8.5 C _L =50 pF	9.5 C _L =50 pF	8.5 C _L =50 pF 6.5 C _L =15 pF	8.5 C _L =50 pF 7.5 C _L =15 pF	22 C _L =50 pF	28 C _L =50 pF	14 C _L =50 pF	ns	ns	ns	
Propagation Delay, t_{PHL}/t_{PHL}		74163 Type C _L =15 pF	74LS163 C _L =15 pF	74ALS163 C _L =50 pF	4163A 10 C _L =50 pF	4163B 10 C _L =50 pF	74AC163 180 at V _{DD} =5 V 80 at V _{DD} =10 V 65 at V _{DD} =15 V C _L =50 pF	74ACT163 5 C _L =50 pF	74VHCT163 6 C _L =50 pF 4.9 C _L =15 pF	8.5 C _L =50 pF 7.7 C _L =15 pF	20 C _L =50 pF	20 C _L =50 pF	18 C _L =50 pF	sn	sn	sn	sn	
Propagation Delay, t_{PHL}/t_{PHL}	Counter	Max C _L =15 pF	38 C _L =15 pF	27 C _L =15 pF	26 C _L =50 pF	650 at V _{DD} =5 V 250 at V _{DD} =10 V C _L =15 pF	360 at V _{DD} =5 V 160 at V _{DD} =10 V 130 at V _{DD} =15 V C _L =50 pF	9.5 C _L =50 pF	12 C _L =50 pF	10.5 C _L =50 pF 8.5 C _L =15 pF	14.5 C _L =50 pF 13.5 C _L =15 pF	28 C _L =50 pF	28 C _L =50 pF	23 C _L =50 pF	ns	ns	ns	
Propagation Delay, t_{PHL}/t_{PHL}		7474 Type C _L =15 pF	74LS74 C _L =15 pF	74ALS74 C _L =50 pF	4013A 13 C _L =50 pF	4013B 75 at V _{DD} =5 V 75 at V _{DD} =10 V C _L =15 pF	74AC74 150 at V _{DD} =5 V 65 at V _{DD} =10 V 45 at V _{DD} =15 V C _L =50 pF	6 C _L =50 pF	6 C _L =50 pF	6.1 C _L =50 pF 4.6 C _L =15 pF	6.3 C _L =50 pF 5.8 C _L =15 pF	20 C _L =50 pF	24 C _L =50 pF	25 C _L =50 pF	ns	ns	ns	
Propagation Delay, t_{PHL}/t_{PHL}	Flip-Flop, D-Type	Max C _L =15 pF	25 C _L =15 pF	13 C _L =50 pF	150 at V _{DD} =5 V 75 at V _{DD} =10 V C _L =15 pF	300 at V _{DD} =5 V 130 at V _{DD} =10 V 90 at V _{DD} =15 V C _L =50 pF	10 C _L =50 pF	11.5 C _L =50 pF 8.5 C _L =15 pF	10.5 C _L =50 pF 9.0 C _L =15 pF	10.0 C _L =50 pF 9.0 C _L =15 pF	30 C _L =50 pF	36 C _L =50 pF	35 C _L =50 pF	ns	ns	ns		



INTEGRATED CIRCUITS

Clock IC, Electronic Thermometer IC

• CMOS IC for LCD Wrist-Watches and Clocks

Part (Pin to Pin Compatibility)	Display			Functions				Multi- plexing Ratio	Supply Current without Load max, μ A	V_{DD} , V	Notes
	Digits	Flags	Marks	Hour Minute Second Month Date	Alarm	Chrono- graph	12H/ 24H				
Digital watch											
IZ6099F/ L/C/E (KS5199)	3.5		1	+			12	1/2	1.5	1.5	
IZ6099K	3.5		1	+			12/24		1.5	1.5	
IZ6199	3.5		1	+			12	1/2	1.5	3.0	IZ6099+EL
IZ6018	12	-	8	+	+	+	12/24	1/3	2.0	3.0	$^{\circ}\text{C}$: -20÷+60 $^{\circ}\text{F}$: -4÷+140
Analog clock											
IZ33173								2.0	1.5	Clock IC	
IZ33567								1.5	1.5	Clock with alarm, snooze, crescendo	

• Electronic Thermometer IC

Part	Pin to Pin Compatibility	Function	Features	Pads
IZ8016		100° Digital thermometer $^{\circ}\text{C}/^{\circ}\text{F}$	<ul style="list-style-type: none"> □ Measurement temperature range: from -50°C to +50°C (from -58°F to +122°F) □ Resolution: 0.2°C (°F) □ Accuracy: $\pm 1^{\circ}\text{C}$ (°F) □ Supply voltage 1.5V □ Measurement cycle 1, 3, 5 & 10 seconds (on default– 10 seconds) □ Measuring RC-oscillator with external resistor & capacitor □ 32 kHz clock RC-oscillator with build-in capacity □ Serial interface □ Build-in circuit of non-linear digital correction □ 3.5 digit LCD with double multiplex 	36
IZ8005	HT7501	Medical thermometer	<ul style="list-style-type: none"> □ Supply voltage 1.5V □ Measurement temperature range: from +32.00°C to +43.00°C □ Accuracy: $\pm 0.1^{\circ}\text{C}$ □ Resolution: 0.01°C □ Selftesting □ Alarm signal □ Storage of measurements results (highest temperature) □ Automatic switch-off after 8 min 40 sec □ One button on/off switching 	37
IZ8071		Digital medical thermometer	<ul style="list-style-type: none"> □ Measurement temperature range: from 32 to 42°C (from 89.6 to 107.6°F) □ Measurement accuracy: $\pm 0.05^{\circ}\text{C}$ – for range from 35 to 38°C, $\pm 0.1^{\circ}\text{C}$ – for ranges from 32 to 35°C & from 38°C to 42°C □ Resolution: 0.0025°C □ RC-oscillator with own frequency 32.32kHz (external resistance) with adjustment function □ Build-in LCD driver circuit 3COM x 11SEG, 1/3 duty, 1/2 bias 	42
IN18B20D IN18B20	DS18B20	Integrated circuit of digital sensor- measurer of temperature for industrial temperature range	<ul style="list-style-type: none"> □ Measurement temperature range: from -55°C to +125°C □ Temperature value is converted to 12-bit digital code □ Accuracy of temperature indication can be programmed by customer form 9 to 12 bit □ Alarm signal for case of temperature excess of threshold values determined (programmed) by customer □ Unique 64-bit serial number for each IC, not available for changes by customer □ Data read/write operation from memory of IC, 1-wire interface of data transfer 	SO-8 TO-92

INTEGRATED CIRCUITS

Melody IC

• Melody IC

Part	Maximum Number of Tunes (Notes)	Vcc, V	Supply Current, μ A		Package
			Operating	Stand-by	
BT8028-XX	16 (64)	1.3 – 3.3	< 60	< 1.0	TO-92
BT8031-XX	2 (127)	2.0 – 5.0	<1000	< 5	TO-92

XX – Melody code

• Voltage Control Oscillator (VCO) IC

Part	Pin to Pin Compatibility	Function	Features	Pads
IZC6990**	LTC6990	Voltage Controlled Silicon Oscillator	<ul style="list-style-type: none"><input type="checkbox"/> Supply voltage 2.25V – 5.5 V<input type="checkbox"/> Frequency Range: 488Hz to 2MHz<input type="checkbox"/> 72μA Supply Current at 100kHz<input type="checkbox"/> Fixed-Frequency or Voltage-Controlled Operation<ul style="list-style-type: none">- Fixed: Single Resistor Programs Frequency with < 1.5% Max error- VCO: Two Resistors Set VCO Center Frequency and Tuning Range<input type="checkbox"/> CMOS Logic Output Sources/Sinks 20mA	6

**Under Development



DISCRETE SEMICONDUCTORS

• Power N-Channel MOSFETs

Part	Function	Package
IFP50N06	N-Channel MOSFET 60 V; 0.023 Ω– 50 A	TO-220/3
IFP70N06	N-Channel MOSFET 60 V; 0.015 Ω– 70 A	Chip
IFP85N06	N-Channel MOSFET 60 V; 0.012 Ω– 85 A	Chip
IFP75N75	N-Channel MOSFET 75 V; 0.017 Ω– 75 A	Chip
IFP75N08	N-Channel MOSFET 80 V; 0.015 Ω– 75 A	TO-220/3
IFP630	N-Channel MOSFET 200 V; 0.400 Ω– 9 A	Chip
IFF630	N-Channel MOSFET 200 V; 0.180 Ω– 18 A	Chip
IFP640	N-Channel MOSFET 250 V; 0.450 Ω– 8 A	Chip
IFF640	N-Channel MOSFET 250 V; 0.950 Ω– 6 A	Chip
IFP634	N-Channel MOSFET 250 V; 0.550 Ω– 10 A	Chip
IFF634	N-Channel MOSFET 400 V; 1.400 Ω– 5 A	TO-220/3
IFP730	N-Channel MOSFET 400 V; 0.550 Ω– 10 A	TO-220FP
IFF730	N-Channel MOSFET 400 V; 0.260 Ω– 20 A	TO-220/3
IFP830	N-Channel MOSFET 500 V; 0.850 Ω– 8 A	TO-220FP
IFF830	N-Channel MOSFET 500 V; 0.490 Ω– 13 A	TO-220/3
IFP840	N-Channel MOSFET 500 V; 0.260 Ω– 20 A	TO-220FP
IFF840	N-Channel MOSFET 500 V; 0.120 Ω– 50 A	TO-220/3
IFP13N50	N-Channel MOSFET 500 V; 0.120 Ω– 50 A	Chip
IFW20N50	N-Channel MOSFET 600 V; 12.000 Ω– 0,9 A	Chip
IFL50N50	N-Channel MOSFET 600 V; 5.0 Ω– 1,8 A	Chip
IFP1N60	N-Channel MOSFET 600 V; 5.0 Ω– 2 A	TO-220/3
IFU1N60	N-Channel MOSFET 600 V; 2.5 Ω– 4.0 A	I-PAK
IFD1N60	N-Channel MOSFET 600 V; 1.2 Ω– 7 A	D-PAK
IFU2N60	N-Channel MOSFET 600 V; 0.8 Ω– 10 A	I-PAK
IFD2N60	N-Channel MOSFET 600 V; 0.32 Ω– 20 A	D-PAK
IFP2N60	N-Channel MOSFET 600 V; 0.26 Ω– 24 A	TO-220/3
IFF2N60	N-Channel MOSFET 600 V; 0.24 Ω– 28 A	TO-220FP
IFP4N60	N-Channel MOSFET 600 V; 0.7 Ω– 12 A	TO-220/3
IFF4N60	N-Channel MOSFET 600 V; 0.16 Ω– 40 A	TO-220FP
IFP7N60	N-Channel MOSFET 600 V; 0.85 Ω– 10 A	TO-220/3
IFF7N60	N-Channel MOSFET 600 V; 0.85 Ω– 10 A	TO-220FP
IFP10N60	N-Channel MOSFET 650 V; 13.0 Ω– 1 A	Chip
IFF10N60	N-Channel MOSFET 650 V; 5.5 Ω– 2 A	Chip
IFP12N60	N-Channel MOSFET 650 V; 2.7 Ω– 4 A	Chip
IFF12N60	N-Channel MOSFET 650 V; 1.3 Ω– 7 A	Chip
IFW20N60	N-Channel MOSFET 650 V; 0.85 Ω– 12 A	Chip
IFW24N60	N-Channel MOSFET 650 V; 0.26 Ω– 24 A	Chip
IFW28N60	N-Channel MOSFET 650 V; 0.24 Ω– 28 A	Chip
IFL40N60	N-Channel MOSFET 650 V; 0.16 Ω– 40 A	Chip
IFU1N65	N-Channel MOSFET 650 V; 0.16 Ω– 40 A	Chip
IFD1N65	N-Channel MOSFET 650 V; 0.16 Ω– 40 A	Chip
IFU2N65	N-Channel MOSFET 650 V; 0.16 Ω– 40 A	Chip
IFD2N65	N-Channel MOSFET 650 V; 0.16 Ω– 40 A	Chip
IFP2N65	N-Channel MOSFET 650 V; 0.16 Ω– 40 A	Chip
IFF2N65	N-Channel MOSFET 650 V; 0.16 Ω– 40 A	Chip
IFP4N65	N-Channel MOSFET 650 V; 0.16 Ω– 40 A	Chip
IFF4N65	N-Channel MOSFET 650 V; 0.16 Ω– 40 A	Chip
IFP7N65	N-Channel MOSFET 650 V; 0.16 Ω– 40 A	Chip
IFF7N65	N-Channel MOSFET 650 V; 0.16 Ω– 40 A	Chip
IFP10N65	N-Channel MOSFET 650 V; 0.16 Ω– 40 A	Chip
IFF10N65	N-Channel MOSFET 650 V; 0.16 Ω– 40 A	Chip
IFF12N65	N-Channel MOSFET 650 V; 0.16 Ω– 40 A	Chip
IFF12N65	N-Channel MOSFET 650 V; 0.16 Ω– 40 A	Chip

DISCRETE SEMICONDUCTORS

Transistors, Diodes, Diode Arrays

• Bipolar Transistors

Part	Pin to Pin Compatibility	Polarity	P _c max, W	V _{CB} max, V	V _{CE} max, V	V _{EB} max, V	I _c max, mA	h _{FE}	V _{CE sat} , V	I _{cBO} , μA	F _T , MHz	Package
KT520A	MPSA42	NPN	0.625	300 200	300 200	6	500	>40	0.5 0.4	100	50	TO-92
KT520Б	MPSA43											
KT521A	MPSA92	PNP	0.625	300 200	300 200	5	500	>40	0.5 0.4	100	50	TO-92
KT521Б	MPSA93											
KT814A					40			40...275				
KT814Б	BD136	PNP	10		50		5	40...275				
KT814В	BD138				70			40...275				
KT814Г	BD140				100			30...275				
KT8225A	BU941ZP	NPN	155	350	350	5	15000	>300	2.7	100		TO-218

• Unijunction Transistors

Part	Pin to Pin Compatibility	P max, W	V _b , b ₂ max, V	I _e pulse, A	I _e rev, μA	V _{eb sat} , V	η	Package
KT132A	2N2646	0.3	35	2.0	12.0 0.2	0.7...3.5	0.56...0.75 0.68...0.82	Case 22A-01
KT132Б	2N2647							
KT133A	2N4870	0.3	35	1.5	1.0	0.7...2.5	0.56...0.75 0.70...0.85	TO-92
KT133Б	2N4871							

• Power Thyristors and Triacs

Part	Pin to Pin Compatibility	Repetitive Peak Off-State Voltages V _{DRM} , V _{RRM} V	RMS On-State Current I _{T (RMS)} A	I ² t for Fusing I ² t, A ² c	Off-State Leakage Current I _D , I _R mA	Holding Current I _H mA	Latching Current I _L mA	Gate Trigger Current I _{GT} mA	Peak Gate Current I _{GM} A	Package
KY251A	MCR100-8	600	1.0	0.415	≤0.05	≤5	≤5	≤0.2	8,0	TO-92
KY251Б	KY251Б	800								
Triac										
KY613A	BTA208-600B	600	8.0	21	≤0.5	≤90	≤60	≤50	2.0	TO-220AB
KY613Б	BTA208-800B	800								

Foundry business

- Semiconductor IC and Discrete Devices Manufacturing under the Customer's Design (delivery on base of Probe Test)
- Semiconductor IC and Discrete Devices Manufacturing under the Customer's Design (delivery on the base of PCM)
- Wafer Fab Service – execution of separate Process Flow Steps or blocks (Metal sputtering, film deposition, EPI growing, back grinding, wafers testing and so on)
- Raw Si substrate and EPI manufacturing under the Customer's Spec

Production Capacity available for Foundry Business:

- 8" wafer production line (0.5-0.35 µm design rule)
- 6" wafer production line (0.8-1.2 µm design rule)
- 4" wafer production line (1.2-3.0 µm design rule)

Basic Process available:

a) Integrated Circuits:

- DMO_S
- CMOS
- BiCMOS
- CDMOS
- BiCDMOS
- Bipolar

b) Discrete devices:

- D-MOS (≤ 1000 V)
- Multi-Epi (≤ 700 V)
- Bipolar
- Process for high frequency devices (≤ 300 V)

Si substrates and EPI, manufacturing and delivery (according to the Customer's Spec):

- 3", 4", 6", 8" wafers
- EPI parameter range: $d=0.5\ldots 80$ µm, $p=0.1\ldots 50 \Omega \cdot \text{cm}$

Mask making:

- Mask Set manufacturing under the Customer's Spec (GDS II and DB):
 - a) for contact lithography
 - b) for Projection Reduction (Stepper lithography) (1:1/1:5/1:10)
- Pellicles manufacturing under the Customer's Spec
- Manufacture of photomasks with P/R coatings (glass and quartz substrates)

Contract management

Packaging:

- IC and Discrete Devices assembly (packaging) with Testing
- IC and Discrete Devices assembly (packaging) without Testing
- IC and Discrete Devices assembly (packaging) with Testing and Marking

Packages Types available:

a) Integrated Circuits:

- SOP (8-28 LD)
- DIP (8-40 LD)
- SHRINK DIP (30, 42, 52, 56 LD)
- QFP (48, 64, 100 LD)
- SIL (3, 8, 13, 17 LD)
- SIP (9LD)
- TO -220 (3, 5, 7 LD)
- SOT -23, SOT -143, SOT -223

b) Discrete devices:

- Case 22A-01
- DO-34, DO-35
- MELF, miniMELF
- SOT -23, SOT -143, SOT -223
- ISOWATT
- TO-18, TO-39, TO-72, TO-92, TO-126,
- TO-218, TO-220
- KD-17
- DPAK, D2PAK

Fabless service

IC and discrete devices design:

- IC Design according to the Customer's Data Sheet (Spec) and Process Development
- Discrete Devices Design according to the Customer's Data Sheet (Spec) and Process development
- GDS II and Tape out
- Engineering Consulting service
- Reengineering

Supplementary services

Design of electronic devices/ instruments and manufacture of samples as per Customer's requirements:

- Design and manufacture of PCB
- Design and manufacture of LCD:
 - TN-type ("twist") for electronic clock/watch, calculators, etc,
 - STN-type ("supertwist") for general purposes

Other services:

- Design and manufacture of quartz tooling and accessories, tools
- Design and manufacture of molds, punches, casting/transfer molds
- Marking blocks manufacturing
- High-precision stamping of lead frames for IC manufacturing

CONTACTS

HEADQUARTERS

INTEGRAL JOINT STOCK COMPANY

121A, Kazintsa I.P. Str., Minsk,
220108, Republic of Belarus
Tel.: (375 17) 353 2257
..... (375 17) 272 3729
Fax: (375 17) 353 2257
E-mail: export@integral.by
<http://www.integral.by/>

MARKETING AND SALES DEPARTMENT

Tel.: (375 17) 353 2257
..... (375 17) 272 3729
Fax: (375 17) 353 2257
E-mail: export@integral.by