

SEMICONDUCTOR PRODUCTS

SHORT FORM CATALOG



2026

JSC “INTEGRAL” reserves the right to make changes in device design, specifications and other information identified in this publication without notice and assumes no responsibility for the use of any device described herein.

JSC “INTEGRAL” advises its customers to obtain the latest version of relevant information to verify before placing orders, that the information being relied upon is current.

Reference to products of other manufacturers are solely for convenience and do not imply total equivalency of design, performance, or otherwise.

CONTENTS

Introduction	4
Integrated Circuits	5
Drivers, Peripherals, Real Time Clock ICs	6
Display Driver ICs	6
LED Driver Circuits	6
Interface Integrated Circuits (Reference Date)	7
Real Time Clock.....	7
Audio ICs	8
ICs for Audio Systems.....	8
Telecommunications ICs	9
Switches and DTMF Receivers	9
Pulse and Tone/Pulse Dialers	9
Single Chip Telephone IC	10
Speaker Integrated Circuits.....	10
Tone Telephone Ringers.....	11
IC for Smart Cards	12
IC for Systems of Identification.....	12
Power Electronics, Standard Analog ICs	13
ICS for Control and Power Electronics	13
Automotive ICs.....	14
Timers.....	15
Comparators	15
μ p Supervisory Circuits	15
Operational Amplifiers.....	16
Voltage Regulators	17
Switching Regulators (Reference Data).....	18
Precision Low Voltage Reference	19
PWM Controllers	19
Voltage Detectors	19
Power Supply ICs	19
Standard Digital Logic IC	20
IN74AC/ACTXXX series	20
I IN74HC/HCTXXXXAN series	21
IN74LVXXXN series	23
IN74XXXN series	23
N74LSXXXN series	24
IN74ALSXXXXN series	24
IW4000BN series	26
Family Characteristics.....	28
Clock/Watch IC/Electronic Thermometer IC	31
CMOS ICs for LCD Wrist-Watches and Clocks	31
Electronic Thermometer IC	31
Melody IC	32
Discrete Semiconductors	33
Transistors	34
Power N-Channel MOSFETs	34
Unijunction Transistors.....	34
Foundry-business	35

INTRODUCTION

JSC «INTEGRAL» develops, manufactures and exports microelectronic components and electronic products. «INTEGRAL» company provides a full cycle of design and manufacture: from silicon substrates up to integrated circuits and semiconductor devices, from microelectronic components up to electronic devices.

Total number of employees is more than 5 thousand persons.

The main line of activity of JSC «INTEGRAL» is design and manufacture of microelectronic components (integrated circuit, transistors, diodes) – about 90 % of the total production volume. JSC «INTEGRAL» exports more than 95 % of the volume of manufactured goods.

«INTEGRAL» company is open for long term cooperation with customers both in design, production and deliveries of products.

• BASIC TYPES OF INTEGRATED CIRCUITS MANUFACTURED:

- Microcontrollers, drivers, peripheral ICs,
- TV and audio ICs,
- Telecommunications ICs,
- Power electronics, standard analog ICs,
- Standard digital logic ICs,
- Special-purpose electronic component base,
- Clock/watch, calculator ICs,
- Melody synthesizer and electronic thermometer ICs,
- etc.

• BASIC TYPES OF SEMICONDUCTOR DEVICES MANUFACTURED:

- Power bipolar Darlington transistors,
- Insulated gate bipolar transistors,
- Bipolar transistors with damping diode and resistor in the emitter-base circuit,
- Unijunction bipolar transistors,
- Low-power n- and p-channel MOSFETs,
- Power n- and p-channel MOSFETs,
- Microwave mixing diodes, rectifier diodes, Schottky diodes,
- Power high-speed diodes and diode matrices,
- Pulse diode matrices,
- Power rectifier and limiter diodes.

CONTACTS

*JSC "INTEGRAL" - "INTEGRAL" Holding Managing Company
121A Kazintsa I.P. Str., office 327, Minsk,
220108, Republic of Belarus
integral.by*

*MARKETING AND SALES DEPARTMENT
+375 (17) 3710005
export@integral.by*

INTEGRATED CIRCUITS

INTEGRATED CIRCUITS

Drivers, Peripherals, Real Time Clock ICs

• Display Driver ICs

Part	Pin to Pin Compatibility	Supply Voltage, Ucc,V	LCD Voltage, V	Duty	RAM	Column Lines	Common Lines	Frequency, kHz	Pins (Pads)	Notes
LCD Controllers and Drivers										
IZ6570AA	NJU6570AA SED1520DAA	2.4...5.5	2.4...13	1/16 1/32	80x32	61	16	2	(100)	Chip
IZ6570OA	NJU6570OA SED1520DOA	2.4...5.5	2.4...13	1/16 1/32	80x32	61	16	18	(100)	Chip
IZ6450	NJU6450A	2.4...5.5	3.5...10	1/16 1/32	80x32	61	16	18	(100)	Chip
IZ6451	NJU6451A	2.4...5.5	3.5...10	1/16 1/32	80x32	72	8	18	(100)	Chip
IZ7065	KS0065	2.7...5.5	3...13	1/8 1/16		40		max400	(59)	Chip
IZ7066	KS0066	4.5...5.5	3...13	1/8 1/11 1/16	80x8	40	16	350	(80)	Chip
IZ602	FL602 HT1621	2.4...5.5	2.4...Ucc	1/2 1/3 1/4	32x4	32	4	256	(48)	Chip

• LED Driver Circuits

Part	Pin to Pin Compatibility	Function	Package
IL9910N IL9910D IL9910DH IZ9910	HV9910	Universal High Brightness LED Driver, 1A	DIP-8 SO-8 SO-16 Chip
IZ9921	HV9921	20mA/50mA/30mA Switch-Mode LED Driver IC	Chip
IZ9922	HV9922		
IZ9922A	-		
IZ9923	HV9923		
IZ7150 IZ7150A	AMC7150	Power LED Driver, 1,5 A Power LED Driver, 0,8 A	Chip
IL3361AD IL3361BD IZ3361	HV9961	High-stable LED-driver IC; 8 V÷450 V supply voltage	SO-8 SO-16 Chip
IL3367D IZ3367	HV9967	High-voltage LED-driver IC with built-in MOSFET key, 8 V÷60 V input voltage	SO-8 Chip
IZ33120		120mA LED Driver IC with built-in MOSFET, 8 V÷450 V input voltage	Chip
IZ3302		Universal High Brightness LED Driver, 1A	Chip
IZR402U IZR402R	BCR402	Constant current LED-driver; 42 V supply voltage; 18.6 V output voltage; LED-driver current: 22 mA up to 65 mA with external resistor Constant current LED-driver; 60 V supply voltage; 38.6 V output voltage; LED-driver current: 22 mA up to 65 mA with external resistor	Chip Chip

• **Interface Integrated Circuits** (Reference Date)

Parameter	IL75232N IL75232DW	ILX202N ILX202D	ILX207N ILX207DW	ILX208N ILX208D	ILX232N ILX232D	ILX485N ILX485D	ILX3221N	ILX3226N	ILX3232N ILX3232D	ILX3483N	ILX3485N	ILX3486N
ESD Voltage (kV)	0.5	2	2	2	2	4	4	4	4	4	4	4
Power Supply Voltage (V)	±9...±15 for TX 5 for RX	4.5...5.5	4.75...5.25	4.5...5.5	4.5...5.5	4.75...5.25	3...5.5	3...5.5	3...5.5	3...3.6	3...3.6	3...3.6
No. of TX/RX	3/5	2/2	5/3	4/4	2/2	1/1	1/1	1/1	2/2	1/1	1/1	1/1
No. of TX/RX on Bus						32						
Supply Current (mA)	30	10	20	20	10	0.9	0.001	0.001	1	0.001	0.001	0.001
Standard	RS-232	•	•	•	•	•	•	•	•	•	•	•
	RS-485/RS-422											
Auto Shutdown Plus, Auto Shutdown							•	•				
Date Rate (bps)		64K	120K	120K	120K	2.5M	250K	250K	120K	250K	12M	2.5M
External Caps (µF)		4x0.1	4x0.1	4x0.1	4x1.0		4x0.1	4x0.1	4x0.1	-	-	-
Operating Temperature Range (°C)	0 ÷ +75	-40 ÷ +85										

• **Real Time Clock**

Part	Pin to Pin Compatibility	Function	Package
Digital timers			
IN1307N IN1307D	DS1307N/ZN	64 x 8 Serial Real Time Clock	DIP-8 SO-8
IN1356D	M41T56	512bit (64bit x 8) Serial Access Timekeeper SRAM	SO-8
IN1363D	PCF8563	Real Time Clock / Calendar	SO-8

• **ICs for Audio Systems**

Part	Pin to Pin Compatibility	Function	Features	Package
IL34119N IL34119D	MC34119	0.25 W Low Power Mono Audio Amplifier	<ul style="list-style-type: none"> □ Vcc=2...16 V □ Low Quiescent Supply Current for Battery Powered Applications □ Chip Disable Input to Power Down the IC □ Drives a Wide Range of Speaker Loads (8-100 Ω) □ Output Power Exceed 250 mW with 32 Ω Speaker □ Gain Adjustable from 0 dB to 46 dB for Voice Band □ Requires Few External Components 	DIP-8 SO-8
IL386N IL386D	LM386	1 W Low Power Mono Audio Amplifier	<ul style="list-style-type: none"> □ Vcc=4...12 V □ Battery Operation □ Low Quiescent Current Drain: 4 mA □ Voltage Gains from 20 to 200 dB □ Ground Referenced Input □ Self-Centering Output Quiescent Voltage □ Low Distortion 	DIP-8 SO-8
ILA7056B	TDA7056B	5 W Mono BTL Audio Amplifier with DC Volume Control	<ul style="list-style-type: none"> □ Vcc=4.5...18 V □ DC volume control □ Few external components □ Mute mode □ Thermal protection □ Short-circuit proof □ No switch-on and of clicks □ Low HF radiation □ Low power consumption 	SIL-9MPF

• **Switches and DTMF Receivers**

Part	Pin to Pin Compatibility	Function	Features	Package
IL9170N IL9170DW	HM9170	DTMF Receiver	<ul style="list-style-type: none"> □ Vcc =2.5...5.5 V □ Icc max=9.0 mA □ Power consumption 15 mW □ Quartz generator 3.58 MHz □ Decoding of 16 DTMF tones-pairs □ 4-bit parallel output □ PWDN 	DIP-18 SO-18
IL567N IL567D	LM567	Tone Decoder	<ul style="list-style-type: none"> □ 20 to 1 frequency range with an external resistor □ Logic compatible output with 100 mA current sinking capability □ Bandwidth adjustable from 0 to 14% □ High rejection of out of band signals and noise □ Immunity to false signals □ Highly stable center frequency □ Center frequency adjustable from 0.01 Hz to 500 kHz 	DIP-8 SO-8
IL9200N IL9200D	HM9200	DTMF generators	<ul style="list-style-type: none"> □ Vcc =2.5...5.5 V □ Low standby current □ Low total distortion 3.58 MHz crystal or ceramic resonator 	DIP-8 SO-8

• **Pulse and Tone/Pulse Dialers**

Part	Pin to Pin Compatibility	Function	Features	Package
IL91531N	UM91531	Parallel Input Tone/Pulse Dialer	<ul style="list-style-type: none"> □ Vcc=2.5...5.5 V □ Quartz generator 3.58 MHz □ Output signal: pulse 10 Hz or DTMF □ 4-bit parallel data input from microcomputer □ Selectable Make/Break ratio □ Inter digital pause 800 ms 	DIP-16
IL91214AN IL91214AD	UMS91214A	Tone/Pulse Dialer with Handsfree Control and Flash Function	<ul style="list-style-type: none"> □ Vcc=2.0...5.5 V □ Quartz generator 3.58 MHz □ 32-digit redial memory □ Tone/Pulse switchable □ Output signal: pulse 10 Hz(20Hz) or DTMF □ Flash Function □ 4x4 keyboard □ 09 - mode output pin (IL91214BN/BDW) □ 10 – key in tone output (IL91214BN/BDW) 	DIP-16 SO-16

INTEGRATED CIRCUITS

Telecommunications ICs

• Single Chip Telephone IC

Part	Pin to Pin Compatibility	Function	Features	Package
IL2533N IL2533DW	AS2533	Multi-Standard CMOS Single Chip Telephone IC with Dual Soft Clipping	<ul style="list-style-type: none"> □ Line/speech circuit, LD/MF repertory dialer and tone ringer on one 28 pin CMOS chip □ Operating range from 13 to 100 mA (down to 5mA with reduced performance) □ Soft clipping to avoid harsh distortion □ Volume control of receive signal □ Line loss compensation selectable by pin option □ Low noise (max. - 72 dBmp) □ Real or complex impedance □ NET 4 compatible. □ LD/MF switchable dialing □ Pacifier tone during programming □ 31 digits last number redial □ Sliding cursor protocol with comparison □ Pause key for access pause or wait function □ 3 flash keys, 100 ms, 280 ms and 375/600 ms □ On chip MF filter (CEPT CS 203 compatible) □ Ring frequency discrimination □ 3-tone melody generator □ Oscillator Frequency (Resonator: Murata CSA 3.58MG312AM)-3.58 MHz □ 4x4...4x8 Keyboard 	DIP-28 SO-28

• Speaker ICs

Part	Pin to Pin Compatibility	Function	Features	Package
IL34118N IL34118DW	MC34118	Voice Switched Speakerphone Circuit	<ul style="list-style-type: none"> □ $V_{cc} = 3.0 \dots 6.5$ V □ $I_{cc} = 5.0$ mA □ Improved Attenuator Gain Range: 52 dB Between Transmit and Receive □ Low Voltage Operation for Line-Powered Applications (3.0-6.5 V) □ 4-Point Signal Sensing for Improved Sensitivity □ Background Noise Monitors for Both Transmit and Receive Paths □ Microphone Amplifier Gain Set by External Resistors – Mute Function Included □ Chip Disable for Active/Standby Operation □ On Board Filter Pinned-Out for User Defined Function □ Dial Tone Detector to Inhibit Receive Idle Mode During Dial Tone Presence □ Standard 28-Pin Plastic Dip Package and SOIC Package Available □ Compatible with IL34119 Speaker Amplifier 	DIP-28 SO-28
IL34119N IL34119D	MC34119	Telephone Audio Amplifier	<ul style="list-style-type: none"> □ $V_{cc} = 2.0 \dots 16.0$ V □ $I_{cc} = 2.7$ mA □ Drives a wide range of speaker loads (8...100 Ω) □ Output power exceeds 250 mW with 32 Ω Speaker □ Low total harmonic distortion □ Gain adjustable 0...46 dB for voice band □ Requires few external components 	DIP-8 SO-8

• **Speaker ICs** (continued)

Part	Pin to Pin Compatibility	Function	Features	Package
IL3726/18N IL3726/18DW	PBL3726/18	Speaker Integrated Circuit	<ul style="list-style-type: none"> □ $V_{LN}=3.3...4.1$ V ($I_L=15$ mA) □ $V_{LN}=11.0... 15.0$ V ($I_L=100$mA) □ 7 Capacitors & Resistors □ Low Voltage Operating □ DTMF signal input with confidence tone □ Mute input for DTMF dialing □ Line loss compensation (line current dependent) for microphone and earpiece amplifiers □ Gain control curve adaptable to exchange supply □ DC line voltage adjustment facility 	DIP-18 SO-20
ILA1062AN ILA1062AD ILA1062N ILA1062D	TEA1062A TEA1062	Low Voltage Transmission Circuit with Dialer Interface	<ul style="list-style-type: none"> □ Low DC line voltage; operates down to 1.6 V □ Line operation current range 10...140 mA □ $I_{cc} \leq 1.35$ mA □ Voltage gain range: <ul style="list-style-type: none"> microphone amplifier 11...52 dB telephone amplifier 20...31 dB □ Voltage regulator with adjustable static resistance □ Provides supply for external circuits □ Symmetrical high-impedance inputs <ul style="list-style-type: none"> (64 kΩ) for dynamic, magnetic or piezoelectric microphones □ Asymmetrical high-impedance inputs <ul style="list-style-type: none"> (32 kΩ) for electret microphones □ DTMF signal input with confidence tone □ Mute input for pulse or DTMF dialing □ Receiving amplifier for dynamic, magnetic or piezoelectric earpieces □ Large gain setting range on microphone and earpiece amplifiers 	DIP-16 SO-16 DIP-16 SO-16

• **Tone Telephone Ringers**

Part	Pin to Pin Compatibility	Function	Features	Package
IL2418N IL2418D	KA2418	Two-Tone Telephone Ringer with Diode Bridge	<ul style="list-style-type: none"> □ $V_{cc}=26$ V □ I_{cc} max=1.8 mA □ Activation voltage 12.2...13 V □ Sustaining voltage 8.0...8.8 V □ Internal Zener diodes to protect against over voltages □ High noise immunity due to built-in voltage-current hysteresis □ Ringer impedance adjustable with external components □ Output $F_1=2100...2550$ Hz $F_2=1500...1850$ Hz 	DIP-8 SO-8

INTEGRATED CIRCUITS

Telecommunications ICs

• IC for Smart Cards

Part	Pin to Pin Compatibility	Function	Features	Pads
IZ2815A-03	SLE4436E	IC for Prepaid Cards	<ul style="list-style-type: none"> □ Vcc=4.5...5.5 V □ Icc=5 mA □ 221-bit EEPROM and 16 bit mask-programmable ROM □ 104 bit user memory fully compatible with IZ4406: <ul style="list-style-type: none"> - 64 bit identification area - 40 bit counter area including 1 bit for personalization □ 133 bit additional memory for advanced features <ul style="list-style-type: none"> - 4 bit counter backup (anti-tearing flags) - 1 bit initiation flag for authentication key 2 - 16 bit data area 1 for free user access - 48 bit authentication key 1 - either 64 bit data area 1 for user defined data or 48 bit authentication key 2 □ EEPROM programming time 5 ms □ Endurance minimum of 100000 write/erase cycles per bit □ Data retention for minimum of 10 years □ Contact configuration and serial interface in accordance to ISO standard 7816-3 	5

• ICs for identification systems

Part	Pin to pin compatibility	Function	Features	Pads
IZ2803-5		Read / write transponder IC	<ul style="list-style-type: none"> □ For non-contact plastic card □ Operating frequency range: 100 ... 150 kHz □ ROM information capacity: 64 bit □ External inductor AC voltage value: 3min and 15 max □ Data retention with the power off: 5 years min 	4
IZ1990	DS1990A	1-Wire interface electronic key IC	<ul style="list-style-type: none"> □ Power supply: 2.8 – 6.0 V □ Unique 64 bite code 	2
IZ1991	DS1991	1-Wire interface and increased security level electronic key IC	<ul style="list-style-type: none"> □ Power supply: 2.8 – 6.0 V □ Unique 64 bite code □ 3 memory blocks, 384 bit each □ Scratch-pad memory: 512 bit 	2

• **ICs for Control and Power Electronics**

Part	Pin to Pin Compatibility	Function	Package
IL33035N IL33035DW	MC33035	Brushless DC Motor Controller	DIP-24 SO-24
IL33153PN	MC33153P	Single IGBT Gate Driver	DIP-8
IL33262N IL33262D	MC33262	Power Factor Controller ($T_A = -40 \dots +105^\circ\text{C}$)	DIP-8 SO-8
IL34262N IL34262D	MC34262	Power Factor Controller	DIP-8 SO-8
IL6562D	L6562		SO-8
IL6562N	L6562	Power Factor Controller	DIP-8
IL7101N/AN/BN IL7101D/AD/BD	GL7101	Earth Leakage Current Detector ($U_T = 4 \dots 9 \text{ mV}$ for AN) ($U_T = 9 \dots 18 \text{ mV}$ for N/D)	DIP-8 DIP-8 SO-8
IL4145AN	RV4145A	Low Power Ground Fault Interrupter	DIP-8
ILN2003BN	ULN2003B	High-Voltage High-Current Darlington Transistor Arrays	DIP-16 SO-16
ILN2004BN ILN2004BD	ULN2004B	High-Voltage High-Current Darlington Transistor Arrays	DIP-16 SO-16
ILN62083N ILN62083D	TD62083AFN	8CH Darlington Sink Driver	DIP-18 SO-18
ILN62084N ILN62084D	TD62084AFN		DIP-18 SO-18
ILN62783N ILN62783D	TD62783AFN		DIP-18 SO-18
ILN62784N ILN62784D	TD62784AFN		DIP-18 SO-18

• **High-Voltage Drivers ICs** (Reference Data)

Part	Topr (°C)	I _{OUT} (max) (mA)	V _{CE} (max) (V)	I _{IN} (max) (mA)	V _{IN} (max) (V)	V _F / V _R (max) (V/V)	Designation	Package
7CH High-Voltage Drivers								
ILN2003BN	- 20 ÷ +85	500	50	1.35	30	2/50	TTL, 5V CMOS	DIP-16 SO-16
ILN2004BN ILN2004BD	- 20 ÷ +85	500	50	1.35	30	2/50	6 ~ 15V PMOS, CMOS	DIP-16 SO-16
8CH High-Voltage Drivers								
ILN62083N ILN62083D	- 40 ÷ +85	500	50	1.35	30	2/50	TTL, 5V CMOS	DIP-18 SO-18
ILN62084N ILN62084D	- 40 ÷ +85	500	50	0.50	30	2/50	6 ~ 15V PMOS, CMOS	DIP-18 SO-18
ILN62783N ILN62783D	- 40 ÷ +85	-500	50	0.26	30	2/50	TTL, 5V CMOS	DIP-18 SO-18
ILN62784N ILN62784D	- 40 ÷ +85	-500	50	0.13	30	2/50	6 ~ 15V PMOS, CMOS	DIP-18 SO-18

INTEGRATED CIRCUITS

Power Electronics, Standard Analog IC

• Automotive ICs

Part	Pin to Pin Compatibility	Function	Package
IL33193N IL33193D	MC33193	Automotive Direction Indicator $R_S=20\text{ m}\Omega$, $F_n=2.2$, Duty Cycle (Normal Operation) 45÷55%, Duty Cycle (One 21 W Lamp Defect) 35÷45%, Defect Lamp Detector Threshold 42.5÷56 mV, $R_{SS}=220\ \Omega$	DIP-8 SO-8
IL33193N-03 IL33193D-03	UEA1041B	Automotive Direction Indicator $R_S=30\text{ m}\Omega$, $F_n=2.5$, Duty Cycle (Normal Operation) 45÷55%, Duty Cycle (One 21 W Lamp Defect) 35÷45%, Defect Lamp Detector Threshold 75÷95 mV, $R_{SS}=220\ \Omega$, Short Circuit Detector Threshold	DIP-8 SO-8
IL33197AN IL33197AD	MC33197A	Automotive Wash Wiper Timer Output Clamp Voltage ($I_{out}=20\text{ mA}$) 19.5÷22 V, Internally incorporated Zener diode 20 V	DIP-8 SO-8
IL6083N IL6083N-01	U6083B	Power Control With Interference Suppression (for N-01: Duty cycle 10... 100%, $V_{S1}=24.5...28.0\text{ V}$, $V_{S2}=18.5...22.0\text{ V}$, $V_{Batt1}=16.7...21.0\text{ V}$ (switched on), $V_{Batt1}=18.3...22.5\text{ V}$ (switched off), $V_{TS}=10.1...10.7\text{ V}$, $I_S=5...17\text{ mA}$)	DIP-8
IN9014N		For light control relay IC	DIP-8
IL8190N IL8190DW	CS8190ENF16 CS8190EDWF20	Precision Air-Core Tach/Speedo Driver with Return to Zero	DIP-16 SO-20
IL33290AD	MC33290	ISO K Line Serial Link Interface	SO-8
ILA82C251D	PCA82C251T	CAN transceiver for 24 V systems	SO-8
IN2515/AN/ADW/BN/BDW	MCP2515	CAN Controller	SO-18
IL33091AN IL33091AD	MC33091A	High-Side MOS Driver	DIP-8 SO-8
ILE4250GS	TLE4250G	Low-Drop Voltage Tracker (2÷36 V); 50 mA; Reverse Polarity Protection	P-TO-263-5-1 TO-220AB/5
ILE4260 ILE4260-2	TLE4260	Low-Drop Voltage Regulator 5 V; 500 mA; Reverse Polarity Protection	P-TO-220-5-12
ILE4264G IZE4264-2	TLE4264G TLE4264-2G	Low-Drop Voltage Regulator 5 V; 100 mA; Reverse Polarity Protection	P-SOT223-4-1 Chip
ILE4266G IZE4266-2	TLE4266G TLE4266-2G	Low-Drop Voltage Regulator 5 V; 100 mA; Reverse Polarity Protection	P-SOT223-4-2 Chip
ILE4267G ILE4267S	TLE4267G TLE4267S	Low-Drop Voltage Regulator 5 V; 400 mA; Reverse Polarity Protection	P-TO-220-7-180 P-TO-220-7-230
ILE4268GDW	TLE4268G	Low-Drop Voltage Regulator 5 V; 150 mA; Reverse Polarity Protection	P-DSO-20-6
ILE4270G ILE4270S ILE4270Q	TLE4270G TLE4270S	Low-Drop Voltage Regulator 5 V; 550 mA; Reverse Polarity Protection	P-TO-263-5-1 P-TO-220-5-12 P-TO-220-5-11
ILE4271G ILE4271S	TLE4271G TLE4271S	Low-Drop Voltage Regulator 5 V; 550 mA; Reverse Polarity Protection	P-TO-220-7-180 P-TO-220-7-230
ILE4274V50/V85/V10	TLE4274	Low-Drop Voltage Regulator 5 V/8.5 V/10 V; 400 mA; Reverse Polarity Protection	TO-220AB/3
ILE4275G/S	TLE4275G	Low-Drop Voltage regulator 5 V; 400 mA; Reverse Polarity Protection	P-TO-263-5-1 TO-220AB/5
ILE4276VG/VS/V50G/V50S/V85G/V85S/V10S	TLE4276	Low-Drop Voltage Regulator 5 V/8.5 V/10 V; 400 mA; Reverse Polarity Protection	P-TO-263-5-1 TO-220AB/5
IZE4278	TLE4278	Low-Drop Voltage Regulator 5 V; 150 mA; Reverse Polarity Protection	Chip
IZ4206	TLE4206G	1 A DC Motor Driver for Servo Driver Applications	Chip
IZE4263	TLE4263	LDO Regulator 5 V; 150 mA	Chip
IZE4279	TLE4279	LDO Regulator 5 V; 150 mA	Chip

• Timers

Part	Pin to Pin Compatibility	Function	Package
Digital timers			
IN555N IN555D	NE555	Timer	DIP-8 SO-8
ILC555N ILC555D	GLC555	Timer	DIP-8 SO-8
IN556N IN556D	NE556	Dual Timer	DIP-14 SO-14
ILC556N	GLC556	Dual Timer	DIP-14
IN558N	NE558	Quad Timer	DIP-16
ILC558N	GLC558	Quad Timer	DIP-16

• Comparators

Part	Pin to Pin Compatibility	Function	Package
IL311AN IL311AD IL311ANM	LM311, LM211	Highly Flexible Voltage Comparators ($T_A = -45...+85^{\circ}\text{C}$)	DIP-8 SO-8 DIP-14
IL339N IL339D	LM339	Quad Comparator	DIP-14 SO-14
IL293N IL293D	LM293	Dual Comparator ($T_A = -40...+85^{\circ}\text{C}$)	DIP-8 SO-8
IL393N IL393D	LM393	Dual Comparator	DIP-8 SO-8

• μP Supervisory Circuits

Part	Pin to Pin Compatibility	Function	Package
IN1232N IN1232D	DS1232	Micro Monitor	DIP-8 SO-8
IN1705N IN1705D IN1705RN IN1705RD	DS1705	Micro Monitor (RN, RD – Push-Pull Reset Output)	DIP-8 SO-8 DIP-8 SO-8
IN1706N IN1706D IN1706SRN IN1706SRD	DS1706S	Micro Monitor (SRN, SRD - Push-Pull Reset Output)	DIP-8 SO-8 DIP-8 SO-8
IN1708N IN1708D	DS1708	Micro Monitor	DIP-8 SO-8
IL809/810LW IL809/810MW IL809/810TW IL809/810SW IL809/810RW	STM809/810LW STM809/810MW STM809/810TW STM809/810SW STM809/810RW	Reset Circuit	SOT-23-3

INTEGRATED CIRCUITS

Power Electronics, Standard Analog IC

• Operational Amplifiers

Part	Pin to Pin Compatibility	Function	Package
IL258N IL258D	LM258	Dual Operational Amplifier ($T_A = -40 \div +85^\circ\text{C}$)	DIP-8 SO-8
IL358N IL358D	LM358	Dual Operational Amplifier	DIP-8 SO-8
IL224N IL224D	LM224	Quad Operational Amplifier ($T_A = -40 \div +85^\circ\text{C}$)	DIP-14 SO-14
IL324N IL324D	LM324	Quad Operational Amplifier	DIP-14 SO-14
IL1776CN, CAN IL1776CD, CAD	MC1776C	Micropower Programmable Operational Amplifier (CAN, CAD $T_A = -40 \div +85^\circ\text{C}$)	DIP-8 SO-8
IL4558N IL4558D	GL4558	Dual Operational Amplifier	DIP-8 SO-8
IZ4560	NJM4560	Dual Operational Amplifier ($T_A = -25 \div +75^\circ\text{C}$)	Chip
IZ4580	NJM4580	Dual Operational Amplifier ($T_A = -40 \div +85^\circ\text{C}$)	Chip
IL8541D	AD8541	Micropower CMOS operational amplifier	Chip SO-8
IL8515D	AD8515	Low power operational amplifier	Chip SO-8
IL8615D	AD8615	Rail to Rail wide bandwidth operational amplifier	Chip SO-8

INTEGRATED CIRCUITS

Power Electronics, Standard Analog IC

• Voltage Regulators

Part	Pin to Pin Compatibility	Output Voltage, V	Output Current, A	Output Voltage Tolerance, %	Tested Operating Junction Temp. Range, °C	Package
------	--------------------------	-------------------	-------------------	-----------------------------	---	---------

Positive Voltage Regulators

IL78XXAC IL78XXC IL78XXB	78XXAC 78XXC 78XXB	5; 6; 8; 9; 10; 12; 15; 18; 20; 24	1.0	2 4 4	T _j = -10...+125 T _j = -10...+125 T _j = -45...+125	TO-220
IL78FXX	78FXX	5; 6; 8; 9;10;12;15;18; 24	1.0	4	T _j = -10...+125	TO-126
IL78MXX	78MXX	5; 6; 8; 9; 12; 15; 18; 24	0,5	2 4	T _j = -10...+125	TO-126
IL78LXXAC IL78LXXC	78LXXAC 78LXXC	3.3; 5; 6; 8; 9; 12; 15; 18; 24	0.1	5 10	T _j = -10...+125	TO-92

Negative Regulators

IL79XXAC IL79XXC IL79XXB	79XXAC 79XXC 79XXB	5; 6; 8; 9; 12; 15; 18; 20; 24	1.0	2 4 4	T _j = -10...+125 T _j = -10...+125 T _j = -45...+125	TO-220
IL79LXXAC IL79LXXC	79LXXAC 79LXXC	5; 6; 8; 9; 12; 15; 18; 24	0.1	5 10	T _j = -10...+125	TO-92

Low Dropout Voltage Regulators

ILE4250G	TLE4250G	2 ÷ 36	0.05	0.5	T _j = -40...+150	P-TO-263-5-1 TO-220AB/5
ILE4260 ILE4260-2	TLE4260S	5	0.5	5 2	T _j = -40...+125	P-TO-220-5-12
ILE4264G	TLE4264G	5	0.10	2	T _j = -40...+125	P-SOT223-4-1
IZE4264-2	TLE4264-2G	5	0.10	3	T _j = -40...+125	Chip
ILE4266G	TLE4266G	5	0.10	2	T _j = -40...+125	P-SOT223-4-2
IZE4266-2	TLE4266-2G	5	0.10	3	T _j = -40...+125	Chip
ILE4267G ILE4267S	TLE4267G TLE4267S	5	0.4	2	T _j = -40...+125	P-TO-220-7-180 P-TO-220-7-230
ILE4268GDW	TLE4268G	5	0.15	2	T _j = -40...+125	SO-20
ILE4270G ILE4270S ILE4270Q	TLE4270G TLE4270S	5	0.55	2	T _j = -40...+125	P-TO-263-5-1 P-TO-220-5-12 P-TO-220-5-11
ILE4270 (without "RESET")		5	0.55	2	T _j = -40...+125	TO-220AB/3
ILE4271G ILE4271S	TLE4271G TLE4271S	5	0.55	2	T _j = -40...+125	P-TO-220-7-180 P-TO-220-7-230
ILE4274	TLE4274	5; 8.5; 10	0.4	4	T _j = -40...+150	TO-220AB/3
ILE4275G/S	TLE4275G	5	0.4	2	T _j = -40...+150	P-TO-263-5-1
ILE4276V	TLE4276	5; 8.5; 10	0.4	4	T _j = -40...+150	TO-220AB/5
IZE4278	TLE4278	5	0.15	2	T _j = -40...+150	Chip
IZ1734-33	SSAIC1734-33	3.3	0.3	2	T _j = -40...+125	Chip
IZ1734-50	SSAIC1734-50	5	0.3	2		
IZ1735-33	SSAIC1735-33	3.3	0.5	2		
IZ1735-50	SSAIC1735-50	5	0.5	2		

INTEGRATED CIRCUITS

Power Electronics, Standard Analog IC

• Voltage Regulators (continued)

Low Dropout Voltage Regulators

Part	Pin to Pin Compatibility	Output Voltage, V	Output Current, A	Output Voltage Tolerance, %	Tested Operating Junction Temp. Range, °C	Package
IL1117A	AMS1117A	1.2; 1.25; Adj; 1.5; 1.8; 2.5; 2.85; 3.3; 5	1.0	1.5	T _j = -40...+125	TO-220 TO-126
IL3480	LM3480	3.3; 5.0	0.1	4	T _j = -10...+125	TO-92
IL1084	LT1084	1.25; 1.5; 1.8; 2.5; 2.85; 3.3; 3.6; 5.0	5.0	1.5	T _j = -10...+125	TO-220
IL1085	LT1085	1.25; 1.5; 1.8; 2.5; 2.85; 3.3; 3.6; 5.0	3.0	1.5	T _j = -10...+125	TO-220

Adjustable Voltage Regulators

Part	Pin to Pin Compatibility	Function	Package
IL317	LM317T	Adjustable Output Positive Voltage Regulator 1.5 A; (1.2...37 V) T _j =-40...+125°C	TO-220AB/3
IL317L	LM317L	Adjustable Output Positive Voltage Regulator 0.1 A; (1.2...37 V) T _j =-40...+125°C	TO-92
IL2931CD	LM2931C	Adjustable Dropout Voltage Regulator 0.1 A; (3...24 V) T _j = -40...+125°C	SO-8

Switching Regulators

Part	Pin to Pin Compatibility	Function	Package
IL2576 – 3.3 IL2576 – 5 IL2576 – 12 IL2576 – 15 IL2576 – ADJ	LM2576 – 3.3 LM2576 – 5 LM2576 – 12 LM2576 – 15 LM2576 – ADJ	3A, 40V, 50 kHz Step-Down Switching Regulator	TO-220 AB/5
IL2576HV – 3.3 IL2576HV – 5 IL2576HV – 12 IL2576HV – 15 IL2576HV – ADJ	LM2576HV – 3.3 LM2576HV – 5 LM2576HV – 12 LM2576HV – 15 LM2576HV – ADJ	3A, 60V, 50 kHz Step-Down Switching Regulator	TO-220 AB/5
IL5256 – 3.3 IL5256 – 5 IL5256 – 12 IL5256 – ADJ	LM2596 – 3.3 LM2596 – 5 LM2596 – 12 LM2596 – ADJ	3A, 40V, 150 kHz Step-Down Voltage Regulator	TO-220 AB/5
IL34063AN IL34063AD	MC34063A	Step-Up /Down/inverting Switching Regulator (I _{sw} ≤1.5A)	Dip-8 SO-8

INTEGRATED CIRCUITS

Power Electronics, Standard Analog IC

• Precision Low Voltage Reference

Part	Pin to Pin Compatibility	Function	Features	Package
IL431	TL431	Programmable precision references. This monolithic IC voltage references operate as a low temperature coefficient Zener. The characteristics of these references make them excellent replacements for zener diodes in many applications such as digital voltmeters, power supplies, and operation amplifier circuits.	<ul style="list-style-type: none"> □ Vref = 2.5...37 V □ I_k max=100 mA □ Shunt Reference Dynamic Impedance $Z \leq 0.5 \Omega$ □ Tolerance 0.5%; 1%; 2% 	TO-92 SOT-23 SO-8
IL432	TL432		<ul style="list-style-type: none"> □ Vref= 1.24...16V □ I_kmax = 100 mA □ Shunt Reference Dynamic Impedance $Z \leq 0.5 \Omega$ □ Tolerance 0.5%; 1% 	TO-92

• PWM Controllers

Part	Pin to Pin Compatibility	Function	Package
IL494N	TL494IN	Pulse-Width-Modulation Control Circuit	DIP-16
IL6083N IL6083N-01	U6083B	Power Control With Interference Suppression (for IL6083N N-01: Duty cycle 10... 100%, V _{S1} =24.5...28.0 V, V _{S2} =18.5...22.0 V, V _{Batt1} =16.7...21.0 V (switched on), V _{batt1} =18.3...22.5 V (switched off), V _{TS} =10.1...10.7 V, I _s =5...17 mA)	DIP-8

• Voltage Detectors

Part	Pin to Pin Compatibility	Function	Package
IL70XX	KIA70XX	Voltage Detector U _{cc} max= 15 V; I _{oL} max<16 mA; U _s = 2.1/2.3/2.5/2.9/ 3.3/ 3.6/3.7/ 3.9/ 4.2/ 4.5 V	TO-92

• Power Supply ICs

Part	Pin to Pin Compatibility	Function	Package
IL1051	TSM1051	Constant Voltage and Constant Current Controller For Adaptors and Battery Chargers	DIP-8 Chip
IL7660	ICL7660	CMOS Voltage Converter	DIP-8, SO – 8, Chip

INTEGRATED CIRCUITS

Standard Digital Logic ICs

• IN74AC/ACTXXXN, D Series

Part	Pin to Pin Compatibility	Function	Package
IN74AC/ACT00N,D	MC74AC/ACT00N,D	Quad 2-Input NAND Gate	DIP-14, SO-14
IN74AC/ACT02N,D	MC74AC/ACT02N,D	Quad 2-Input NOR Gate	DIP-14, SO-14
IN74AC/ACT04N,D	MC74AC/ACT04N,D	Hex Inverter	DIP-14, SO-14
IN74AC/ACT05N,D	CD74AC/ACT05N,D	Hex Inverter, OC	DIP-14, SO-14
IN74AC/ACT08N,D	MC74AC/ACT08N,D	Quad 2-Input AND Gate	DIP-14, SO-14
IN74AC/ACT10N,D	MC74AC/ACT10N,D	Triple 3-Input Positive-NAND Gate	DIP-14, SO-14
IN74AC/ACT11N,D	MC74AC/ACT11N,D	Triple 3-Input AND Gate	DIP-14, SO-14
IN74AC/ACT14N,D	MC74AC/ACT14N,D	Hex Schmitt-Trigger Inverter	DIP-14, SO-14
IN74AC/ACT20N,D	CD74AC/ACT20N,D	Dual 4-Input NAND Gate	DIP-14, SO-14
IN74AC/ACT21N,D	Own	Dual 4-Input AND Gate	DIP-14, SO-14
IN74AC/ACT27N,D	Own	Triple 3-Input NOR Gate	DIP-14, SO-14
IN74AC/ACT32N,D	MC74A/ACTC32N,D	Quad 2-Input OR Gate	DIP-14, SO-14
IN74AC/ACT34N,D	own	Hex Non-Inverter	DIP-14, SO-14
IN74AC/ACT74N,D	MC74AC/ACT74N,D	Dual D-Type Flip-Flop	DIP-14, SO-14
IN74AC/ACT86N,D	MC74AC/ACT86N,D	Quad 2-Input Exclusive-OR Gate	DIP-14, SO-14
IN74AC/ACT109N,D	MC74AC/ACT109N,D	Dual J-K Positive-Edge-Triggered Flip-Flop	DIP-16, SO-16
IN74AC/ACT112N,D	CD74AC/ACT112N,D	Dual J-K Negative-Edge-Triggered Flip-Flop	DIP-16, SO-16
IN74AC/ACT125N,D	T74AC/ACT125N,D	Quad 3-State Buffer	DIP-14, SO-14
IN74AC/ACT132N,D	MC74AC/ACT132N,D	Quad 2-Input NAND Schmitt-Trigger Inverter	DIP-14, SO-14
IN74AC/ACT138N,D	MC74AC/ACT138N,D	3-8 Decoder/Demultiplexer	DIP-16, SO-16
IN74AC/ACT139N,D	MC74AC/ACT139N,D	Dual 2-4 Decoder/Demultiplexer	DIP-16, SO-16
IN74AC/ACT151N,D	MC74AC/ACT151N,D	8-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74AC/ACT153N,D	MC74AC/ACT153N,D	Dual 4-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74AC/ACT157N,D	MC74AC/ACT157N,D	Quad 2-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74AC/ACT158N,D	MC74AC/ACT158N,D	Quad 2-1 Data Selector/Multiplexer, INV	DIP-16, SO-16
IN74AC/ACT161N,D	MC74AC/ACT161N,D	4-Bit Synchronous Binary Counter, Asynchronous Reset	DIP-16, SO-16
IN74AC/ACT163N,D	MC74AC/ACT163N,D	4-Bit Synchronous Binary Counter, Synchronous Reset	DIP-16, SO-16
IN74AC/ACT164N,D	CD74AC/ACT164N,D	8-Bit Serial-In Parallel-Out Shift Register	DIP-14, SO-14
IN74AC/ACT174N,D	MC74AC/ACT174N,D	Hex D-Type Flip-Flop	DIP-16, SO-16
IN74AC/ACT175N,D	MC74AC/ACT175N,D	Quad D-Type Flip-Flop	DIP-16, SO-16
IN74AC/ACT192N,D	MC74AC/ACT192N,D	Synchronous Decade Up/Down Counter	DIP-16, SO-16
IN74AC/ACT193N,D	CD74AC/ACT193N,D	4-Bit Synchronous Binary Up/Down Counter	DIP-16, SO-16
IN74AC/ACT240N,D	MC74AC/ACT240N,D	Octal Buffer/Line Driver, INV (3-State)	DIP-20, SO-20
IN74AC/ACT241N,D	MC74AC/ACT241N,D	Octal Buffer/Line Driver, NINV (3-State)	DIP-20, SO-20
IN74AC/ACT244N,D	MC74AC/ACT244N,D	Octal Buffer/Line Driver NINV (3-State)	DIP-20, SO-20
IN74AC/ACT245N,D	MC74AC/ACT245N,D	Octal Bus Transceiver, NINV (3-State)	DIP-20, SO-20
IN74AC/ACT251N,D	MC74AC/ACT251N,D	8-1 Data Selector/Multiplexer (3-State)	DIP-16, SO-16
IN74AC/ACT253N,D	MC74AC/ACT253N,D	Dual 4-1 Data Selector/Multiplexer, NINV (3-State)	DIP-16, SO-16
IN74AC/ACT257N,D	MC74AC/ACT257N,D	Quad 2-1 Data Selector/Multiplexer, NINV (3-State)	DIP-16, SO-16
IN74AC/ACT258N,D	MC74AC/ACT258N,D	Quad 2-1 Data Selector/Multiplexer, INV (3-State)	DIP-16, SO-16
IN74AC/ACT273N,D	MC74AC/ACT273N,D	Octal D-Type Flip-Flop	DIP-20, SO-20
IN74AC/ACT299N,D	MC74AC/ACT299N,D	8-Bit Universal Shift/Storage Register (3-State)	DIP-20, SO-20
IN74AC/ACT323N,D	CD74AC/ACT323N,D	8-Bit Universal Shift/Storage Register (3-State)	DIP-20, SO-20
IN74AC/ACT373N,D	MC74AC/ACT373N,D	Octal D-Type Latch (3-State)	DIP-20, SO-20
IN74AC/ACT374N,D	MC74AC/ACT374N,D	Octal D-Type Flip-Flop (3-State)	DIP-20, SO-20
IN74AC/ACT533N,D	MC74AC/ACT533N,D	Octal D-Type Latch, INV (3-State)	DIP-20, SO-20
IN74AC/ACT534N,D	MC74AC/ACT534N,D	Octal D-Type Flip-Flop, NINV (3-State)	DIP-20, SO-20
IN74AC/ACT563N,D	MC74AC/ACT563N,D	Octal D-Type Transparent Latch	DIP-20, SO-20
IN74AC/ACT564N,D	MC74AC/ACT564N,D	Octal Edge-Triggered Flip-Flop	DIP-20, SO-20
IN74AC/ACT573N,D	MC74AC/ACT573N,D	Octal Transparent Latch (3-State)	DIP-20, SO-20
IN74AC/ACT574N,D	MC74AC/ACT574N,D	Octal D-Type Flip-Flop, NINV (3-State)	DIP-20, SO-20
IN74AC/ACT620N,D	MC74AC/ACT620N,D	Octal Bidirectional Bus Transceiver, INV	DIP-20, SO-20
IN74AC/ACT623N,D	MC74AC/ACT623N,D	Octal Bidirectional Bus Transceiver, NINV	DIP-20, SO-20
IN74AC/ACT640N,D	MC74AC/ACT640N,D	Octal Bus Transceiver (3-State)	DIP-20, SO-20

• IN74AC/ACTXXXN, D Series (continued)

Part	Pin to Pin Compatibility	Function	Package
IN74AC/ACT643N,D	MC74AC/ACT643N,D	Octal Bus Transceiver (3-State)	DIP-20, SO-20
IN74AC/ACT651N,D	CD74AC/ACT651N,D	Octal Bus Transceiver/Register, INV (3-State)	DIP-24, SO-24
IN74AC/ACT652N,D	Own	Octal Bus Transceiver/Register, NINV (3-State)	DIP-24, SO-24
IN74AC/ACT810N,D	MC74AC/ACT810N,D	Quad Exclusive-NOR Gate	DIP-14, SO-14
IN74AC/ACT4006N,D	own	18-Bit Static Shift Register	DIP-14, SO-14
IN74AC/ACT4015N,D	own	Dual 4-Bit Static Shift Register	DIP-16, SO-16
IN74AC/ACT4035N,D	own	4-Bit Parallel-In/Parallel-Out Shift Register	DIP-16, SO-16
IN74AC/ACT4520N,D	own	Dual 4-Bit Synchronous Binary Counter	DIP-16, SO-16

• IN74HC/HCTXXXAN, AD Series

Part	Pin to Pin Compatibility	Function	Package
IN74HC/HCT00AN,AD	MC74HC/HCT00AN,AD	Quad 2-Input NAND Gate	DIP-14, SO-14
IN74HC/HCT02AN,AD	MC74HC/HCT02AN,AD	Quad 2-Input NOR Gate	DIP-14, SO-14
IN74HC03AN,AD	MC74HC03AN,AD	Quad 2-Input NAND Gate, OC	DIP-14, SO-14
IN74HC/HCT04AN,AD	MC74HC/HCT04AN,AD	Hex Inverter	DIP-14, SO-14
IN74HC05AN,AD	SN74HC05AN,AD	Hex Inverter, OC	DIP-14, SO-14
IN74HC/HCT08AN,AD	MC74HC/HCT08AN,AD	Quad 2-Input AND Gate	DIP-14, SO-14
IN74HC/HCT10AN,AD	MC74HC/HCT10AN,AD	Triple 3-Input NAND Gate	DIP-14, SO-14
IN74HC11AN,AD	MC74HC11AN,AD	Triple 3-Input AND Gate	DIP-14, SO-14
IN74HC/HCT14AN,AD	MC74HC/HCT14AN,AD	Hex Schmitt-Trigger Inverter	DIP-14, SO-14
IN74HC/HCT20AN,AD	MC74HC/HCT20AN,AD	Dual 4-Input NAND Gate	DIP-14, SO-14
IN74HC21AN,AD	MC74HC21AN,AD	Dual 4-Input Positive-AND Gate	DIP-14, SO-14
IN74HC22AN,AD	MC74HC22AN,AD	Dual 4-Input Positive-NAND Gate, OC	DIP-14, SO-14
IN74HC/HCT27AN,AD	MC74HC/HCT27AN,AD	Triple 3-Input Positive-NOR Gate	DIP-14, SO-14
IN74HC/HCT30AN,AD	MC74HC/HCT30AN,AD	8-Input Positive-NAND Gate	DIP-14, SO-14
IN74HC/HCT32AN,AD	MC74HC/HCT32AN,AD	Quad 2-Input OR Gate	DIP-14, SO-14
IN74HC/HCT74AN,AD	MC74HC/HCT74AN,AD	Dual D-Type Flip-Flop	DIP-14, SO-14
IN74HC75AN,AD	MC74HC75AN,AD	Quad Bistable Latch	DIP-16, SO-16
IN74HC/HCT85AN,AD	MC74HC/HCT85AN,AD	4-Bit Magnitude Comparator	DIP-16, SO-16
IN74HC/HCT86AN,AD	MC74HC/HCT86AN,AD	Quad 2-Input Exclusive-OR Gate	DIP-14, SO-14
IN74HC109AN,AD	MC74HC109AN,AD	Dual J-K Positive-Edge-Triggered Flip-Flop	DIP-16, SO-16
IN74HC112AN,AD	MC74HC112AN,AD	Dual J-K Negative-Edge-Triggered Flip-Flop	DIP-16, SO-16
IN74HC123AN,AD	MC74HC123AN,AD	Dual Monostable Multivibrator with Reset	DIP-16, SO-16
IN74HC/HCT125AN,AD	MC74HC/HCT125AN,AD	Quad 3-State Buffer	DIP-14, SO-14
IN74HCT126AN,AD	MC74HCT126AN,AD	Quad 3-State Buffer	DIP-14, SO-14
IN74HC/HCT132AN,AD	MC74HC/HCT132AN,AD	Quad 2-Input NAND Schmitt-Trigger Inverter	DIP-14, SO-14
IN74HC/HCT138AN,AD	MC74HC/HCT138AN,AD	3-8 Decoder/Demultiplexer	DIP-16, SO-16
IN74HC/HCT139AN,AD	MC74HC/HCT139AN,AD	Dual 2-4 Decoder/Demultiplexer	DIP-16, SO-16
IN74HC/HCT151AN,AD	MC74HC/HCT151AN,AD	8-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74HC/HCT153AN,AD	MC74HC/HCT153AN,AD	Dual 4-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74HC154AN,AD	MC74HC154AN,AD	4-16 Decoder/Demultiplexer (3-State)	DIP-24, SO-24
IN74HC/HCT155AN,AD	MM74HC/HCT155AN,AD	Dual 2-4 Decoder/Demultiplexer	DIP-16, SO-16
IN74HC/HCT157AN,AD	MC74HC/HCT157AN,AD	Quad 2-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74HC158AN,AD	MC74HC158AN,AD	Quad 2-1 Data Selector/Multiplexer, INV	DIP-16, SO-16
IN74HC161AN,AD	MC74HC161AN,AD	4-Bit Synchronous Binary Counter, Asynchronous Reset	DIP-16, SO-16
IN74HC/HCT163AN,AD	MC74HC/HCT163AN,AD	4-Bit Synchronous Binary Counter, Synchronous Reset	DIP-16, SO-16
IN74HC/HCT164AN,AD	MC74HC/HCT164AN,AD	8-Bit Serial-In Parallel-Out Shift Register	DIP-14, SO-14
IN74HC/HCT165AN,AD	MC74HC/HCT165AN,AD	8-Bit Parallel-in Serial-Out Shift Register	DIP-16, SO-16
IN74HC166AN,AD	CD74HC166AN,AD	8-Bit Parallel-in Serial-Out Shift Register	DIP-16, SO-16
IN74HC/HCT174AN,AD	MC74HC/HCT174AN,AD	Hex D-Type Flip-Flop	DIP-16, SO-16

INTEGRATED CIRCUITS

Standard Digital Logic ICs

IN74HC175AN,AD	MC74HC175AN,AD	Quad D-Type Flip-Flop	DIP-16, SO-16
IN74HC192AN,AD	CD74HC192AN,AD	Synchronous Decade Up/Down Counter	DIP-16, SO-16
IN74HC193AN,AD	CD74HC193AN,AD	4-Bit Synchronous Binary Up/Down Counter	DIP-16, SO-16
IN74HC221AN,AD	CD74HC221AN,AD	Dual Monostable Multivibrator with Reset	DIP-16, SO-16
IN74HC/HCT240AN,AD W	MC74HC/HCT240AN,AD W	Octal Buffer/Line Driver, INV (3-State)	DIP-20, SO-20
IN74HC/HCT241AN,AD W	MC74HC/HCT241AN,AD W	Octal Buffer/Line Driver, NINV (3-State)	DIP-20, SO-20
IN74HC/HCT244AN,AD W	MC74HC/HCT244AN,AD W	Octal Buffer/Line Driver NINV (3-State)	DIP-20, SO-20
IN74HC/HCT245AN,AD W	MC74HC/HCT245AN,AD W	Octal Bus Transceiver, NINV (3-State)	DIP-20, SO-20
IN74HC/HCT251AN,AD	MC74HC/HCT251AN,AD	8-I Data Selector/Multiplexer (3-State)	DIP-16, SO-16
IN74HC253AN,AD	MC74HC253AN,AD	Dual 4-1 Data Selector/Multiplexer, NINV (3-State)	DIP-16, SO-16
IN74HC257AN,AD	MC74HC257AN,AD	Quad 2-1 Data Selector/Multiplexer, NINV (3-State)	DIP-16, SO-16
IN74HC258AN,AD	CD74HC258AN,AD	Quad 2-1 Data Selector/Multiplexer, INV (3-State)	DIP-16, SO-16
IN74HC/HCT273AN,AD W	MC74HC/HCT273AN,AD W	Octal D-Type Flip-Flop	DIP-20, SO-20
IN74HC279AN,AD	MC74HC279AN,AD	Quad Set/Reset Latch	DIP-16, SO-16
IN74HC/HCT283AN,AD	CD74HC/HCT283AN,AD	4-Bit Full Adder	DIP-16, SO-16
IN74HC/HCT299AN,AD W	MC74HC/HCT299AN,AD W	8-Bit Universal Shift/Storage Register (3-State)	DIP-20, SO-20
IN74HC/HCT323AN,AD W	MC74HC/HCT323AN,AD W	8-Bit Universal Shift/Storage Register (3-State)	DIP-20, SO-20
IN74HC365AN,AD	MC74HC365AN,AD	Hex Buffer/Line Driver (3-State)	DIP-16, SO-16
IN74HC367AN,AD	MC74HC367AN,AD	Hex Buffer/Line Driver (3-State)	DIP-16, SO-16
IN74HC/HCT373AN,AD W	MC74HC/HCT373AN,AD W	Octal D-Type Latch (3-State)	DIP-20, SO-20
IN74HC/HCT374AN,AD W	MC74HC/HCT374AN,AD W	Octal D-Type Flip-Flop (3-State)	DIP-20, SO-20
IN74HC393AN,AD	MC74HC393AN,AD	Dual 4-Bit Binary Counter	DIP-14, SO-14
IN74HC533AN,ADW	MC74HC533AN,AD	Octal D-Type Latch, INV (3-State)	DIP-20, SO-20
IN74HC534AN,ADW	MC74HC534AN,AD	Octal D-Type Flip-Flop, NINV (3-State)	DIP-20, SO-20
IN74HC/HCT573AN,AD W	MC74HC/HCT573AN,AD W	Octal Transparent Latch (3-State)	DIP-20, SO-20
IN74HC/HCT574AN,AD W	MC74HC/HCT574AN,AD W	Octal D-Type Flip-Flop, NINV (3-State)	DIP-20, SO-20
IN74HC595AN,AD	MC74HC595AN,AD	8-Bit Shift Register with Output Latch	DIP-16, SO-16
IN74HC597AN,AD	MC74HC597AN,AD	8-Bit Shift Register with Input Latch	DIP-16, SO-16
IN74HC/HCT620AN,AD W	SN74HC/HCT620AN,AD W	Octal Bidirectional Bus Transceiver, INV	DIP-20, SO-20
IN74HC/HCT623AN,AD W	SN74HC/HCT623AN,AD W	Octal Bidirectional Bus Transceiver, NINV	DIP-20, SO-20
IN74HC/HCT640AN,AD W	MC74HC/HCT640AN,AD W	Octal Bus Transceiver (3-State)	DIP-20, SO-20
IN74HC651AN,ADW	CD74HC651AN,AD	Octal Bus Transceiver/Register (3-State)	DIP-24, SO-24
IN74HC652AN,ADW	CD74HC652AN,AD	Octal Bus Transceiver/Register, NINV (3-State)	DIP-24, SO-24
IN74HC/HCT874AN,AD W	own	Dual 4-Bit D-Type Flip Flop	DIP-24, SO-24
IN74HC4015AN,AD	MC74HC4015AN,AD	Dual 4-Bit Static Shift Register	DIP-16, SO-16
IN74HC4046AN,AD	MC74HC4046AN,AD	Phase-Locked Loop	DIP-16, SO-16
IN74HC4051AN,AD	MC74HC4051AN,AD	8-Channel Analog Multiplexer/Demultiplexer	DIP-16, SO-16
IN74HC4052AN,AD	MC74HC4052AN,AD	Dual 4-Channel Analog Multiplexer/Demultiplexer	DIP-16, SO-16
IN74HC4053AN,AD	MC74HC4053AN,AD	Triple 2-Channel Analog Multiplexer/Demultiplexer	DIP-16, SO-16
IN74HC4094AN,AD	CD74HC4094AN,AD	8-Bit Shift and Bus Register	DIP-16, SO-16

• IN74LVXXN, D Series

Part	Pin to Pin Compatibility	Function	Package
IN74LV00N,D	74LV00N,D	Quad 2-Input NAND Gate	DIP-14, SO-14
IN74LV02N,D	74LV02N,D	Quad 2-Input NOR Gate	DIP-14, SO-14
IN74LV04N,D	74LV04N,D	Hex Inverter	DIP-14, SO-14
IN74LVU04N,D	74LVU04N,D	Hex Inverter	DIP-14, SO-14
IN74LV08N,D	74LV08N,D	Quad 2-Input AND Gate	DIP-14, SO-14
IN74LV14N,D	74LV14N,D	Hex Schmitt-Trigger Inverter	DIP-14, SO-14
IN74LV32N,D	74LV32N,D	Quad 2-Input OR Gate	DIP-14, SO-14
IN74LV74N,D	74LV74N,D	Dual D-Type Flip-Flop	DIP-14, SO-14
IN74LV86N,D	74LV86N,D	Quad 2-Input Exclusive-OR Gate	DIP-14, SO-14
IN74LV138N,D	74LV138N,D	3-8 Decoder/Demultiplexer	DIP-16, SO-16
IN74LV139N,D	74LV139N,D	Dual 2-4 Decoder/Demultiplexer	DIP-16, SO-16
IN74LV164N,D	74LV164N,D	8-Bit Serial-In Parallel-Out Shift Register	DIP-14, SO-14
IN74LV174N,D	74LV174N,D	Hex D-Type Flip-Flop	DIP-16, SO-16
IN74LV240N,D	74LV240N,D	Octal Buffer/line Driver, INV (3-State)	DIP-20, SO-20
IN74LV241N,D	74LV241N,D	Octal Buffer/Line Driver, NINV (3-State)	DIP-20, SO-20
IN74LV244N,D	74LV244N,D	Octal Buffer/Line Driver, NINV (3-State)	DIP-20, SO-20
IN74LV245N,D	74LV245N,D	Octal Bus Transceiver, NINV (3-State)	DIP-20, SO-20
IN74LV273N,D	74LV273N,D	Octal D-Type Flip-Flop	DIP-20, SO-20
IN74LV373N,D	74LV373N,D	Octal D-Type Latch (3-State)	DIP-20, SO-20
IN74LV374N,D	74LV374N,D	Octal D-Type Flip-Flop (3-State)	DIP-20, SO-20
IN74LV573N,D	74LV573N,D	Octal Transparent Latch (3-State)	DIP-20, SO-20
IN74LV574N,D	74LV574N,D	Octal D-Type Flip-Flop, NINV (3-State)	DIP-20, SO-20
IN74LV620N,D	74LV620N,D	Octal Bidirectional Bus Transceiver, INV	DIP-20, SO-20
IN74LV623N,D	74LV623N,D	Octal Bidirectional Bus Transceiver, NINV	DIP-20, SO-20
IN74LV640N,D	74LV640N,D	Octal Bus Transceiver (3-State)	DIP-20, SO-20

• IN74XXN, D Series

Part	Pin to Pin Compatibility	Function	Package
IN7401N	SN7401N	Quad 2-Input NAND Gate, OC	DIP-14
IN7406N,D	SN7406N,D	Hex Inverter/Buffer with High-Voltage Output, OC	DIP-14, SO-14
IN7420N	SN7420N	Dual 4-Input NAND Gate	DIP-14
IN7450N	SN7450N	Dual 2-Wide 2-Input AND-OR-Invert Gate	DIP-14
IN7472N	SN7472N	J-K Flip-Flop	DIP-14
IN74141N	SN74141N	BCD-to-Decimal Decoder/Driver	DIP-16
IN74145N	SN74145N	BCD-to-Decimal Decoder, OC	DIP-16
IN74154N	SN74154N	4-16 Decoder/Demultiplexer	DIP-24
IN74175N	SN74175N	Quad D-Type Flip-Flop	DIP-16

INTEGRATED CIRCUITS

Standard Digital Logic ICs

• IN74LSXXXN, D Series

Part	Pin to Pin Compatibility	Function	Package
IN74LS04N,D	CD74LS04N,D	Hex Inverter	DIP-14, SO-14
IN74LS05N,D	CD74LS05N,D	Hex Inverter, OC	DIP-14, SO-14
IN74LS06N,D	CD74LS06N,D	Hex Inverter/Buffer with High-Voltage Output, OC	DIP-14, SO-14
IN74LS07N,D	CD74LS07N,D	Hex Buffer with High-Voltage Output, OC, 30 V	DIP-14, SO-14
IN74LS14N,D	CD74LS14N,D	Hex Schmitt-Trigger Inverter	DIP-14, SO-14
IN74LS86N,D	CD74LS86N,D	Quad 2-Input Exclusive-OR Gate	DIP-14, SO-14
IN74LS138N,D	CD74LS138N,D	3-8 Decoder/Demultiplexer	DIP-16, SO-16
IN74LS157N,D	CD74LS157N,D	Quad 2-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74LS161AN,AD	CD74LS161AN,AD	4-Bit Binary Counter	DIP-16, SO-16
IN74LS164N,D	CD74LS164N,D	8-Bit Parallel-Out Shift Register	DIP-14, SO-14
IN74LS244N,D	CD74LS244N,DW	Octal Buffer/Line Driver, NINV (3-State)	DIP-20, SO-20
IN74LS245N,D	CD74LS245N,DW	Octal Bus Transceiver, NINV (3-State)	DIP-20, SO-20

• IN74ALSXXXXN, D Series

Part	Pin to Pin Compatibility	Function	Package
IN74ALS00AN,A	SN74ALS00AN,AD	Quad 2-Input Positive-NAND Gate	DIP-14, SO-14
IN74ALS01N,D	SN74ALS01N,D	Quad 2-Input Positive-NAND Gate, OC	DIP-14, SO-14
IN74ALS02N,D	SN74ALS02N,D	Quad 2-Input Positive-NOR Gate	DIP-14, SO-14
IN74ALS03AN,A	SN74ALS03AN,AD	Quad 2-Input Positive-NAND Gate, OC	DIP-14, SO-14
IN74ALS04AN,A	SN74ALS04AN,AD	Hex Inverter	DIP-14, SO-14
IN74ALS05AN,A	SN74ALS05AN,AD	Hex Inverter, OC	DIP-14, SO-14
IN74ALS08N,D	SN74ALS08N,D	Quad 2-Input Positive-AND Gate	DIP-14, SO-14
IN74ALS09N,D	SN74ALS09N,D	Quad 2-Input Positive-AND Gate, OC	DIP-14, SO-14
IN74ALS10AN,AD	SN74ALS10AN,AD	Triple 3-Input Positive-NAND Gate	DIP-14, SO-14
IN74ALS11AN,AD	SN74ALS11AN,AD	Triple 3-Input Positive-AND Gate	DIP-14, SO-14
IN74ALS12AN,AD	SN74ALS12AN,AD	Triple 3-Input Positive-NAND Gate, OC	DIP-14, SO-14
IN74ALS14N,D	SN74ALS14N,D	Hex Schmitt-Trigger Inverter	DIP-14, SO-14
IN74ALS15AN,AD	SN74ALS15AN,AD	Triple 3-Input Positive-AND Gate, OC	DIP-14, SO-14
IN74ALS20AN,AD	SN74ALS20AN,AD	Dual 4-Input Positive-NAND Gate	DIP-14, SO-14
IN74ALS21N,AD	SN74ALS21N,AD	Dual 4-Input Positive-AND Gate	DIP-14, SO-14
IN74ALS22BN,BD	SN74ALS22BN,BD	Dual 4-Input Positive-NAND Gate, OC	DIP-14, SO-14
IN74ALS27N,D	SN74ALS27N,D	Triple 3-Input Positive-NOR Gate	DIP-14, SO-14
IN74ALS30AN,AD	SN74ALS30AN,AD	8-Input Positive-NAND Gate	DIP-14, SO-14
IN74ALS32N,D	SN74ALS32N,D	Quad 2-Input Positive-OR Gate	DIP-14, SO-14
IN74ALS33AN,AD	SN74ALS33AN,AD	Quad 2-Input Positive-NOR Buffer, OC	DIP-14, SO-14

• IN74ALSXXXXN, D Series (continued)

Part	Pin to Pin Compatibility	Function	Package
IN74ALS51N,D	SN74ALS51N,D	AND-OR-Invert Gate	DIP-14, SO-14
IN74ALS54N,D	SN74ALS54N,D	4-Wide AND-OR-Invert Gate	DIP-14, SO-14
IN74ALS55N,D	SN74ALS55N,D	2-Wide 4-Input AND-OR-Invert Gate	DIP-14, SO-14
IN74ALS74AN,AD	SN74ALS74AN,AD	Dual D-Type Flip-Flop	DIP-14, SO-14
IN74ALS75N,D	SN74ALS75N,D	Quad Bistable Latch	DIP-16, SO-16
IN74ALS85N,D	SN74ALS85N,D	4-Bit Magnitude Comparator	DIP-16, SO-16
IN74ALS86N,D	SN74ALS86N,D	Quad 2-Input Exclusive-OR Gate	DIP-14, SO-14
IN74ALS90N,D	SN74ALS90N,D	4-Bit Decade Counter	DIP-14, SO-14
IN74ALS93N,D	SN74ALS93N,D	4-Bit Binary Counter	DIP-14, SO-14
IN74ALS107N,D	SN74ALS107N,D	Dual J-K Flip-Flop with Clear	DIP-14, SO-14
IN74ALS109N,D	SN74ALS109N,D	Dual J-K Positive-Edge-Triggered Flip-Flop	DIP-16, SO-16
IN74ALS112AN,AD	SN74ALS112AN,AD	Dual J-K Negative-Edge-Triggered Flip-Flop	DIP-16, SO-16
IN74ALS113AN,AD	SN74ALS113AN,AD	Dual J-K Negative-Edge-Triggered Flip-Flop	DIP-14, SO-14
IN74ALS114AN,AD	SN74ALS114AN,AD	Dual J-K Negative-Edge-Triggered Flip-Flop	DIP-14, SO-14
IN74ALS123N,D	SN74ALS123N,D	Dual Monostable Multivibrator with Reset	DIP-16, SO-16
IN74ALS125N,D	SN74ALS125N,D	Quad 3-State Buffer	DIP-14, SO-14
IN74ALS136N,D	SN74ALS136N,D	Quad 2-Input Exclusive-OR Gate, OC	DIP-14, SO-14
IN74ALS138N,D	SN74ALS138N,D	3-8 Decoder/Demultiplexer	DIP-16, SO-16
IN74ALS139N,D	SN74ALS139N,D	Dual 2-4 Decoder/Demultiplexer	DIP-16, SO-16
IN74ALS151N,D	SN74ALS151N,D	8-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74ALS153N,D	SN74ALS153N,D	Dual 4-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74ALS154N,DW	SN74ALS154N,D	4-16 Decoder/Demultiplexer (3-State)	DIP-24, SO-24
IN74ALS155N,D	SN74ALS155N,D	Dual 2-4 Decoder/Demultiplexer	DIP-16, SO-16
IN74ALS157N,D	SN74ALS157N,D	Quad 2-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74ALS158N,D	SN74ALS158N,D	Quad 2-1 Data Selector/Multiplexer, INV	DIP-16, SO-16
IN74ALS160AN,AD	SN74ALS160AN,AD	Synchronous Decade Counter, Asynchronous Reset	DIP-16, SO-16
IN74ALS161AN,AD	SN74ALS161AN,AD	4-Bit Synchronous Binary Counter, Asynchronous Reset	DIP-16, SO-16
IN74ALS162AN,AD	SN74ALS162AN,AD	Synchronous Decade Counter, Synchronous Reset	DIP-16, SO-16
IN74ALS163AN,AD	SN74ALS163AN,AD	4-Bit Synchronous Binary Counter, Synchronous Reset	DIP-16, SO-16
IN74ALS164N,D	SN74ALS164N,D	8-Bit Serial-In Parallel-Out Shift Register	DIP-14, SO-14
IN74ALS165N,D	SN74ALS165N,D	8-Bit Parallel-in Serial-Out Shift Register	DIP-16, SO-16
IN74ALS166N,D	SN74ALS166N,D	8-Bit Parallel-in Serial-Out Shift Register	DIP-16, SO-16
IN74ALS170N,D	SN74ALS170N,D	4-by-4 Register File, OC	DIP-16, SO-16
IN74ALS173AN,AD	SN74ALS173AN,AD	4-Bit D-Type Register (3-State)	DIP-16, SO-16
IN74ALS174N,D	SN74ALS174N,D	Hex D-Type Flip-Flop	DIP-16, SO-16
IN74ALS175N,D	SN74ALS175N,D	Quad D-Type Flip-Flop	DIP-16, SO-16
IN74ALS181N,DW	SN74ALS181N,D	4-Bit Arithmetic Logic Unit	DIP-24, SO-24
IN74ALS182N,D	SN74ALS182N,D	Look-Ahead Carry Generator	DIP-16, SO-16
IN74ALS190N,D	SN74ALS190N,D	Synchronous Decade Up/Down Counter	DIP-16, SO-16
IN74ALS191N,D	SN74ALS191N,D	4-Bit Synchronous Binary Up/Down Counter	DIP-16, SO-16
IN74ALS192N,D	SN74ALS192N,D	Synchronous Decade Up/Down Counter	DIP-16, SO-16
IN74ALS193N,D	SN74ALS193N,D	4-Bit Synchronous Binary Up/Down Counter	DIP-16, SO-16
IN74ALS240AN,AD	SN74ALS240AN,AD	Octal Buffer/Line Driver, INV (3-State)	DIP-20, SO-20
IN74ALS241AN,AD	SN74ALS241AN,AD	Octal Buffer/Line Driver, NINV (3-State)	DIP-20, SO-20
IN74ALS242AN,AD	SN74ALS242AN,AD	Quad Bus Transceiver, INV (3-State)	DIP-14, SO-14
IN74ALS243AN,AD	SN74ALS243AN,AD	Quad Bus Transceiver, NINV (3-State)	DIP-14, SO-14
IN74ALS244AN,AD	SN74ALS244AN,AD	Octal Buffer/Line Driver, NINV (3-State)	DIP-20, SO-20
IN74ALS245AN,AD	SN74ALS245AN,AD	Octal Bus Transceiver, NINV (3-State)	DIP-20, SO-20
IN74ALS251N,D	SN74ALS251N,D	8-1 Data Selector/Multiplexer, INV (3-State)	DIP-16, SO-16
IN74ALS253N,D	SN74ALS253N,D	Dual 4-1 Data Selector/Multiplexer, NINV (3-State)	DIP-16, SO-16
IN74ALS257AN,AD	SN74ALS257AN,AD	Quad 2-1 Data Selector/Multiplexer, NINV (3-State)	DIP-16, SO-16
IN74ALS258AN,AD	SN74ALS258AN,AD	Quad 2-1 Data Selector/Multiplexer, INV (3-State)	DIP-16, SO-16
IN74ALS259N,D	SN74ALS259N,D	8-Bit Addressable Latch	DIP-16, SO-16
IN74ALS273N,DW	SN74ALS273N,D	Octal D-Type Flip-Flop	DIP-20, SO-20
IN74ALS279N,D	SN74ALS279N,D	Quad Set/Reset Latch	DIP-16, SO-16
IN74ALS280N,D	SN74ALS280N,D	9-Bit Odd/Even Parity Generator/Checker	DIP-14, SO-14

INTEGRATED CIRCUITS

Standard Digital Logic ICs

• IN74ALSXXXN, D Series (continued)

Part	Pin to Pin Compatibility	Function	Package
IN74ALS295BN,BD	SN74ALS295BN,BD	4-Bit Universal Shift Register	DIP-14, SO-14
IN74ALS298N,D	SN74ALS298N,D	Quad 2-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74ALS299N,DW	SN74ALS299N,D	8-Bit Universal Shift/Storage Register (3-State)	DIP-20, SO-20
IN74ALS323N,DW	SN74ALS323N,D	8-Bit Universal Shift/Storage Register (3-State)	DIP-20, SO-20
IN74ALS352N,D	SN74ALS352N,D	Dual 4-1 Data Selector/Multiplexer	DIP-16, SO-16
IN74ALS353N,D	SN74ALS353N,D	Dual 4-1 Data Selector/Multiplexer (3-State)	DIP-16, SO-16
IN74ALS368N,D	SN74ALS368N,D	Hex Bus Driver (3-State)	DIP-16, SO-16
IN74ALS373N,DW	SN74ALS373N,D	Octal D-Type Latch (3-State)	DIP-20, SO-20
IN74ALS374AN,AD	SN74ALS374AN,AD	Octal D-Type Flip-Flop (3-State)	DIP-20, SO-20
IN74ALS377AN,AD	SN74ALS377AN,AD	Octal D-Type Flip-Flop with Enable	DIP-20, SO-20
IN74ALS393N,D	SN74ALS393N,D	Dual 4-Bit Binary Counter	DIP-14, SO-14
IN74ALS465AN,AD	SN74ALS465AN,AD	Octal Buffer, NINV (3-State)	DIP-20, SO-20
IN74ALS466AN,AD	SN74ALS466AN,AD	Octal Buffer, INV (3-State)	DIP-20, SO-20
IN74ALS573N,D	SN74ALS573N,D	Octal Transparent Latch (3-State)	DIP-20, SO-20
IN74ALS574N,D	SN74ALS574N,D	Octal D-Type Flip-Flop (3-State)	DIP-20, SO-20
IN74ALS640BN,BD	SN74ALS640BN,BD	Octal Bus Transceiver (3-State)	DIP-20, SO-20
IN74ALS643AN,AD	SN74ALS643AN,AD	Octal Bus Transceiver (3-State)	DIP-20, SO-20
IN74ALS670N,D	SN74ALS670N,D	4-by-4 Register File (3-State)	DIP-16, SO-16
IN74ALS873N,D	SN74ALS873N,D	Dual 4-Bit D-Type Latch (3-State)	DIP-24, SO-24
IN74ALS874N,D	SN74ALS874N,D	Dual 4-Bit D-Type Flip-Flop	DIP-24, SO-24
IN74ALS1000AN,AD	SN74ALS1000AN,AD	Quad 2-Input Positive-NAND Buffer	DIP-14, SO-14
IN74ALS1002AN,AD	SN74ALS1002AN,AD	Quad 2-Input Positive-NOR Buffer	DIP-14, SO-14
IN74ALS1003AN,AD	SN74ALS1003AN,AD	Quad 2-Input Positive-NAND Buffer, OC	DIP-14, SO-14
IN74ALS1004N,D	SN74ALS1004N,D	Hex Inverting Driver	DIP-14, SO-14
IN74ALS1005N,D	SN74ALS1005N,D	Hex Inverting Buffer, OC	DIP-14, SO-14
IN74ALS1008AN,AD	SN74ALS1008AN,AD	Quad 2-Input Positive-NAND Buffer	DIP-14, SO-14
IN74ALS1010AN,AD	SN74ALS1010AN,AD	Triple 3-Input Positive-NAND Buffer	DIP-14, SO-14
IN74ALS1011AN,AD	SN74ALS1011AN,AD	Triple 3-Input Positive-AND Buffer	DIP-14, SO-14
IN74ALS1020AN,AD	SN74ALS1020AN,AD	Dual 4-Input Positive-NAND Buffer	DIP-14, SO-14
IN74ALS1032AN,AD	SN74ALS1032AN,AD	Quad 2-Input Positive-OR Buffer/Driver	DIP-14, SO-14
IN74ALS1034N,D	SN74ALS1034N,D	Hex Driver	DIP-14, SO-14
IN74ALS1035N,D	SN74ALS1035N,D	Hex Noninverting Buffer, OC	DIP-14, SO-14

• IW4000BN, D Series

Part	Pin to Pin Compatibility	Function	Package
IW4001BN,BD	CD4001BN,BD	Quad 2-Input NOR Gate	DIP-14, SO-14
IW4002BN,BD	CD4002BN,BD	Dual 4-Input NOR Gate	DIP-14, SO-14
IW4006BN,BD	CD4006BN,BD	18-Bit Static Shift Register	DIP-14, SO-14
IW4008BN,BD	CD4008BN,BD	4-Bit Full Adder	DIP-16, SO-16
IW4011BN,BD	CD4011BN,BD	Quad 2-Input NAND Gate	DIP-14, SO-14
IW4012BN,BD	CD4012BN,BD	Dual 4-Input NAND Gate	DIP-14, SO-14
IW4013BN,BD	CD4013BN,BD	Dual D-Type Flip-Flop	DIP-14, SO-14
IW4015BN,BD	CD4015BN,BD	Dual 4-Bit Static Shift Register	DIP-16, SO-16
IW4016BN,BD	CD4016BN,BD	Quad Bilateral Switch	DIP-14, SO-14
IW4017BN,BD	CD4017BN,BD	Decade Counter/Driver	DIP-16, SO-16
IW4018BN,BD	CD4018BN,BD	Presetable Divide-by-N Counter	DIP-16, SO-16
IW4019BN,BD	CD4019BN,BD	Quad AND-OR Gate	DIP-16, SO-16
IW4020BN,BD	CD4020BN,BD	14-Bit Binary Divide Counter	DIP-16, SO-16

• IW4000BN, D Series (continued)

Part	Pin to Pin Compatibility	Function	Package
IW4021BN,BD	CD4021BN,BD	8-Bit Shift Register	DIP-16, SO-16
IW4022BN,BD	CD4022BN,BD	Divide-by-8 Counter/Divider	DIP-16, SO-16
IW4023BN,BD	CD4023BN,BD	Triple 3-Input NAND Gate	DIP-14, SO-14
IW4025BN,BD	CD4025BN,BD	Triple 3-Input NOR Gate	DIP-14, SO-14
IW4027BN,BD	CD4027BN,BD	Dual J-K Flip-Flop	DIP-16, SO-16
IW4028BN,BD	CD4028BN,BD	BCD-to-Decimal Decoder	DIP-16, SO-16
IW4029BN,BD	CD4029BN,BD	Binary or BCD-Decade Counter	DIP-16, SO-16
IW4030BN,BD	CD4030BN,BD	Quad Exclusive-OR Gate	DIP-14, SO-14
IW4034BN,BD	CD4034BN,BD	8-Bit Shift Register	DIP-24, SO-24
IW4035BN,BD	CD4035BN,BD	4-Bit Parallel-In/Parallel-Out Shift Register	DIP-16, SO-16
IW4040BN,BD	CD4040BN,BD	12-Bit Binary Counter	DIP-16, SO-16
IW4042BN,BD	CD4042BN,BD	Quad Clocked D-Latch	DIP-16, SO-16
IW4043BN,BD	CD4043BN,BD	Quad NOR R-S Latch (3-State)	DIP-16, SO-16
IW4049BN,BD	CD4049BN,BD	Hex Buffer/Converter	DIP-16, SO-16
IW4050BN,BD	CD4050BN,BD	Hex Buffer/Converter	DIP-16, SO-16
IW4051BN,BD	CD4051BN,BD	8-Channel Analog Multiplexer/Demultiplexer	DIP-16, SO-16
IW4052BN,BD	CD4052BN,BD	Dual 4-Channel Analog Multiplexer/Demultiplexer	DIP-16, SO-16
IW4053BN,BD	CD4053BN,BD	Triple 2-Channel Analog Multiplexer/Demultiplexer	DIP-16, SO-16
IW4059AN,AD	CD4059AN,AD	Programmable Counter	DIP-24, SO-24
IW4060BN,BD	CD4060BN,BD	14-Bit Binary Divide/ Counter	DIP-16, SO-16
IW4066BN,BD	CD4066BN,BD	Quad Bilateral Switch	DIP-14, SO-14
IW4068BN,BD	CD4068BN,BD	8-Input NAND Gate	DIP-14, SO-14
IW4069UBN,UBD	CD4069UBN,UBD	Hex Inverter	DIP-14, SO-14
IW4070BN,BD	CD4070BN,BD	Quad Exclusive-OR Gate	DIP-14, SO-14
IW4071BN,BD	CD4071BN,BD	Quad 2-Input OR Gate	DIP-14, SO-14
IW4072BN,BD	CD4072BN,BD	Dual 4-Input OR Gate	DIP-14, SO-14
IW4073BN,BD	CD4073BN,BD	Triple 3-Input AND Gate	DIP-14, SO-14
IW4075BN,BD	CD4075BN,BD	Triple 3-Input OR Gate	DIP-14, SO-14
IW4077BN,BD	CD4077BN,BD	Quad Exclusive-NOR Gate	DIP-14, SO-14
IW4081BN,BD	CD4081BN,BD	Quad 2-Input AND Gate	DIP-14, SO-14
IW4093BN,BD	CD4093BN,BD	Quad 2-Input NAND Schmitt Trigger	DIP-14, SO-14
IW4098BN,BD	CD4098BN,BD	Dual Monostable Multivibrator	DIP-16, SO-16
IW40107BN,BD	CD40107BN,BD	Dual 2-Input NAND Buffer/Driver	DIP-14, SO-14
IW4502BN,BD	CD4502BN,BD	Hex Inverter/Buffer	DIP-16, SO-16
IW4503BN,BD	CD4503BN,BD	Hex Buffer	DIP-16, SO-16
IW4511BN,BD	CD4511BN,BD	BCD-to-7-Segment Latch Decoder/Driver	DIP-16, SO-16
IW4516BN,BD	CD4516BN,BD	Presetable Binary Up/Down Counter	DIP-16, SO-16
IW4518BN,BD	CD4518BN,BD	Dual BCD Up Counter	DIP-16, SO-16
IW4519BN,BD	CD4519BN,BD	Quad AND/OR Select Gate	DIP-16, SO-16
IW4520BN,BD	CD4520BN,BD	Dual Binary Up Counter	DIP-16, SO-16
IW4528BN,BD	CD4528BN,BD	Dual Monostable Multivibrator	DIP-16, SO-16
IW4531BN,BD	NEF4531BN,BD	12-Bit Checker Tree	DIP-16, SO-16
IW4541BN,BD	CD4541BN,BD	Programmable Timer	DIP-14, SO-14
IW4543BN,BD	CD4543BN,BD	BCD-to-7-Segment Latch/Decoder/Driver for Liquid-Crystal Display	DIP-16, SO-16
IW4585BN,BD	CD4585BN,BD	4-Bit Comparator	DIP-16, SO-16

• FAMILY CHARACTERISTICS

DC Characteristics (Max)

	TTL			CMOS							Units
	74	74LS	74ALS	4000B	74AC	74ACT	74HC	74HCT	74LV		
	5±5%	5±5%	5±10%	3...18	2...6	5±10%	2...6	5±10%	1.0...5.5		
Supply Voltage Range, $V_{CC}(V_{DD})$	-10...+70	0...+70	-10...+70	-55...+125	-45...+85	-45...+85	-55...+125	-55...+125	-40...+125	V	
Operating Temperature, T_A	2	2	2	0.7xV _{DD}	0.7xV _{CC}	2	0.7xV _{CC}	2	0.7xV _{CC}	°C	
High -Level Input Voltage, V_{IH} (min)	0.8	0.8	0.8	0.3xV _{DD}	0.3xV _{CC}	0.8	0.3xV _{CC}	0.8	0.3xV _{CC}	V	
Low -Level Input Voltage, V_{IL} (max)	2.4	V _{CC} -2	V _{CC} -2	V _{DD} -0.05	V _{CC} -0.1	V _{CC} -0.1	V _{CC} -0.1	V _{CC} -0.1	V _{CC} -0.2	V	
High-Level Output Voltage, V_{OH} (min)	0.4	0.5	0.5	0.05	0.1	0.1	0.1	0.1	0.2	V	
Low-Level Output Voltage, V_{OL} (max)	40	20	20	+0.3	+1	+1	+1	+1	+1	µA	
High-Level Input Current, I_{IH}	-1600	-400	-100	-0.3	-1	-1	-1	-1	-1	µA	
Low-Level Input Current, I_{IL}	-0.4	-0.4	-0.4	-4.2 at $V_0=2.5V$ $V_{DD}=5.0V$	-24 at $V_0=V_{CC}-0.8$	-24 at $V_0=V_{CC}-0.8$	-4 at $V_0=V_{CC}-0.8$	-4 at $V_0=V_{CC}-0.8$	-16	mA	
High-Level Output Current, I_{OH}	16	8	8	0.88 at $V_0=0.4V$ $V_{DD}=5.0V$	24 at $V_0=0.4V$	24 at $V_0=0.4V$	4 at $V_0=0.4V$	4 at $V_0=0.4V$	16	mA	
Low-Level Output Current, I_{OL}	0.4/0.4	0.3/0.7	0.3/0.7	1.5 at $V_{DD}=5V$ 3.0 at $V_{DD}=10V$ 4.0 at $V_{DD}=15V$	1.25/1.25	0.7/2.4	1.25/1.25	0.7/2.4	0.8/0.8	V	
DC Noise Margin, DCM											

• FAMILY CHARACTERISTICS

DC Characteristics (Type)

Parameters	TTL			CMOS					Units
	74	74LS	74ALS	74AC	74ACT	74HC	74HCT	74LV	
Supply Current for Gate, I_G	3.4	0.4	0.2	0.0005	0.0005	0.0005	0.0005	0.0005	mA
Power Supply for Gate, P_G	10	2	1	0.0025	0.0025	0.001	0.001	0.001	mW
Propagation Delay Time, T_P	10	7	5	5	5	8	8	10	ns
Clock Frequency, F_{max}	35 $C_L=15$ pF	40	45	140	140	30	30	40	MHz
		$C_L=15$ pF	$C_L=50$ pF	$C_L=50$ pF	$C_L=50$ pF	$C_L=50$ pF	$C_L=50$ pF	$C_L=50$ pF	
Inputs V_{IL}/V_{IH}	TTL	TTL	TTL	CMOS	TTL, CMOS	CMOS	TTL, CMOS	CMOS	-
Outputs V_{OL}/V_{OH}	TTL	TTL	TTL	TTL, CMOS	TTL, CMOS	TTL, CMOS	TTL, CMOS	TTL, CMOS	-

● FAMILY CHARACTERISTICS

AC Characteristics

Parameters	Performance	TTL			CMOS					Units
		7400	74LS00	74ALS00	74AC00	74ACT00	74HC00	74HCT00	74LV00	
Propagation Delay, t_{PHL}/t_{PHL}	Type	10 $C_L=15$ pF	7 $C_L=15$ pF	5 $C_L=50$ pF	5 $C_L=50$ pF	5 $C_L=50$ pF	8 $C_L=50$ pF	8 $C_L=50$ pF	10 $C_L=50$ pF	ns
	Gate, NOR or NAND									
Propagation Delay, t_{PHL}/t_{PHL} (Clock to Q)	Max	22 $C_L=15$ pF	15 $C_L=15$ pF	11 $C_L=50$ pF	8.5 $C_L=50$ pF	9.5 $C_L=50$ pF	22 $C_L=50$ pF	28 $C_L=50$ pF	14 $C_L=50$ pF	ns
		74163	74LS163	74ALS163	74AC163	74ACT163	74HC163	74HCT163	74LV163	
Propagation Delay, t_{PHL}/t_{PHL} (Clock to Q)	Type	16 $C_L=15$ pF	18 $C_L=15$ pF	10 $C_L=50$ pF	5 $C_L=50$ pF	6 $C_L=50$ pF	20 $C_L=50$ pF	20 $C_L=50$ pF	18 $C_L=50$ pF	sn
	Counter									
Propagation Delay, t_{PHL}/t_{PHL} (Clock to Q)	Max	38 $C_L=15$ pF	27 $C_L=15$ pF	26 $C_L=50$ pF	9.5 $C_L=50$ pF	12 $C_L=50$ pF	28 $C_L=50$ pF	28 $C_L=50$ pF	23 $C_L=50$ pF	ns
		7474	74LS74	74ALS74	74AC74	74ACT74	74HC74	74HCT74	74LV74	
Propagation Delay, t_{PHL}/t_{PHL} (Clock to Q)	Type	25 $C_L=15$ pF	25 $C_L=15$ pF	13 $C_L=50$ pF	6 $C_L=50$ pF	6 $C_L=50$ pF	20 $C_L=50$ pF	24 $C_L=50$ pF	25 $C_L=50$ pF	ns
	Flip-Flop, D-Type									
Propagation Delay, t_{PHL}/t_{PHL} (Clock to Q)	Max	40 $C_L=15$ pF	40 $C_L=15$ pF	18 $C_L=50$ pF	10 $C_L=50$ pF	11.5 $C_L=50$ pF	30 $C_L=50$ pF	36 $C_L=50$ pF	35 $C_L=50$ pF	ns

• **CMOS ICs for LCD Wrist-Watches and Clocks**

Part (Pin to Pin Compatibility)	Display			Functions				Multi- plexing Ratio	Supply Current without Load max, μA	V _{DD} , V	Notes	
	Digits	Flags	Marks	Hour Minute Second Month Date	Alarm	Chrono- graph	12H/ 24H					
Digital watch												
IZ6099F (KS5199)	3.5		1	+			12	1/2	1.5	1.5		
Analog clock												
IZ33173	Output pulse duration 31.25 ms							2.0	1.5	Clock IC		
IZ33567								1.5	1.5	Clock with alarm, snooze, crescendo		

• **Electronic Thermometer IC**

Part	Pin to Pin Compatibility	Function	Features	Package
IZ8016		100° Digital thermometer °C/°F	<ul style="list-style-type: none"> □ Measurement temperature range: from -50°C to +50°C (from -58°F to +122°F) □ Resolution: 0.2°C (°F) □ Accuracy: ±1°C (°F) □ Supply voltage 1.5V □ Measurement cycle 1, 3, 5 & 10 seconds (on default– 10 seconds) □ Measuring RC-oscillator with external resistor & capacitor □ 32 kHz clock RC-oscillator with build-in capacity □ Serial interface □ Build-in circuit of non-linear digital correction □ 3.5 digit LCD with double multiplex 	Chip
IZ8005	HT7501	Medical thermometer	<ul style="list-style-type: none"> □ Supply voltage 1.5V □ Measurement temperature range: from +32.00°C to+43.00°C □ Accuracy: ±0.1°C □ Resolution: 0.01°C □ Selftesting □ Alarm signal □ Storage of measurements results (highest temperature) □ Automatic switch-off after 8 min 40 sec □ One button on/off switching 	Chip
IZ8071		Digital medical thermometer	<ul style="list-style-type: none"> □ Measurement temperature range: from 32 to 42°C (from 89.6 to 107.6°F) □ Measurement accuracy: ±0.05°C – for range from 35 to 38°C, ±0.1°C – for ranges from 32 to 35°C & from 38°C to 42°C □ Resolution: 0.0025°C □ RC-oscillator with own frequency 32.32kHz (external resistance) with adjustment function □ Build-in LCD driver circuit 3COM x 11SEG, 1/3 duty, 1/2 bias 	Chip
IN18B20 IN18B20D	DS18B21	Integrated circuit of digital sensor- measurer of temperature for industrial temperature range	<ul style="list-style-type: none"> □ Measurement temperature range: from -55°C to +125°C □ Temperature value is converted to 12-bit digital code □ Accuracy of temperature indication can be programmed by customer form 9 to 12 bit □ Alarm signal for case of temperature excess of threshold values determined (programmed) by customer □ Unique 64-bit serial number for each IC, not available for changes by customer □ Data read/write operation from memory of IC, 1-wire interface of data transfer 	TO-92 SO-8

INTEGRATED CIRCUITS

Clock IC, Electronic Thermometer IC

• Melody IC

Part	Maximum Number of Tunes (Notes)	Vcc V	Icc, μ A		Package
			Tune Play	Stop	
BT8028C-XX	16 (64)	1.3 – 3.3	60	0.5	TO-92
BT8031-XX	2 (127)	1.3 – 3.3	1.0	0.5	TO-92

XX – Melody code

• Voltage Controlled Oscillator (VCO) IC

Part	Pin to Pin Compatibility	Function	Features	Package
IZC6990	IZC6990	Voltage Controlled Oscillator	<ul style="list-style-type: none">□ Supply Voltage 2.25V-5.5V□ Frequency Range: 488Hz to 2MHz□ 72μA Supply Current at 100kHz□ Fixed-Frequency or Voltage-Controlled Operation<ul style="list-style-type: none">- Fixed: Single resistor programs frequency with <1.5% max error;- VCO: Two resistors set VCO center frequency and tuning range□ CMOS Logic Output Sources/Sinks 20mA	Chip

DISCRETE SEMICONDUCTORS

DISCRETE SEMICONDUCTORS

Transistors

• Power N-Channel MOSFETs

Part	Function	Package
IFP630	N-Channel MOSFET 200 V; 0.400 Ω - 9 A	Chip
IFF630		Chip
IFP640	N-Channel MOSFET 200 V; 0.180 Ω - 18 A	Chip
IFF640		Chip
IFP634	N-Channel MOSFET 250 V; 0.450 Ω - 8 A	Chip
IFF634		Chip
IFP730	N-Channel MOSFET 400 V; 0.950 Ω - 6 A	TO-220/3
IFF730		TO-220FP
IFP740	N-Channel MOSFET 400 V; 0.550 Ω - 10 A	TO-220/3
IFF740		TO-220FP
IFP830	N-Channel MOSFET 500 V; 1.400 Ω - 5 A	TO-220/3
IFF830		TO-220FP
IFP840	N-Channel MOSFET 500 V; 0.850 Ω - 8 A	TO-220/3
IFF840		TO-220FP
IFP1N60	N-Channel MOSFET 600 V; 12.000 Ω - 0,9 A	TO-220/3
IFU1N60		I-PAK
IFD1N60		D-PAK
IFU2N60	N-Channel MOSFET 600 V; 5.0 Ω -1,8 A	I-PAK
IFD2N60		D-PAK
IFP2N60	N-Channel MOSFET 600 V; 5.0 Ω - 2 A	TO-220/3
IFF2N60		TO-220FP
IFP4N60	N-Channel MOSFET 600 V; 2.5 Ω - 4.0 A	TO-220/3
IFF4N60		TO-220FP
IFP7N60	N-Channel MOSFET 600 V; 1.2 Ω - 7 A	TO-220/3
IFF7N60		TO-220FP
IFP10N60	N-Channel MOSFET 600 V; 0.8 Ω - 10 A	Chip
IFF10N60		Chip
IFP12N60	N-Channel MOSFET 600 V; 0.7 Ω - 12 A	Chip
IFF12N60		Chip
IFU1N65	N-Channel MOSFET 650 V; 13.0 Ω - 1 A	Chip
IFD1N65		Chip
IFU2N65		Chip
IFD2N65	N-Channel MOSFET 650 V; 5.5 Ω - 2 A	Chip
IFP2N65		Chip
IFF2N65		Chip
IFP4N65	N-Channel MOSFET 650 V; 2.7 Ω - 4 A	Chip
IFF4N65		Chip
IFP7N65	N-Channel MOSFET 650 V; 1.3 Ω - 7 A	Chip
IFF7N65		Chip
IFP10N65	N-Channel MOSFET 650 V; 0.85 Ω - 10 A	Chip
IFF10N65		Chip
IFF12N65	N-Channel MOSFET 650 V; 0.8 Ω - 12 A	Chip
IFF12N65		Chip

• Unijunction Transistors

Part	Pin to Pin Compatibility	P max, W	Vb, b2 max, V	le pulse, A	le rev, μ A	Veb sat, V	η	Package
2N2646	2N2646	0.3	35	2.0	12.0	0.7...3.5	0.56...0.75	Case 22A-01
2N2647	2N2647							
2N4870	2N4870	0.3	35	1.5	1.0	0.7...2.5	0.56...0.75	TO-92
2N4871	2N4871							

Foundry business

- Semiconductor IC and Discrete Devices Manufacturing under the Customer's Design (delivery on base of Probe Test)
- Semiconductor IC and Discrete Devices Manufacturing under the Customer's Design (delivery on the base of PCM)
- Wafer Fab Service – execution of separate Process Flow Steps or blocks (Metal sputtering, film deposition, EPI growing, back grinding, wafers testing and so on)
- Raw Si substrate and EPI manufacturing under the Customer's Spec

Production Capacity available for Foundry Business:

- 8" wafer production line (0.5-0.35 μ m design rule)
- 6" wafer production line (0.8-1.2 μ m design rule)
- 4" wafer production line (1.2-3.0 μ m design rule)

Basic Process available:

a) Integrated Circuits:

- DMOS
- CMOS
- BiCMOS
- CDMOS
- BiCDMOS
- Bipolar

b) Discrete devices:

- D-MOS (≤ 1000 V)
- Multi-Epi (≤ 700 V)
- Bipolar
- Process for high frequency devices (≤ 300 V)

Si substrates and EPI, manufacturing and delivery (according to the Customer's Spec):

- 4", 6", 8" wafers
- EPI parameter range: $d=0.5\dots 80$ μ m, $\rho=0.1\dots 50$ $\Omega \cdot$ cm

Mask making:

- Mask Set manufacturing under the Customer's Spec (GDS II and DB):
 - a) for contact lithography
 - b) for Projection Reduction (Stepper lithography) (1:1/1:5/1:10)
- Pellicles manufacturing under the Customer's Spec
- Manufacture of photomasks with P/R coatings (glass and quartz substrates)

Contract management

Packaging:

- IC and Discrete Devices assembly (packaging) with Testing
- IC and Discrete Devices assembly (packaging) without Testing
- IC and Discrete Devices assembly (packaging) with Testing and Marking

Packages Types available:

a) Integrated Circuits:

- SOP (8-28 LD)
- DIP (8-40 LD)
- SHRINK DIP (30, 42, 52, 56 LD)
- QFP (48, 64, 100 LD)
- SIL (3, 8, 13, 17 LD)
- SIP (9LD)
- TO -220 (3, 5, 7 LD)
- SOT -23, SOT -143, SOT -223

b) Discrete devices:

- Case 22A-01
- DO-34, DO-35
- MELF, miniMELF
- SOT -23, SOT -143, SOT -223
- ISOWATT
- TO-18, TO-39, TO-72, TO-92, TO-126,
- TO-218, TO-220
- KD-17
- DPAK, D2PAK

Fabless service

IC and discrete devices design:

- IC Design according to the Customer's Data Sheet (Spec) and Process Development
- Discrete Devices Design according to the Customer's Data Sheet (Spec) and Process development
- GDS II and Tape out
- Engineering Consulting service
- Reengineering

Supplementary services

Design of electronic devices/ instruments and manufacture of samples as per Customer's requirements:

- Design and manufacture of PCB
- Design and manufacture of LCD:
 - TN-type ("twist") for electronic clock/watch, calculators, etc,
 - STN-type ("supertwist") for general purposes

Other services:

- Design and manufacture of quartz tooling and accessories, tools
- Design and manufacture of molds, punches, casting/transfer molds
- Marking blocks manufacturing
- High-precision stamping of lead frames for IC manufacturing